

Report No.: 2022

Test Time: 2022-06-22 16:54

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: LED

Lamp Description: 3000K

Luminous Width (mm): 60

Voltage: 119.7 V

Power: 63.34 W

Luminaire Description: MX482H-60W-4FT

Luminous Length (mm): 1200

Luminous Height (mm): 120

Current: 0.535 A

Power Factor: 0.989

Photometric Results

CIE Class: Direct

Measurement Flux: 8225.7 lm

Downward Ratio: 92%

Field Angle: H159.9 V216.8

Luminaire Efficacy Rating (LER): 130

Max. Intensity: 2407.31 cd

Total Rated Lamp Lumens: 8225.7 lm

Efficiency: 100%


Upward Ratio: 8%

Beam Angle: H107.6 V129.1


Central Intensity: 2406.52 cd

Pos of Max. Intensity: H180 V1

Picture Of Luminaire



Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 118.3° Unit: cd

— C0-C180 — C90-C270 — G1

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0



Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 30.0
Test Lab:
Test Type: TYPE C
Temperature: 23
Operator: HUA

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 8.580 m
Humidity: 88
Inspector:

Luminous Intensity Distribution Curve(cd / klm)



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95	92
1	105	100	95	90	102	97	92	88	91	87	84	86	83	80	81	78	76	73
2	95	86	78	72	91	83	76	71	78	73	68	74	69	65	70	66	62	60
3	86	75	66	59	83	73	65	58	69	62	56	65	59	54	61	56	52	50
4	79	66	57	50	76	64	56	49	61	53	47	57	51	46	54	49	45	42
5	72	59	49	43	70	57	48	42	54	47	41	51	45	40	49	43	39	36
6	67	53	44	37	64	51	43	36	49	41	36	46	40	35	44	38	34	31
7	62	48	39	32	59	47	38	32	44	37	31	42	36	31	40	34	30	28
8	57	44	35	29	55	43	34	29	41	33	28	39	32	27	37	31	27	25
9	54	40	32	26	52	39	31	26	37	30	25	36	29	25	34	28	24	22
10	50	37	29	23	49	36	28	23	34	28	23	33	27	22	32	26	22	20

Spacing Criteria (0-180): 1.22

Spacing Criteria (90-270): 1.29

Spacing Criteria (Diagonal): 1.38



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Isocandela (rectangle)



Imax (100%): 2407 cd

(10%): 241 cd	(16%): 385 cd
(25%): 602 cd	(40%): 963 cd
(63%): 1517 cd	(100%): 2407 cd

C Plane (°): 0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°): 0.0-180.0: 1.0


Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Isocandela (sphere)



I_{max} (100%): 2407 cd

(10%): 241 cd	(16%): 385 cd
(25%): 602 cd	(40%): 963 cd
(63%): 1517 cd	(100%): 2407 cd

C Plane (°): 0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°): 0.0-180.0: 1.0


Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

IsoLux Plot



Mounting Height: 3.3m Max Lux(100%): 221.0 lx

(1%): 2.2 lx	(2%): 4.4 lx
(5%): 11.0 lx	(10%): 22.1 lx
(20%): 44.2 lx	

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Illuminance at a Distance



C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 2406.5 lx

— (1%): 24.1 lx	— (2%): 48.1 lx
— (5%): 120.3 lx	— (10%): 240.7 lx
— (20%): 481.3 lx	

C Plane (°):0.0-360.0: 30.0
 Test Lab:
 Test Type: TYPE C
 Temperature: 23
 Operator: HUA

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-1600L
 Distance: 8.580 m
 Humidity: 88
 Inspector:




Area Flux Table

Unit: lm

		Vertical plane																		Horizontal plane																	
		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90																	
Vertical plane	Flux(E)	0.0	38.5	130.8	259.6	410.2	569.7	714.8	821.5	880.4	876.2	809.6	697.6	550.9	393.4	247.3	123.9	37.3	0.0	7562	Flux(T)	Flux(E)															
	Flux(T)	6.1	46.3	133.7	259.6	410.2	569.7	714.8	821.5	880.4	876.2	809.6	697.6	550.9	393.4	247.5	128.2	45.3	6.2	7597																	
	90	0.2	1.3	3.2	5.8	8.7	12.0	14.7	16.5	17.8	17.7	16.2	14.3	11.5	8.2	5.3	2.9	1.2	0.2	157.7			151.4														
	80	0.3	1.6	4.2	7.9	12.3	16.9	21.0	23.8	25.6	25.4	23.4	20.4	16.2	11.6	7.3	3.9	1.5	0.3	223.4			220.1														
	70	0.3	2.0	5.5	10.4	16.3	22.5	28.1	32.0	34.4	34.2	31.5	27.4	21.7	15.5	9.7	5.1	1.9	0.3	298.5			296.5														
	60	0.3	2.4	6.7	12.9	20.3	28.0	35.1	40.1	43.0	42.8	39.6	34.3	27.1	19.4	12.2	6.4	2.3	0.3	373.1			371.6														
	50	0.4	2.7	7.9	15.3	24.0	33.1	41.5	47.6	51.0	50.8	47.0	40.6	32.2	23.0	14.5	7.6	2.7	0.4	442.4			441.3														
	40	0.4	3.1	9.0	17.4	27.2	37.7	47.2	54.4	58.2	58.0	53.8	46.3	36.6	26.2	16.7	8.6	3.0	0.4	504.1			503.2														
	30	0.4	3.3	9.8	19.1	30.0	41.4	51.9	60.0	64.3	64.1	59.4	51.0	40.3	29.0	18.4	9.5	3.3	0.4	555.6			554.8														
	20	0.4	3.4	10.3	20.2	32.0	44.3	55.4	64.0	68.7	68.5	63.6	54.6	43.2	31.1	19.6	10.0	3.4	0.4	593.2			592.4														
10	0.4	3.4	10.4	20.7	33.0	46.0	57.8	66.7	71.3	71.3	66.1	56.7	44.8	32.0	20.1	10.2	3.5	0.4	614.7	613.9																	
0	0.4	3.4	10.4	20.7	33.1	46.2	58.2	67.3	71.9	71.2	66.0	56.7	44.8	32.1	20.1	10.2	3.5	0.4	616.7	615.9																	
-10	0.4	3.4	10.3	20.3	32.3	44.9	56.4	65.2	69.7	69.2	63.9	54.7	43.3	31.1	19.6	10.0	3.4	0.4	598.8	598.0																	
-20	0.4	3.3	9.8	19.2	30.4	42.2	53.1	61.4	65.7	65.2	60.3	51.6	40.5	29.1	18.4	9.5	3.3	0.4	563.9	563.1																	
-30	0.4	3.1	9.0	17.5	27.7	38.5	48.5	56.0	59.9	59.5	55.0	47.2	37.0	26.3	16.7	8.6	3.0	0.4	514.3	513.3																	
-40	0.4	2.7	7.9	15.4	24.4	34.0	42.8	49.2	52.8	52.5	48.4	41.7	32.7	23.2	14.5	7.6	2.7	0.4	453.2	452.1																	
-50	0.3	2.3	6.7	13.0	20.6	28.8	36.3	41.6	44.7	44.5	41.0	35.4	27.8	19.6	12.2	6.3	2.3	0.3	383.8	382.4																	
-60	0.3	1.9	5.4	10.4	16.6	23.2	29.2	33.4	36.0	35.8	32.9	28.5	22.4	15.8	9.7	5.1	1.9	0.3	308.6	306.5																	
-70	0.3	1.5	4.1	7.9	12.5	17.5	21.9	24.9	26.9	26.8	24.5	21.4	16.9	11.9	7.4	3.9	1.5	0.3	232.0	228.6																	
-80	0.2	1.2	3.1	5.7	8.9	12.4	15.3	17.2	18.6	18.5	17.0	14.9	11.9	8.4	5.3	2.9	1.2	0.2	163.0	156.6																	
-90	0.2	1.2	3.1	5.7	8.9	12.4	15.3	17.2	18.6	18.5	17.0	14.9	11.9	8.4	5.3	2.9	1.2	0.2	163.0	156.6																	

The Average Illuminance Effective Figure



C Plane (°): 0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°): 0.0-180.0: 1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	12.7	14.2	13.2	14.7	15.2	11.8	13.4	12.3	13.8	14.3
3H	14.5	15.9	15.0	16.4	16.9	13.7	15.1	14.2	15.5	16.1
4H	15.1	16.5	15.7	17.0	17.5	14.4	15.8	14.9	16.3	16.8
6H	15.6	16.8	16.1	17.3	17.9	15.1	16.3	15.6	16.8	17.4
8H	15.7	16.9	16.3	17.5	18.0	15.4	16.6	15.9	17.1	17.7
12H	15.8	17.0	16.4	17.5	18.1	15.7	16.8	16.2	17.3	17.9
X=4H Y=2H	13.1	14.5	13.6	14.9	15.5	12.4	13.8	12.9	14.3	14.8
3H	15.1	16.2	15.6	16.7	17.3	14.5	15.6	15.0	16.2	16.7
4H	15.8	16.9	16.4	17.4	18.0	15.4	16.4	15.9	17.0	17.6
6H	16.4	17.3	17.0	17.9	18.5	16.2	17.1	16.8	17.7	18.3
8H	16.6	17.4	17.2	18.0	18.7	16.6	17.5	17.2	18.0	18.7
12H	16.7	17.5	17.3	18.1	18.7	16.9	17.7	17.5	18.3	19.0
X=8H Y=4H	16.1	16.9	16.6	17.5	18.1	15.7	16.6	16.3	17.1	17.8
6H	16.8	17.5	17.4	18.1	18.8	16.7	17.4	17.3	18.1	18.7
8H	17.0	17.7	17.6	18.3	19.0	17.2	17.8	17.8	18.5	19.1
12H	17.2	17.8	17.9	18.4	19.2	17.7	18.3	18.3	18.9	19.6
X=12H Y=4H	16.1	16.9	16.7	17.5	18.1	15.8	16.5	16.3	17.1	17.8
6H	16.9	17.5	17.5	18.1	18.8	16.8	17.5	17.4	18.0	18.7
8H	17.2	17.8	17.8	18.4	19.1	17.3	17.9	17.9	18.5	19.3

Calculate in accordance with CIE 190:2010

C Plane (°): 0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA


Gamma Plane (°): 0.0-180.0: 1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM


ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	3755	45.7
FL (0°-30°)	919	11.2
FM (30°-60°)	1781	21.7
FH (60°-80°)	836	10.2
FVH (80°-90°)	219	2.7
BACK LIGHT	3843	46.7
BL (0°-30°)	930	11.3
BM (30°-60°)	1823	22.2
BH (60°-80°)	862	10.5
BVH (80°-90°)	227	2.8
UP LIGHT	628	7.6
UL (90°-100°)	275	3.3
UH (100°-180°)	353	4.3
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U5 G2
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B2 U5 G1

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.52	0.61	0.68	0.74	0.81	0.86	0.90	0.95	0.98
	0.30		0.43	0.53	0.61	0.66	0.74	0.80	0.84	0.90	0.94
	0.20		0.38	0.47	0.54	0.60	0.68	0.75	0.79	0.86	0.90
0.50	0.50	0.20	0.49	0.58	0.65	0.70	0.77	0.81	0.85	0.89	0.92
	0.30		0.42	0.51	0.58	0.63	0.71	0.76	0.80	0.85	0.89
	0.20		0.37	0.46	0.53	0.58	0.66	0.72	0.76	0.82	0.86
0.30	0.50	0.20	0.47	0.56	0.62	0.66	0.73	0.77	0.80	0.84	0.87
	0.30		0.41	0.50	0.56	0.61	0.68	0.73	0.76	0.81	0.84
	0.20		0.36	0.45	0.51	0.56	0.64	0.69	0.73	0.78	0.82
0.00	0.00	0.00	0.33	0.41	0.47	0.52	0.59	0.64	0.67	0.72	0.75
Rating:63W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.25									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	1.03	0.87	0.75	0.66	0.54	0.45	0.39	0.31	0.26	
	0.30		0.86	0.74	0.65	0.59	0.49	0.42	0.37	0.29	0.25	
	0.20		0.74	0.65	0.58	0.53	0.44	0.39	0.34	0.28	0.24	
0.50	0.50	0.20	0.98	0.82	0.71	0.63	0.51	0.46	0.37	0.30	0.25	
	0.30		0.83	0.71	0.63	0.56	0.47	0.40	0.35	0.28	0.24	
	0.20		0.72	0.63	0.56	0.51	0.43	0.37	0.33	0.27	0.23	
0.30	0.50	0.20	0.94	0.78	0.67	0.59	0.48	0.41	0.35	0.28	0.23	
	0.30		0.80	0.69	0.60	0.54	0.44	0.38	0.33	0.27	0.22	
	0.20		0.70	0.61	0.54	0.49	0.41	0.36	0.31	0.25	0.22	
0.00	0.00	0.00	0.60	0.51	0.45	0.40	0.34	0.29	0.25	0.20	0.17	
Rating:63W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.25								
Room Reflectance			Room Index(RI)								
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.24	0.25	0.26	0.27	0.28	0.28	0.29	0.29	0.29
	0.30		0.17	0.18	0.20	0.21	0.22	0.23	0.24	0.25	0.26
	0.20		0.12	0.13	0.15	0.16	0.18	0.19	0.21	0.22	0.23
0.50	0.50	0.20	0.23	0.24	0.25	0.26	0.27	0.27	0.27	0.28	0.28
	0.30		0.17	0.18	0.19	0.20	0.22	0.23	0.23	0.25	0.25
	0.20		0.12	0.13	0.15	0.16	0.17	0.19	0.20	0.22	0.23
0.30	0.50	0.20	0.22	0.24	0.24	0.25	0.26	0.26	0.26	0.27	0.27
	0.30		0.16	0.18	0.19	0.20	0.21	0.22	0.23	0.24	0.24
	0.20		0.12	0.13	0.14	0.15	0.17	0.18	0.19	0.21	0.22
0.00	0.00	0.00	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08
Rating:63W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980											

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2386.6	2.3	2.3	0.03	0.03
1.0-2.0	2385.7	6.8	9.1	0.08	0.11
2.0-3.0	2383.9	11.4	20.5	0.14	0.25
3.0-4.0	2381.2	15.9	36.5	0.19	0.44
4.0-5.0	2377.6	20.5	56.9	0.25	0.69
5.0-6.0	2373.1	24.9	81.9	0.30	1.00
6.0-7.0	2367.7	29.4	111.3	0.36	1.35
7.0-8.0	2361.4	33.8	145.1	0.41	1.76
8.0-9.0	2354.2	38.2	183.2	0.46	2.23
9.0-10.0	2346.1	42.5	225.7	0.52	2.74
10.0-11.0	2337.3	46.7	272.4	0.57	3.31
11.0-12.0	2327.6	50.9	323.3	0.62	3.93
12.0-13.0	2317.1	55.0	378.3	0.67	4.60
13.0-14.0	2305.7	59.0	437.3	0.72	5.32
14.0-15.0	2293.6	63.0	500.3	0.77	6.08
15.0-16.0	2280.7	66.8	567.1	0.81	6.89
16.0-17.0	2266.8	70.6	637.7	0.86	7.75
17.0-18.0	2252.3	74.3	712.0	0.90	8.66
18.0-19.0	2237.1	77.8	789.8	0.95	9.60
19.0-20.0	2221.2	81.3	871.1	0.99	10.59
20.0-21.0	2204.5	84.7	955.8	1.03	11.62
21.0-22.0	2187.1	87.9	1043.7	1.07	12.69
22.0-23.0	2169.0	91.0	1134.7	1.11	13.79
23.0-24.0	2150.2	94.0	1228.7	1.14	14.94
24.0-25.0	2130.8	96.9	1325.7	1.18	16.12
25.0-26.0	2110.9	99.7	1425.3	1.21	17.33
26.0-27.0	2090.2	102.3	1527.6	1.24	18.57
27.0-28.0	2068.9	104.8	1632.3	1.27	19.84
28.0-29.0	2047.1	107.1	1739.5	1.30	21.15
29.0-30.0	2024.5	109.3	1848.8	1.33	22.48
30.0-31.0	2001.4	111.4	1960.2	1.35	23.83
31.0-32.0	1977.8	113.3	2073.5	1.38	25.21
32.0-33.0	1953.8	115.1	2188.6	1.40	26.61
33.0-34.0	1929.2	116.8	2305.4	1.42	28.03
34.0-35.0	1904.1	118.3	2423.6	1.44	29.46
35.0-36.0	1878.5	119.6	2543.3	1.45	30.92

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	1852.4	120.8	2664.1	1.47	32.39
37.0-38.0	1825.9	121.9	2786.0	1.48	33.87
38.0-39.0	1799.1	122.8	2908.8	1.49	35.36
39.0-40.0	1771.9	123.6	3032.4	1.50	36.86
40.0-41.0	1744.4	124.2	3156.6	1.51	38.38
41.0-42.0	1716.4	124.7	3281.4	1.52	39.89
42.0-43.0	1688.1	125.1	3406.4	1.52	41.41
43.0-44.0	1659.5	125.3	3531.7	1.52	42.93
44.0-45.0	1630.5	125.3	3657.0	1.52	44.46
45.0-46.0	1601.4	125.3	3782.3	1.52	45.98
46.0-47.0	1571.9	125.0	3907.3	1.52	47.50
47.0-48.0	1542.2	124.7	4032.0	1.52	49.02
48.0-49.0	1512.3	124.2	4156.2	1.51	50.53
49.0-50.0	1482.1	123.6	4279.8	1.50	52.03
50.0-51.0	1451.6	122.8	4402.6	1.49	53.52
51.0-52.0	1421.0	122.0	4524.6	1.48	55.01
52.0-53.0	1390.2	120.9	4645.5	1.47	56.48
53.0-54.0	1359.1	119.8	4765.3	1.46	57.93
54.0-55.0	1327.7	118.5	4883.9	1.44	59.37
55.0-56.0	1296.1	117.1	5001.0	1.42	60.80
56.0-57.0	1264.6	115.6	5116.6	1.41	62.20
57.0-58.0	1232.9	114.0	5230.7	1.39	63.59
58.0-59.0	1201.1	112.3	5343.0	1.37	64.95
59.0-60.0	1169.2	110.5	5453.4	1.34	66.30
60.0-61.0	1137.2	108.5	5562.0	1.32	67.62
61.0-62.0	1105.2	106.5	5668.5	1.29	68.91
62.0-63.0	1072.9	104.4	5772.8	1.27	70.18
63.0-64.0	1040.7	102.1	5875.0	1.24	71.42
64.0-65.0	1008.5	99.8	5974.8	1.21	72.64
65.0-66.0	976.3	97.4	6072.2	1.18	73.82
66.0-67.0	944.1	94.9	6167.1	1.15	74.97
67.0-68.0	912.1	92.4	6259.6	1.12	76.10
68.0-69.0	880.2	89.8	6349.4	1.09	77.19
69.0-70.0	848.2	87.1	6436.5	1.06	78.25
70.0-71.0	816.3	84.4	6520.9	1.03	79.27
71.0-72.0	784.8	81.6	6602.5	0.99	80.27

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	753.4	78.8	6681.3	0.96	81.22
73.0-74.0	722.0	75.9	6757.2	0.92	82.15
74.0-75.0	691.0	73.0	6830.2	0.89	83.03
75.0-76.0	660.6	70.1	6900.3	0.85	83.89
76.0-77.0	630.5	67.2	6967.6	0.82	84.70
77.0-78.0	600.8	64.3	7031.9	0.78	85.49
78.0-79.0	571.7	61.4	7093.3	0.75	86.23
79.0-80.0	543.3	58.6	7151.9	0.71	86.95
80.0-81.0	515.6	55.8	7207.7	0.68	87.62
81.0-82.0	488.6	53.0	7260.7	0.64	88.27
82.0-83.0	462.6	50.3	7311.0	0.61	88.88
83.0-84.0	437.8	47.7	7358.7	0.58	89.46
84.0-85.0	414.3	45.2	7403.9	0.55	90.01
85.0-86.0	392.1	42.9	7446.8	0.52	90.53
86.0-87.0	371.3	40.6	7487.4	0.49	91.02
87.0-88.0	352.3	38.6	7526.0	0.47	91.49
88.0-89.0	334.8	36.7	7562.7	0.45	91.94
89.0-90.0	319.0	35.0	7597.7	0.43	92.36
90.0-91.0	304.7	33.4	7631.1	0.41	92.77
91.0-92.0	291.5	32.0	7663.0	0.39	93.16
92.0-93.0	278.9	30.6	7693.6	0.37	93.53
93.0-94.0	266.9	29.2	7722.8	0.36	93.89
94.0-95.0	255.3	27.9	7750.7	0.34	94.23
95.0-96.0	244.3	26.7	7777.4	0.32	94.55
96.0-97.0	233.7	25.5	7802.8	0.31	94.86
97.0-98.0	223.3	24.3	7827.1	0.30	95.15
98.0-99.0	213.2	23.1	7850.3	0.28	95.44
99.0-100.0	203.5	22.0	7872.3	0.27	95.70
100.0-101.0	194.0	20.9	7893.2	0.25	95.96
101.0-102.0	184.9	19.9	7913.1	0.24	96.20
102.0-103.0	176.1	18.9	7931.9	0.23	96.43
103.0-104.0	167.6	17.9	7949.8	0.22	96.65
104.0-105.0	158.8	16.9	7966.6	0.20	96.85
105.0-106.0	150.0	15.9	7982.5	0.19	97.04
106.0-107.0	141.7	14.9	7997.4	0.18	97.22
107.0-108.0	133.4	13.9	8011.3	0.17	97.39

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	125.4	13.0	8024.4	0.16	97.55
109.0-110.0	118.0	12.2	8036.6	0.15	97.70
110.0-111.0	111.1	11.4	8048.0	0.14	97.84
111.0-112.0	104.7	10.7	8058.7	0.13	97.97
112.0-113.0	99.1	10.0	8068.7	0.12	98.09
113.0-114.0	93.7	9.4	8078.1	0.11	98.21
114.0-115.0	88.7	8.8	8087.0	0.11	98.31
115.0-116.0	83.8	8.3	8095.3	0.10	98.41
116.0-117.0	79.3	7.8	8103.1	0.09	98.51
117.0-118.0	74.9	7.3	8110.3	0.09	98.60
118.0-119.0	70.8	6.8	8117.2	0.08	98.68
119.0-120.0	66.8	6.4	8123.5	0.08	98.76
120.0-121.0	63.0	6.0	8129.5	0.07	98.83
121.0-122.0	59.5	5.6	8135.1	0.07	98.90
122.0-123.0	56.2	5.2	8140.3	0.06	98.96
123.0-124.0	53.1	4.9	8145.1	0.06	99.02
124.0-125.0	50.2	4.5	8149.7	0.06	99.08
125.0-126.0	47.4	4.2	8153.9	0.05	99.13
126.0-127.0	44.7	3.9	8157.8	0.05	99.17
127.0-128.0	42.2	3.7	8161.5	0.04	99.22
128.0-129.0	39.7	3.4	8164.9	0.04	99.26
129.0-130.0	37.5	3.2	8168.1	0.04	99.30
130.0-131.0	35.4	2.9	8171.0	0.04	99.34
131.0-132.0	33.4	2.7	8173.8	0.03	99.37
132.0-133.0	31.5	2.5	8176.3	0.03	99.40
133.0-134.0	29.9	2.4	8178.7	0.03	99.43
134.0-135.0	28.4	2.2	8180.9	0.03	99.46
135.0-136.0	27.0	2.1	8183.0	0.03	99.48
136.0-137.0	25.9	2.0	8184.9	0.02	99.50
137.0-138.0	25.1	1.9	8186.8	0.02	99.53
138.0-139.0	24.6	1.8	8188.6	0.02	99.55
139.0-140.0	24.1	1.7	8190.3	0.02	99.57
140.0-141.0	23.8	1.7	8192.0	0.02	99.59
141.0-142.0	23.6	1.6	8193.6	0.02	99.61
142.0-143.0	23.5	1.6	8195.1	0.02	99.63
143.0-144.0	23.5	1.5	8196.7	0.02	99.65

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	23.5	1.5	8198.2	0.02	99.67
145.0-146.0	23.5	1.5	8199.6	0.02	99.68
146.0-147.0	23.6	1.4	8201.1	0.02	99.70
147.0-148.0	23.6	1.4	8202.5	0.02	99.72
148.0-149.0	23.7	1.4	8203.8	0.02	99.73
149.0-150.0	23.8	1.3	8205.1	0.02	99.75
150.0-151.0	23.8	1.3	8206.4	0.02	99.77
151.0-152.0	23.9	1.3	8207.7	0.02	99.78
152.0-153.0	23.9	1.2	8208.9	0.01	99.80
153.0-154.0	24.0	1.2	8210.1	0.01	99.81
154.0-155.0	24.1	1.1	8211.2	0.01	99.82
155.0-156.0	24.1	1.1	8212.3	0.01	99.84
156.0-157.0	24.2	1.1	8213.3	0.01	99.85
157.0-158.0	24.2	1.0	8214.4	0.01	99.86
158.0-159.0	24.3	1.0	8215.3	0.01	99.87
159.0-160.0	24.4	0.9	8216.3	0.01	99.89
160.0-161.0	24.5	0.9	8217.2	0.01	99.90
161.0-162.0	24.5	0.9	8218.0	0.01	99.91
162.0-163.0	24.6	0.8	8218.8	0.01	99.92
163.0-164.0	24.7	0.8	8219.6	0.01	99.93
164.0-165.0	24.8	0.7	8220.3	0.01	99.93
165.0-166.0	24.8	0.7	8221.0	0.01	99.94
166.0-167.0	24.9	0.6	8221.7	0.01	99.95
167.0-168.0	25.0	0.6	8222.2	0.01	99.96
168.0-169.0	25.1	0.5	8222.8	0.01	99.96
169.0-170.0	25.2	0.5	8223.3	0.01	99.97
170.0-171.0	25.2	0.5	8223.8	0.01	99.98
171.0-172.0	25.3	0.4	8224.2	0.00	99.98
172.0-173.0	25.3	0.4	8224.5	0.00	99.99
173.0-174.0	25.4	0.3	8224.8	0.00	99.99
174.0-175.0	25.4	0.3	8225.1	0.00	99.99
175.0-176.0	25.5	0.2	8225.3	0.00	100.00
176.0-177.0	25.5	0.2	8225.5	0.00	100.00
177.0-178.0	25.6	0.1	8225.6	0.00	100.00
178.0-179.0	25.7	0.1	8225.7	0.00	100.00
179.0-180.0	25.7	0.0	8225.7	0.00	100.00

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G0.0	2406.5	2395.4	2387.8	2382.1	2376.9	2372.1	2406.5	2395.4	2387.8	2382.1
G1.0	2404.8	2393.3	2386.0	2380.6	2376.1	2372.1	2407.3	2396.5	2389.0	2382.7
G2.0	2402.0	2390.2	2383.2	2378.4	2374.6	2371.2	2407.0	2396.6	2389.3	2382.6
G3.0	2398.1	2386.0	2379.5	2375.4	2372.1	2369.3	2405.6	2395.8	2388.7	2381.7
G4.0	2393.3	2381.1	2375.2	2371.8	2369.1	2366.4	2403.2	2394.0	2387.3	2380.1
G5.0	2387.1	2375.1	2369.9	2367.3	2364.8	2362.5	2399.7	2391.2	2385.0	2377.7
G6.0	2380.1	2368.4	2363.8	2362.2	2360.0	2357.7	2395.2	2387.4	2381.9	2374.5
G7.0	2372.1	2360.4	2357.0	2356.1	2354.3	2351.9	2389.5	2382.6	2378.1	2370.8
G8.0	2363.1	2351.6	2349.4	2349.5	2347.9	2345.2	2382.8	2376.8	2373.2	2365.9
G9.0	2353.2	2341.6	2340.7	2342.0	2340.4	2337.5	2375.2	2370.1	2367.6	2360.5
G10.0	2342.4	2331.3	2331.4	2334.1	2332.3	2329.1	2366.2	2362.4	2361.4	2354.5
G11.0	2330.2	2319.2	2321.4	2325.3	2323.6	2319.6	2356.9	2353.8	2354.1	2347.8
G12.0	2317.6	2307.3	2310.8	2315.8	2314.0	2309.5	2345.9	2344.3	2345.9	2340.0
G13.0	2303.8	2294.0	2299.3	2305.6	2303.4	2298.2	2334.6	2334.1	2337.3	2331.7
G14.0	2289.1	2279.9	2287.4	2294.9	2292.6	2285.8	2321.7	2322.0	2327.8	2322.8
G15.0	2273.4	2264.9	2274.2	2283.7	2281.0	2272.8	2308.1	2310.4	2317.5	2313.1
G16.0	2257.2	2249.3	2260.9	2271.6	2268.8	2259.4	2293.2	2297.1	2306.2	2302.7
G17.0	2239.6	2232.5	2246.8	2258.8	2255.1	2243.9	2277.2	2282.1	2294.4	2291.5
G18.0	2221.6	2215.3	2232.0	2245.7	2242.0	2228.8	2260.9	2267.7	2281.8	2280.1
G19.0	2202.6	2196.9	2216.6	2232.1	2227.3	2212.6	2243.3	2251.7	2268.4	2267.8
G20.0	2182.6	2178.5	2200.2	2217.9	2212.0	2195.2	2225.3	2235.3	2254.7	2254.9
G21.0	2162.1	2158.6	2183.6	2203.3	2196.5	2177.5	2205.6	2217.8	2239.8	2241.6
G22.0	2141.0	2138.6	2166.2	2187.7	2180.4	2159.1	2185.6	2198.7	2224.9	2227.7
G23.0	2119.2	2117.3	2147.7	2171.4	2163.3	2140.0	2164.8	2179.6	2208.3	2212.6
G24.0	2096.6	2095.8	2129.9	2154.6	2145.5	2119.6	2142.5	2159.7	2192.2	2197.8
G25.0	2073.2	2073.5	2110.9	2137.7	2127.5	2098.8	2120.0	2138.5	2174.6	2182.0
G26.0	2048.5	2050.4	2091.8	2120.4	2109.1	2077.3	2096.6	2117.5	2157.1	2166.0
G27.0	2023.7	2026.8	2071.1	2101.2	2089.8	2055.2	2072.3	2095.7	2138.1	2148.9
G28.0	1998.8	2003.2	2051.3	2082.9	2069.9	2032.4	2048.4	2072.6	2119.4	2131.3
G29.0	1972.2	1978.0	2029.5	2063.6	2049.4	2009.7	2022.2	2049.0	2100.0	2112.7
G30.0	1945.1	1952.3	2006.8	2043.4	2029.0	1985.9	1995.9	2024.8	2079.7	2094.4
G31.0	1918.7	1926.7	1985.2	2023.7	2006.6	1961.0	1968.5	2000.1	2058.9	2075.4
G32.0	1891.2	1900.6	1962.6	2002.6	1984.7	1936.0	1941.7	1974.2	2037.1	2055.7
G33.0	1862.4	1874.0	1939.6	1981.6	1962.3	1910.6	1913.5	1948.8	2015.1	2035.6
G34.0	1833.6	1846.7	1915.3	1959.9	1940.4	1884.5	1885.4	1921.6	1993.0	2014.9
G35.0	1805.6	1819.6	1891.1	1938.2	1915.7	1859.0	1854.6	1894.4	1969.3	1993.0
G36.0	1775.0	1791.3	1867.0	1915.6	1892.7	1830.6	1825.1	1867.8	1946.1	1972.2

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G37.0	1744.7	1763.3	1841.9	1892.7	1867.7	1803.5	1795.2	1839.5	1921.9	1949.4
G38.0	1714.0	1733.7	1817.1	1869.7	1842.8	1775.5	1764.0	1811.4	1897.8	1926.8
G39.0	1683.6	1705.1	1791.3	1846.6	1817.5	1748.3	1731.9	1781.7	1872.3	1904.4
G40.0	1652.2	1675.5	1765.3	1824.3	1791.4	1718.8	1700.1	1752.4	1846.4	1881.3
G41.0	1620.5	1645.5	1739.7	1801.1	1766.9	1690.3	1668.4	1721.9	1821.3	1857.4
G42.0	1588.3	1614.5	1712.8	1776.0	1741.0	1660.7	1635.6	1692.3	1795.1	1833.5
G43.0	1557.1	1585.1	1687.5	1752.6	1715.4	1630.5	1600.8	1660.9	1768.5	1809.8
G44.0	1522.5	1553.8	1660.0	1727.1	1688.3	1599.9	1568.5	1630.4	1741.8	1785.4
G45.0	1490.6	1523.0	1634.1	1702.4	1662.1	1569.0	1534.3	1598.8	1714.8	1760.0
G46.0	1456.1	1490.6	1606.7	1676.9	1635.7	1538.4	1500.4	1566.7	1687.9	1736.0
G47.0	1422.1	1460.2	1579.1	1651.7	1608.3	1507.0	1464.6	1535.1	1659.8	1709.9
G48.0	1388.7	1428.1	1551.3	1625.6	1580.8	1475.3	1430.3	1502.7	1633.4	1684.8
G49.0	1355.1	1395.9	1523.5	1600.0	1553.7	1444.2	1394.2	1469.3	1604.3	1658.9
G50.0	1320.6	1363.6	1495.4	1572.4	1525.3	1412.2	1359.2	1437.2	1577.5	1632.0
G51.0	1286.6	1331.1	1467.9	1546.4	1497.3	1380.0	1322.2	1403.3	1548.5	1605.9
G52.0	1251.5	1298.3	1439.4	1519.3	1468.8	1347.4	1287.4	1371.2	1520.3	1578.7
G53.0	1216.7	1265.9	1411.8	1493.1	1442.0	1315.3	1249.7	1336.7	1491.4	1551.3
G54.0	1180.8	1234.2	1382.2	1464.7	1413.1	1282.9	1213.3	1303.4	1462.1	1524.2
G55.0	1144.8	1200.1	1353.7	1437.8	1384.7	1250.4	1175.8	1269.2	1432.5	1495.6
G56.0	1109.4	1167.5	1324.4	1409.6	1354.8	1216.4	1139.0	1235.6	1403.5	1468.6
G57.0	1074.8	1135.1	1295.7	1381.8	1326.7	1184.7	1099.7	1199.9	1373.9	1439.6
G58.0	1037.6	1102.2	1266.3	1352.7	1295.9	1151.1	1063.7	1166.5	1343.5	1411.1
G59.0	1002.0	1069.5	1237.5	1324.1	1267.8	1119.7	1024.9	1132.5	1313.6	1382.3
G60.0	965.4	1036.8	1207.3	1296.0	1238.2	1085.4	987.4	1098.4	1283.4	1353.8
G61.0	928.5	1004.7	1178.8	1267.6	1208.9	1053.9	949.0	1062.9	1253.8	1323.7
G62.0	891.3	972.4	1148.8	1238.1	1178.8	1021.5	909.4	1030.3	1222.6	1294.1
G63.0	854.8	939.4	1118.7	1209.8	1149.3	988.4	870.5	996.4	1191.2	1264.4
G64.0	818.1	906.7	1088.6	1179.3	1119.0	956.0	832.3	963.2	1161.2	1234.4
G65.0	780.7	874.8	1059.9	1150.1	1088.7	923.9	793.3	928.7	1131.7	1204.4
G66.0	744.1	841.7	1029.9	1120.2	1059.2	889.6	754.4	895.4	1100.5	1175.0
G67.0	706.9	811.1	1000.0	1090.4	1029.1	857.2	715.6	863.0	1069.9	1144.8
G68.0	669.8	778.6	970.3	1061.5	999.0	827.3	676.8	829.3	1039.3	1113.9
G69.0	632.7	747.8	941.2	1031.7	970.4	793.1	638.7	797.9	1008.7	1083.4
G70.0	595.6	716.3	910.8	1002.7	939.0	761.9	599.0	764.4	978.0	1053.6
G71.0	559.3	685.8	881.9	972.9	910.4	729.4	560.2	731.2	947.3	1023.8
G72.0	522.4	654.1	853.0	943.1	880.5	700.0	522.4	700.4	917.2	993.3
G73.0	485.7	624.3	823.8	914.3	851.6	668.8	484.1	668.5	886.7	962.8

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 2)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G74.0	449.5	594.2	794.9	884.3	821.6	638.1	446.2	637.0	856.3	931.3
G75.0	413.8	564.6	765.8	855.2	793.3	607.1	409.0	606.2	827.2	902.0
G76.0	378.6	535.6	738.2	827.2	764.1	578.6	372.5	575.1	796.9	872.4
G77.0	343.4	506.5	709.9	797.6	736.5	548.1	336.7	545.9	767.5	843.5
G78.0	310.5	479.5	682.7	769.8	708.8	520.7	301.6	515.9	738.4	813.4
G79.0	276.9	451.8	655.9	742.0	680.9	491.5	268.2	488.3	710.3	784.4
G80.0	244.9	425.4	630.3	716.3	654.0	464.6	234.4	458.9	681.8	756.4
G81.0	213.4	399.2	604.1	689.6	627.8	437.8	203.5	432.0	653.9	728.8
G82.0	184.7	375.2	579.4	663.7	602.4	412.5	172.8	405.5	626.7	700.6
G83.0	156.9	351.6	555.1	639.8	577.3	386.4	146.1	380.6	600.2	674.5
G84.0	130.6	329.2	532.4	616.3	553.2	362.7	120.1	355.7	575.4	648.8
G85.0	107.3	308.2	510.7	593.7	530.7	339.1	97.5	333.7	551.5	623.9
G86.0	86.8	288.2	489.6	571.9	508.7	318.4	77.8	311.0	527.0	599.3
G87.0	68.6	269.5	470.0	550.7	488.3	298.3	62.5	291.5	505.0	576.6
G88.0	54.8	253.4	450.9	530.4	468.9	280.1	50.8	272.4	483.0	554.3
G89.0	44.6	237.8	433.1	510.4	449.4	262.8	43.9	255.4	463.3	533.9
G90.0	39.1	224.0	416.0	492.5	432.0	247.3	41.7	239.3	443.8	512.9
G91.0	38.0	210.7	399.4	474.9	414.6	232.9	41.1	225.4	425.1	493.8
G92.0	37.5	198.2	384.1	458.0	398.8	219.5	40.4	211.7	407.9	475.0
G93.0	37.0	186.9	368.8	441.0	382.6	207.0	39.9	199.6	390.8	456.7
G94.0	36.6	175.8	354.9	425.8	367.7	195.0	39.3	187.5	374.8	439.9
G95.0	36.2	165.4	340.1	410.1	353.1	183.3	38.8	176.8	359.6	423.2
G96.0	35.8	155.5	326.7	395.6	339.3	172.8	38.3	165.8	345.0	407.5
G97.0	35.4	145.2	313.4	381.3	325.4	162.2	38.1	155.4	330.7	391.9
G98.0	35.0	136.0	300.5	367.0	312.1	152.1	37.9	145.4	316.7	376.7
G99.0	34.5	127.4	287.6	353.0	299.1	142.3	37.9	135.9	303.2	362.4
G100.0	34.1	118.9	275.6	340.1	286.1	133.1	37.4	126.6	289.7	347.7
G101.0	33.8	110.6	263.3	326.7	273.8	124.2	36.7	118.0	276.7	334.0
G102.0	33.3	102.8	251.6	313.4	261.4	116.2	35.7	110.1	264.3	321.0
G103.0	33.0	95.8	239.7	300.9	249.4	108.0	34.9	103.0	251.9	307.9
G104.0	32.6	89.2	228.7	288.5	238.5	100.8	34.2	96.3	239.6	294.7
G105.0	32.2	82.8	217.5	276.6	226.7	93.7	33.9	89.9	222.5	282.5
G106.0	31.9	77.1	207.0	264.7	215.8	87.4	33.3	83.8	206.1	270.0
G107.0	31.5	71.3	195.8	252.7	205.0	81.3	32.6	78.1	191.8	257.6
G108.0	31.1	66.1	177.3	241.9	191.8	75.5	32.2	72.3	180.4	244.0
G109.0	30.8	60.8	164.2	230.2	177.0	69.7	31.7	66.3	171.1	232.4
G110.0	30.4	55.9	151.6	219.1	165.1	64.8	31.3	60.9	162.3	222.2

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G111.0	30.0	50.9	142.5	204.7	154.4	59.4	30.7	55.8	153.7	211.8
G112.0	29.7	46.3	135.2	193.8	146.3	54.5	30.4	51.3	145.7	201.7
G113.0	29.4	42.1	127.8	184.0	138.1	50.0	29.7	47.6	137.9	192.1
G114.0	29.1	38.6	120.8	175.0	130.3	45.9	29.2	44.3	130.8	182.9
G115.0	28.8	35.7	113.5	165.9	122.4	42.3	28.8	41.1	123.7	174.1
G116.0	28.4	33.3	107.0	157.4	115.3	39.0	28.5	38.2	116.8	165.4
G117.0	28.1	31.1	100.7	148.6	108.3	36.3	28.0	35.8	110.3	157.0
G118.0	27.8	29.5	94.6	140.5	101.6	33.8	27.6	33.3	103.9	148.7
G119.0	27.5	28.5	88.4	132.4	95.1	31.9	27.1	31.0	97.5	140.9
G120.0	27.2	27.6	82.4	124.7	88.6	30.3	26.8	29.0	91.5	133.1
G121.0	27.0	27.1	76.7	117.4	82.4	28.8	26.4	27.2	85.5	125.9
G122.0	26.7	26.8	71.1	110.1	76.6	27.9	26.0	25.8	80.1	118.7
G123.0	26.5	26.6	66.0	103.2	70.8	27.4	25.7	25.1	74.6	111.6
G124.0	26.2	26.3	60.8	96.4	65.4	27.0	25.3	24.8	69.5	104.9
G125.0	25.9	26.0	56.0	89.9	60.2	26.7	24.9	24.5	64.3	98.4
G126.0	25.7	25.7	51.5	83.6	55.4	26.3	24.6	24.2	59.9	92.0
G127.0	25.4	25.5	47.3	77.7	50.8	25.9	24.3	24.0	55.3	85.8
G128.0	25.2	25.3	43.5	71.4	46.5	25.6	24.1	23.6	51.2	79.8
G129.0	25.0	25.1	40.0	66.1	42.7	25.3	23.8	23.4	47.2	74.2
G130.0	24.8	24.9	36.9	60.6	39.2	25.1	23.6	23.1	43.5	68.8
G131.0	24.6	24.7	34.0	55.7	36.0	24.7	23.3	22.9	39.9	63.5
G132.0	24.4	24.5	31.3	51.1	32.9	24.5	23.1	22.7	36.7	58.5
G133.0	24.2	24.4	29.2	46.6	30.4	24.2	22.9	22.4	33.7	53.6
G134.0	24.1	24.1	27.6	42.6	28.4	24.0	22.6	22.2	30.8	49.2
G135.0	23.9	24.0	26.4	38.9	26.8	23.7	22.4	22.1	28.3	44.9
G136.0	23.7	23.7	25.6	35.4	25.5	23.5	22.2	21.9	26.0	41.0
G137.0	23.6	23.5	25.5	32.5	25.0	23.3	22.1	21.7	24.2	37.4
G138.0	23.5	23.3	25.5	30.4	24.9	23.1	21.9	21.5	23.4	34.2
G139.0	23.3	23.2	25.5	28.6	24.9	22.9	21.8	21.4	23.3	31.2
G140.0	23.2	23.1	25.5	27.3	24.9	22.7	21.7	21.3	23.3	28.4
G141.0	23.1	22.9	25.5	26.8	24.9	22.5	21.5	21.2	23.4	26.3
G142.0	23.1	22.9	25.6	26.7	24.9	22.4	21.5	21.2	23.4	25.3
G143.0	23.0	22.8	25.5	26.7	24.9	22.3	21.4	21.1	23.5	25.0
G144.0	23.0	22.8	25.5	26.6	24.9	22.3	21.3	21.1	23.5	25.0
G145.0	22.9	22.9	25.6	26.6	24.9	22.3	21.2	21.2	23.5	25.0
G146.0	22.9	23.0	25.6	26.5	24.9	22.3	21.2	21.4	23.6	24.9
G147.0	22.9	23.2	25.6	26.4	24.9	22.4	21.1	21.5	23.6	24.9

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0
G148.0	22.9	23.3	25.6	26.4	24.9	22.6	21.2	21.7	23.7	24.9
G149.0	22.9	23.5	25.6	26.3	24.9	22.7	21.3	21.9	23.7	24.9
G150.0	23.1	23.6	25.6	26.3	24.9	22.9	21.5	22.0	23.7	24.9
G151.0	23.2	23.7	25.6	26.1	24.9	23.0	21.7	22.2	23.8	24.9
G152.0	23.4	23.9	25.5	26.1	24.9	23.1	21.9	22.3	23.8	24.8
G153.0	23.5	24.1	25.4	26.0	24.9	23.3	22.1	22.5	23.9	24.7
G154.0	23.6	24.2	25.4	25.9	24.8	23.4	22.3	22.6	23.9	24.7
G155.0	23.8	24.3	25.3	25.9	24.9	23.6	22.5	22.8	23.9	24.7
G156.0	24.0	24.4	25.3	25.8	24.9	23.7	22.8	22.9	24.0	24.6
G157.0	24.1	24.5	25.3	25.7	24.9	23.9	22.9	23.0	24.0	24.6
G158.0	24.2	24.6	25.3	25.7	24.9	24.0	23.1	23.2	24.1	24.6
G159.0	24.3	24.7	25.2	25.6	24.9	24.1	23.3	23.3	24.1	24.6
G160.0	24.4	24.8	25.3	25.6	25.0	24.2	23.4	23.4	24.1	24.7
G161.0	24.5	24.9	25.3	25.6	25.0	24.4	23.6	23.5	24.2	24.6
G162.0	24.6	25.0	25.4	25.6	25.0	24.5	23.8	23.6	24.2	24.7
G163.0	24.8	25.1	25.5	25.5	25.1	24.6	23.9	23.7	24.2	24.7
G164.0	24.9	25.2	25.6	25.5	25.1	24.7	24.1	23.9	24.3	24.7
G165.0	25.0	25.3	25.7	25.5	25.2	24.8	24.2	24.0	24.3	24.7
G166.0	25.1	25.4	25.7	25.6	25.3	24.9	24.4	24.1	24.4	24.7
G167.0	25.3	25.4	25.8	25.6	25.4	25.0	24.6	24.2	24.4	24.7
G168.0	25.4	25.5	25.9	25.7	25.4	25.1	24.7	24.3	24.5	24.8
G169.0	25.5	25.6	25.9	25.7	25.5	25.2	24.8	24.4	24.5	24.8
G170.0	25.6	25.7	25.9	25.8	25.5	25.3	25.0	24.5	24.6	24.9
G171.0	25.7	25.7	25.9	25.9	25.6	25.4	25.1	24.6	24.6	25.0
G172.0	25.7	25.8	25.9	25.9	25.6	25.5	25.3	24.7	24.7	25.0
G173.0	25.8	25.8	25.9	26.0	25.7	25.5	25.4	24.7	24.7	25.1
G174.0	25.9	25.8	25.8	26.1	25.7	25.5	25.5	24.8	24.8	25.3
G175.0	25.9	25.9	25.8	26.1	25.7	25.5	25.7	24.9	24.8	25.3
G176.0	26.0	25.8	25.7	26.2	25.7	25.5	25.8	25.0	24.9	25.5
G177.0	26.0	25.8	25.7	26.3	25.7	25.5	25.9	25.1	25.0	25.5
G178.0	26.0	25.8	25.7	26.3	25.7	25.6	26.0	25.3	25.1	25.6
G179.0	26.0	25.7	25.7	26.2	25.7	25.5	26.1	25.5	25.4	25.9
G180.0	25.9	25.6	25.5	26.1	25.5	25.5	26.1	25.7	25.6	26.1

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 5)

Unit: cd

G\c	C300.0	C330.0	C360.0							
G0.0	2376.9	2372.1	2406.5							
G1.0	2376.8	2371.1	2404.8							
G2.0	2375.9	2369.2	2402.0							
G3.0	2374.2	2366.3	2398.1							
G4.0	2371.6	2362.4	2393.3							
G5.0	2368.3	2357.6	2387.1							
G6.0	2364.1	2351.8	2380.1							
G7.0	2359.0	2345.1	2372.1							
G8.0	2353.0	2337.4	2363.1							
G9.0	2346.3	2328.8	2353.2							
G10.0	2339.1	2319.3	2342.4							
G11.0	2330.6	2309.0	2330.2							
G12.0	2321.8	2297.6	2317.6							
G13.0	2311.9	2285.4	2303.8							
G14.0	2301.6	2272.5	2289.1							
G15.0	2289.9	2258.7	2273.4							
G16.0	2278.2	2243.6	2257.2							
G17.0	2265.5	2228.0	2239.6							
G18.0	2252.1	2211.5	2221.6							
G19.0	2237.3	2194.2	2202.6							
G20.0	2223.5	2176.6	2182.6							
G21.0	2207.7	2157.3	2162.1							
G22.0	2191.8	2137.9	2141.0							
G23.0	2174.8	2118.1	2119.2							
G24.0	2157.7	2096.3	2096.6							
G25.0	2139.8	2075.1	2073.2							
G26.0	2122.2	2052.7	2048.5							
G27.0	2102.8	2029.0	2023.7							
G28.0	2083.0	2005.8	1998.8							
G29.0	2062.8	1981.9	1972.2							
G30.0	2042.1	1957.2	1945.1							
G31.0	2020.9	1931.3	1918.7							
G32.0	1999.2	1905.5	1891.2							
G33.0	1976.4	1879.1	1862.4							
G34.0	1954.6	1851.5	1833.6							
G35.0	1931.1	1824.5	1805.6							
G36.0	1907.3	1797.1	1775.0							

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 6)

Unit: cd

G/C	C300.0	C330.0	C360.0							
G37.0	1882.4	1768.1	1744.7							
G38.0	1858.2	1739.8	1714.0							
G39.0	1833.1	1711.4	1683.6							
G40.0	1808.3	1682.7	1652.2							
G41.0	1782.1	1651.6	1620.5							
G42.0	1755.9	1621.5	1588.3							
G43.0	1728.8	1590.2	1557.1							
G44.0	1703.2	1559.8	1522.5							
G45.0	1675.7	1527.8	1490.6							
G46.0	1648.4	1496.8	1456.1							
G47.0	1620.9	1465.6	1422.1							
G48.0	1594.1	1433.6	1388.7							
G49.0	1566.5	1400.8	1355.1							
G50.0	1538.6	1369.1	1320.6							
G51.0	1510.4	1335.7	1286.6							
G52.0	1482.7	1303.5	1251.5							
G53.0	1453.3	1269.6	1216.7							
G54.0	1423.7	1237.8	1180.8							
G55.0	1395.1	1202.7	1144.8							
G56.0	1365.9	1170.0	1109.4							
G57.0	1337.4	1137.3	1074.8							
G58.0	1307.4	1104.9	1037.6							
G59.0	1278.6	1070.3	1002.0							
G60.0	1248.2	1037.8	965.4							
G61.0	1219.1	1004.7	928.5							
G62.0	1188.4	972.3	891.3							
G63.0	1159.6	938.7	854.8							
G64.0	1128.7	907.3	818.1							
G65.0	1099.2	874.0	780.7							
G66.0	1069.2	841.7	744.1							
G67.0	1039.3	809.0	706.9							
G68.0	1008.6	778.6	669.8							
G69.0	979.3	746.2	632.7							
G70.0	949.2	714.7	595.6							
G71.0	919.8	684.1	559.3							
G72.0	889.2	652.5	522.4							
G73.0	860.0	623.2	485.7							

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 7)

Unit: cd

G/C	C300.0	C330.0	C360.0							
G74.0	829.7	591.7	449.5							
G75.0	801.2	563.5	413.8							
G76.0	773.0	533.9	378.6							
G77.0	744.3	505.5	343.4							
G78.0	715.4	476.9	310.5							
G79.0	687.4	450.2	276.9							
G80.0	660.4	424.1	244.9							
G81.0	633.9	398.3	213.4							
G82.0	606.8	372.8	184.7							
G83.0	581.3	350.0	156.9							
G84.0	556.7	327.0	130.6							
G85.0	533.6	306.1	107.3							
G86.0	509.9	285.7	86.8							
G87.0	488.7	267.6	68.6							
G88.0	468.0	250.1	54.8							
G89.0	448.6	234.8	44.6							
G90.0	429.7	220.3	39.1							
G91.0	412.1	207.1	38.0							
G92.0	395.0	194.5	37.5							
G93.0	379.0	183.2	37.0							
G94.0	363.4	171.7	36.6							
G95.0	348.2	161.3	36.2							
G96.0	333.7	151.3	35.8							
G97.0	320.3	141.8	35.4							
G98.0	306.3	132.2	35.0							
G99.0	292.9	123.5	34.5							
G100.0	280.1	114.8	34.1							
G101.0	267.7	107.1	33.8							
G102.0	255.4	100.1	33.3							
G103.0	243.4	93.6	33.0							
G104.0	230.1	87.6	32.6							
G105.0	210.4	82.0	32.2							
G106.0	196.1	76.7	31.9							
G107.0	181.4	71.4	31.5							
G108.0	172.2	65.7	31.1							
G109.0	163.7	60.3	30.8							
G110.0	155.4	55.2	30.4							

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:

Candlepower Table (Continue 8)

Unit: cd

G\C	C300.0	C330.0	C360.0							
G111.0	147.1	50.8	30.0							
G112.0	140.0	47.0	29.7							
G113.0	133.1	43.7	29.4							
G114.0	126.3	40.8	29.1							
G115.0	119.6	38.0	28.8							
G116.0	113.1	35.7	28.4							
G117.0	106.9	33.5	28.1							
G118.0	100.8	31.4	27.8							
G119.0	94.7	29.5	27.5							
G120.0	89.1	27.9	27.2							
G121.0	83.5	26.5	27.0							
G122.0	78.1	25.6	26.7							
G123.0	73.0	25.1	26.5							
G124.0	68.1	24.8	26.2							
G125.0	63.4	24.6	25.9							
G126.0	59.0	24.3	25.7							
G127.0	54.8	24.1	25.4							
G128.0	50.6	23.9	25.2							
G129.0	46.7	23.6	25.0							
G130.0	43.0	23.4	24.8							
G131.0	39.5	23.2	24.6							
G132.0	36.3	23.0	24.4							
G133.0	33.4	22.8	24.2							
G134.0	30.7	22.5	24.1							
G135.0	28.2	22.3	23.9							
G136.0	26.1	22.2	23.7							
G137.0	24.6	22.1	23.6							
G138.0	24.0	22.0	23.5							
G139.0	23.9	21.8	23.3							
G140.0	23.9	21.7	23.2							
G141.0	24.0	21.6	23.1							
G142.0	24.0	21.7	23.1							
G143.0	24.1	21.7	23.0							
G144.0	24.1	21.8	23.0							
G145.0	24.1	21.9	22.9							
G146.0	24.2	22.1	22.9							
G147.0	24.3	22.2	22.9							

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector:



Candlepower Table (Continue 9)

Unit: cd

G/C	C300.0	C330.0	C360.0							
G148.0	24.3	22.4	22.9							
G149.0	24.4	22.5	22.9							
G150.0	24.4	22.6	23.1							
G151.0	24.4	22.8	23.2							
G152.0	24.3	22.9	23.4							
G153.0	24.3	23.0	23.5							
G154.0	24.3	23.1	23.6							
G155.0	24.3	23.2	23.8							
G156.0	24.3	23.3	24.0							
G157.0	24.3	23.4	24.1							
G158.0	24.3	23.5	24.2							
G159.0	24.3	23.6	24.3							
G160.0	24.3	23.7	24.4							
G161.0	24.4	23.9	24.5							
G162.0	24.5	24.0	24.6							
G163.0	24.5	24.1	24.8							
G164.0	24.6	24.2	24.9							
G165.0	24.7	24.3	25.0							
G166.0	24.7	24.3	25.1							
G167.0	24.8	24.4	25.3							
G168.0	24.8	24.5	25.4							
G169.0	24.8	24.6	25.5							
G170.0	24.8	24.7	25.6							
G171.0	24.8	24.7	25.7							
G172.0	24.8	24.8	25.7							
G173.0	24.8	24.8	25.8							
G174.0	24.8	24.9	25.9							
G175.0	24.9	24.9	25.9							
G176.0	24.8	25.0	26.0							
G177.0	24.9	25.1	26.0							
G178.0	25.1	25.3	26.0							
G179.0	25.4	25.5	26.0							
G180.0	25.6	25.5	25.9							

C Plane (°):0.0-360.0: 30.0

Test Lab:

Test Type: TYPE C

Temperature: 23

Operator: HUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 8.580 m

Humidity: 88

Inspector: