VNTLO020-34

ADJUSTABLE CCT 3000K-6000K



PROJECT: TYPE: CATALOG#: DATE:



VNTLO020-31 7 29/64" (189mm) 2 21/52" (Ф72mm) (088mm) 3 5/66" (088mm)

DESCRIPTION

VEGA (VNTLO series, Zoomable version) is a stylish and compact LED track light that will fit smoothly into any museum, gallery or retail environment. Featuring an adjustable beam mechanism designed to provide endless beam options from 25° to 60° distribution. The head can be adjusted precisely 360°+ horizontal (rotation) and 90° vertical without dead angle. The light, as a result, is emitted exactly where needed. The integrated driver gives a clean feeling and the ceiling will not be cluttered with drivers aimed in different directions.

FEATURES

- 3000K-6000K CCT adjustable.
- Self-dim to adjust light intensity from 0-100%
- · Stylish and compact design with integrated driver
- Excellent modular combination concept: integrated driver + different fixture bases, DIY to get different light solutions and ease of maintenance.
- Beam angle adjustable mechanism provides endless beam options from a narrow to a wide flood distribution by simply rotating the rubber ring. Light efficiency is up to 70lm/W.
- Patented joints can hold the track head at any position without malfunctions.
- 360°+ rotation without dead angles and 90° vertical aiming.

SPECIFICATION

3F LOII ICATION					
	VN-TL0020-34				
WATTAGE	20W				
LUMEN OUTPUT	1357lm				
BEAM ANGLE	25°- 60°				
ССТ	3000K - 6000K				
CRI	80+, 90+, 95+ (optional)				
INPUT WATTAGE	20W				
INPUT VOLTAGE	120VAC Dimming, 50Hz/60Hz				
DIMMING TYPE	Optional leading (Triac) and trailing edge (ELV) for 120V only				
MOUNTING	Track-Mounted: 1. Single-circuit: Halo, Juno, Lightolier	Wall-Mounted			
	2 Two circuit: TEK, HTEK				
	3 Three-circuit: Global				
FINISH	White, Black, Silver				
WEIGHT	1.79lbs (0.81kg)				
LISTINGS	cETLus Listed to UL and CSA Standards; Suitable for Dry Locations only				
WARRANTY	5 year limited warranty				
SYSTEM RATING	80% of initial lumens at 50000 hours (L80)				

Approximate lumen output based on 3000K performance, see photometric test results for additional information.

Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)







^{***}Please note lumens and wattage are subject to change and will be determined post production of the first articles.

^{*}Any custom modifications are subject to minimum order quantity. (M.O.Q.)

VNTLO020-34

ADJUSTABLE CCT 3000K-6000K



PROJECT: TYPE: CATALOG#: DATE: ACCESSORIES (TO BE ORDERED SEPARATELY. FOR INSTALLATION, CONSULT THE INSTALLATION GUIDE.) **HONEYCOMB FILTER CROSS LOUVER SNOOT** VN-TLO-AC01-(White/Black) VN-TLO-AC02-(White/Black) VN-TLO-AC03-(White/Black) **EYE SNOOT WALL WASHING RING BARN DOOR** VN-TLO-AC04-(White/Black) VN-TLO-AC05-(White/Black) VN-TLO-AC06-(White/Black)

OPTICAL ACCESSORIES

CIRCULAR SMALL FILTER VN-TLO-AC17-(White/Black)





WIDE LINE FILTER





CIRCULAR BIG FILTER VN-TLO-AC18-(White/Black)





WALL WASHING FILTER VN-TLO-AC23-(White/Black)





SQUARE BIG FILTER VN-TLO-AC19-(White/Black)





Theoretical Lumens: XXX LM (subject to change) Theoretical Wattage: XXX W (subject to change)

*Any custom modifications are subject to minimum order quantity. (M.O.Q.)







^{***}Please note lumens and wattage are subject to change and will be determined post production of the first articles.

VNTLO020-34

ADJUSTABLE CCT 3000K-6000K





PROJECT: TYPE: CATALOG#: DATE:

PHOTOMETRICS

CCT (K)	CRI	LOAD (W)	BEAM OPTIC	LUMENS (lm)	EFFICACY (lm/w)	MAX CANDELA (cd)
3000K		20W	25°	848	43	4545
	90		60°	1034	52	1385
6000K			25°	1120	56	6001
			60°	1357	69	1740


ZOOMABLE-20W






Above test data is based on 3000K 90CRI LED

ZOOMABLE-20W





Above test data is based on 6000K 90CRI LED

Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

***Please note lumens and wattage are subject to change and will be determined post production of the first articles.

*Any custom modifications are subject to minimum order quantity. (M.O.Q.)







VNTLO020-34

ADJUSTABLE CCT 3000K-6000K




PROJECT: TYPE: CATALOG#: DATE:


PRODUCT CHARACTERISTICS

Smooth adjustment without noise from narrow beam to flood beam






SOLUTION 1: Stepless CCT adjustment





SOLUTION 2: 5 Steps CCT adjustment





Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)







^{***}Please note lumens and wattage are subject to change and will be determined post production of the first articles.

^{*}Any custom modifications are subject to minimum order quantity. (M.O.Q.)


VNTLO020-34

ADJUSTABLE CCT 3000K-6000K



PROJECT: TYPE: CATALOG#: DATE:

EXCELLENT MODULAR COMBINATION CONCEPT



Wall-Mounted

VN-TLO020-34



Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

***Please note lumens and wattage are subject to change and will be determined post production of the first articles.

*Any custom modifications are subject to minimum order quantity. (M.O.Q.)





