

OPUS UP-DOWN LIT PRISMATIC SUSPENDED

VOH40FP1200

By VONN Lighting


VONN

PROJECT:

TYPE:

CATALOG#:

DATE:



DESCRIPTION

- Up-down lit Prismatic
- Black
- Length: 1200mm
- 48W
- 2700K//3000K/4000K
- Ra90
- Non-dimming

FEATURES

- Installation: Pendant
- Size: 25\*100\*1200/1500/1800/2400mm
- Material: AL6063-T5
- Coating: Black/White (Customizable) optional
- Dimming method: Non/DALI-2/CASAMBI
- Input voltage: DC48V
- SDCM: <3 Step (ANSI)
- CRI: 90
- CCT: 2700/3000/4000K optional
- Beam angle: Up:100°, Down: 65°x90°
- Application: Indoor
- IP grade: IP20
- Warranty: 5 years
- Certification: CE, UKCA, ETL, ROHS, Reach

SPECIFICATION

MODEL	LENGTH	VOLTAGE	WATTAGE	CRI	CCT	LUMENS
VOH40FP1200	1208mm [3.96']	DC48V	48W	>90	2700K	2736 [691LM/ft]
					3000K	2784 [703LM/ft]
					4000K	2976 [752LM/ft]
VOH40FP1500	1508mm [4.95']		60W		2700K	3420 [691LM/ft]
					3000K	3480 [703LM/ft]
					4000K	3720 [752LM/ft]
VOH40FP1800	1808mm [5.93']		72W		2700K	4104 [691LM/ft]
					3000K	4176 [703LM/ft]
					4000K	4464 [752LM/ft]
VOH40FP2400	2408mm [7.90']		96W		2700K	5472 [691LM/ft]
					3000K	5568 [703LM/ft]
					4000K	5952 [752LM/ft]

Note:

1. The above parameters were tested based on Ra90, 4000K, light source;
2. luminous flux is allowed to have a ±10% error range;
3. The above parameters are typical values.

Theoretical Lumens: XXX LM (subject to change)  
Theoretical Wattage: XXX W (subject to change)  
\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.  
\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)

© VONN Lighting, 2024

OPUS UP-DOWN LIT PRISMATIC SUSPENDED

VOH40FP1200

By VONN Lighting

VONN



PROJECT:

TYPE:


CATALOG#:

DATE:

PHOTOMETRICS




DIMENSIONS



Theoretical Lumens: XXX LM (subject to change)  
Theoretical Wattage: XXX W (subject to change)  
\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.  
\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)

© VONN Lighting, 2024



# OPUS UP-DOWN LIT PRISMATIC SUSPENDED

## VOH40FP1200

By VONN Lighting

PROJECT:

TYPE:

CATALOG#:

DATE:

## PRODUCT ACCESSORIES INFORMATION

Picture	Section size	Name	Description	Model	Note
		Base	Material: PC+ADC12 Input Voltage:DC48V Coating:Black/White Open Size: φ42-45mm Rated Power:150W Rated Current:3A Maximum load: 8Kg/Lamp	VRA-HR40(N)	
		Base	Material: PC+ADC12 Input Voltage:DC48V Coating:Black/White Open Size: φ55mm Rated Power:150W Rated Current:3A Maximum load: 1Kg/Lamp	VRA-HE40	
		Quick connector	Material:PA6 Size:L38*W9.4*H10.5mm [Inch Size: L1.5"*W0.37"*H0.41"] Applicable wires: solid wire:0.5-4mm <sup>2</sup> stranded wire:0.5-2.5mm <sup>2</sup> Rated Voltage:250V/600V Rated Current:32A	VTB-02	
		Power supply	Dimming mode: Non-dimming Size:350*30*18mm Input voltage:AC220~240V Operating frequency: 50/60Hz PF value:≥0.9 Output voltage:48V Output current:2.1A Power:0-100W Efficiency:0.9	VBN-V48-100P	Power supply Accessories
		Power supply	Dimming mode: Non-dimming Size:350*30*18mm Input voltage:AC220~240V Operating frequency: 50/60Hz PF value:≥0.95 Output voltage:48V Output current:3.125A Power:0-150W Efficiency:0.9	VBN-V48-150P	
		Power supply	Dimming mode: Non-dimming Size:400*40*22mm Input voltage:AC220~240V Operating frequency: 50/60Hz PF value:≥0.95 Output voltage:48V Output current:5.12A Power:0-250W Efficiency:0.9	VBN-V48-250P	
		CASAMBI controller	Dimming mode: CASAMBI Size:180*42*25mm [Inch Size:7.09"*1.65"*0.98"] Input voltage:24-48VDC Output signal:DALI Output DALI Max.current: 250mA Control devices:≤64 Control groups:≤8	V1200EN1612-CAS -0-0000003	Controller should be used with DALI dimming modules.

Note:

1. Max. power cable (16AWG main cable) of base ≤ 50M
2. Total power of modules during work < 80%~85% output power of supply

Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.

\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)

© VONN Lighting, 2024