

# LYRA / ORION SPOTLIGHT

By VONN Lighting



VUTH20S42

PROJECT:

TYPE:

CATALOG#:


DATE:



## DESCRIPTION

- Spotlight
- 18°/24°/36°/50°
- Black
- 42mm
- 6W
- 2700K/3000K/4000K
- Ra90

## DIMENSIONS



## FEATURES

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Size: 42\*68mm
- IP grade: IP20
- CCT: 2700K,3000K,4000K, 3000K-3800K-5000K optional
- CRI: 90
- SDCM: <3 Step (ANSI)
- Beam angle: 15°,24°,36°,50°(Normal version) 28°,36°,50°(3 CCT tunable(Dial switch))
- Light efficiency: 82 LM/W
- Input voltage: DC24V-48V,DC48V
- Lighting direction: Downward
- Dimming method: Non-dimming,DALI-2,Tuya Bluetooth,CASAMBI
- Application: Indoor
- Certification: CE, UKCA, ROHS, Reach
- Warranty: 5 years

Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.

\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)


© VONN Lighting, 2024

VONN, LLC.

3323 NE 163rd St. PH-706  
North Miami Beach, FL 33160

WWW.VONN.COM 888.604.8666

VONN, LLC. reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance.



PROJECT: \_\_\_\_\_ TYPE: \_\_\_\_\_ CATALOG#: \_\_\_\_\_ DATE: \_\_\_\_\_

### SPECIFICATION

MODEL	LENGTH	VOLTAGE	WATTAGE	CRI	BEAM ANGLE	CCT	LUMENS
VUTH20S42	W 42mm (1.65") x H 68mm (2.67")	24-48VDC	6.0W	>90	15°	2700K	400lm
						3000K	425lm
						4000K	455lm
					24°	2700K	420lm
						3000K	445lm
						4000K	480lm
					36°	2700K	420lm
						3000K	445lm
						4000K	480lm
					50°	2700K	425lm
						3000K	450lm
						4000K	485lm
VUTH20S42 3CCT Tunable (Dial switch)					28°	3000K	405lm
						3800K	430lm
						5000K	420lm
					36°	3000K	445lm
						3800K	480lm
						5000K	470lm
					50°	3000K	460lm
						3800K	490lm
						5000K	485lm

- Note:
1. The output data is based on the testing result of Ra90,4000K luminaires;
  2. The tolerance of output data can be vary up to 10%;
  3. The output data is typical value.


Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.

\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)

© VONN Lighting, 2024



PROJECT:





TYPE:

CATALOG#:




DATE:

## PHOTOMETRICS

· Normal



· 3 CCT tunable(Dial switch)



Theoretical Lumens: XXX LM (subject to change)

Theoretical Wattage: XXX W (subject to change)

\*\*\*Please note lumens and wattage are subject to change and will be determined post production of the first articles.

\*Any custom modifications are subject to minimum order quantity. (M.O.Q.)

© VONN Lighting, 2024