



Fixture Type:
Catalog Number:
Project:
Location:

PRODUCT DESCRIPTION

Landscape accent luminaire. Simple to retrofit existing line voltage systems or coordinate well with a new commercial landscape installation.

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Detachable shroud, 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Colo	Color Temp		
5012 Accent 120V	30	3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5012-30

Example: 5012-30BBR

SPECIFICATIONS

 Input:
 110V - 120VAC

 Power:
 3.5W to 14.5W

 Brightness:
 100 lm to 900 lm

 Beam Angle:
 15° to 60°

 CRI:
 85

Rated Life: 45,000 hours

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585



Accessories				
Power Stake	M6000-STAKE	PVC		Easy wiring accessory designed for 12V & 120V products Eliminates the need for a separate Junction box
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR	Black on Alumir Bronze on Alum Bronze on Brass	inum	Shields lamp and reduces glare
6"Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR	Black on Alumir Bronze on Alum Bronze on Brass	inum	Reduce glare. Ideal for downlighting application
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK	Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK	Bronze on Alum Black on Alumir		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-20-AMB Amb LENS-20-GRN Gree LENS-20-RED Red	en LENS-20-FR	Frosted	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in	1	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS 150W Max

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

