



PRODUCT

Partnumber	V-C2-EUP
Use	Install controller between power outlet and wiring to Vinci bulbs to control the bulbs

DEVICE MODES

Stand Alone mode	Built-in effects generator with customizable colors and parameters
- Live	Control effects live through smartphone companion app
- Favorites (up to 3)	Up to three effects can be stored as a favorite and recalled later
- Shows	Program and schedule shows by sequencing effects
DMX mode	Control connected bulbs in realtime with DMX
Sync Master mode	Accurate frame sync of lights effects on multiple controllers through proprietary wireless synchronisation protocol using "Wireless Solutions Sweden AB" module.
Sync Slave mode	Display colors in mirrored way (same as on Sync Master) or extended way (effect continues after Sync Master on Sync Slave)

DATA PROTOCOL

Communications speed	"25 FPS for all bulbs DMX compatible speed 128 x 4 control channels channel assignment depends on bulbs type eg RGBW"
Communications dataprotocol	Proprietary Lucenti Powerline communication protocol = Lucenti Data Over Power (DOP)

CONNECTIVITY/ELECTRICAL

Built-in Wi-Fi	IEEE 802.11 B/G/N 2.4GHz Wi-Fi - Can connect to external router (infrastructure mode) or create own wireless network (ad-hoc mode)
DMX input	5pin Male XLR (through adapter cable)
DMX output	5pin Female XLR (through adapter cable)
Power Input	110-240 VAC, max 10A, 50Hz
Power+DATA Output	Connection to socket wire, max 10A
Power Consumption	7,5W
Max. current througput	10A

CONTROLS

Smartphone companion app	Vinci smartphone companion APP (iOS/Android), connected to controller via Wi-Fi network
Built-in LCD display and buttons	Navigate through device menu using the buttons to change system parameters and control device mode
Built-in website	Built-in website accessible through modern desktop or mobile browser

ADDRESSING / ADDING BULBS TO SETUP

	Easy automatic or manual addressing of bulbs
	Locate broken bulbs function

RESET

Wi-Fi reset	Reset Wi-Fi to default settings: Ad-Hoc mode, no password
Factory reset	Reset controller to factory state

MECHANICAL

Mounting	Separate plastic wall/ceiling mounting bracket included
IP Rating	IP65 - Outdoor Use
Controller Dimensions	246x129x65mm (LxWxH)
Weight	900g

PRODUCTS

Controller package - schuko version

V-C2-EUP

Package content: Controller with schuko outlets, soft case, mounting bracket, manual, DMX adapter cable, data terminator

Data terminator schuko

V-DT1-EU

Dmx adapter cable

LU-ZZZ-C017

