

STANCOR



Oil-Minder® Simplex & Duplex Pump and Control Systems

Solid State, NEMA 4x
Oil-Minder® Control



SE50 Pump
with Float &
Oil-Minder®
Probe



The Stancor Oil-Minder® Control and Pump System allows water to be automatically pumped from elevator pits, transformer vaults, and industrial sumps without danger of ejecting potentially harmful oily substances into sewers, rivers and waterways. There is no need for a separate oil-water separator. The product is engineered for efficient and trouble free pumping, even under the most severe conditions. The Stancor Oil-Minder® System is the overwhelming choice among design engineers and compliance authorities worldwide, and has a proven record for protecting valuable equipment and the environment.

Features

- NEMA 4x weathertight corrosion resistant polycarbonate enclosures
- Stainless steel sensor probe with patented electronic technology that repels dirt contamination
- Single direct plug-in power source for operation of entire system
- Solid state components
- Alarms, lights, silence switch, and remote monitoring circuit for oil, high liquid, and high amperage conditions
- Complete factory assembly and testing insures quality of entire pump and control system
- Patented - Pat. #4,715,785, #4,752,188, #6,203,281 and others pending
- Oil-Minder® System can be combined with a variety of different pumps and valves
- Choice of: 115v or 220v (1 phase) OR 230v/460v/575v (3 phase)
- LED indicator lights for oil spill, power, high liquid level, overload, and pump run
- UL 508 and 778 approved
- ENTELA tested and approved as a system

“There Is Only One Oil-Minder® System and Stancor Makes It”
Quality You Can Believe In

Description of Stancor Simplex Oil-Minder® Systems


The **Stancor Simplex Oil-Minder® System** is available in two primary configurations, as follows:

The **Multi-Option Oil-Minder® System** is designed for easy, fool-proof installation. All pump and control cables are factory wired into a wall mountable junction box. Between the junction box and the main Oil-Minder® control panel is a multi-pin quick connect cable. This single cord, 8-pin system allows the electrical cable between the junction box and control panel to be run through conduit and interconnected up to 250 feet long, using a single “push and turn” motion. There is no need for field wiring. Electrical installation costs are reduced by approximately 75% and all connections are secure and water-tight.

The **Junior Oil-Minder® System** is a good choice where the main control is located in the same area as the pump pit, or where the main control will be located remotely and conventional “hard wiring” is used between a junction box and the main control. Comparative features of each model are as follows:

Feature included in standard package	O/M Multi-Option	O/M Junior
SE-40 (.4 HP) or SE-50 (.5 HP) 115V or 230V single phase pump	x	x
Solid state NEMA 4x control panel	x	x
Separate LED indicator lights on NEMA 4x control for A) oil alert, B) high water, C) high motor amps, D) power to system, and E) pump activation	x	x
Self cleaning, hermetically sealed stainless steel oil detection probe	x	x
Float switches for pump activation and high water alert	x	x
Monitoring relays for alert conditions at remote locations	x	x
High decibel, water tight horn and silence switch for alert conditions	x	x
Direct plug-in activation of entire pump and control system from the main control panel (6' cord and molded plug included)	x	x
Factory hard wiring of pump, oil probe, and floats into NEMA 4x junction box	x	
Factory hard wiring of pump, oil probe, and floats directly into main NEMA 4x control panel		x
Junction box with female 8-pin cable receptacle and disconnect	x	
25' 8-pin Quick Connect cable (expandable to 250' with interconnecting extension cables)	x	
Female 8-pin cable receptacle installed in the NEMA 4x control panel	x	

Typical Stancor Simplex Multi-Option Oil-Minder® System



 STANCOR	TECHNICAL DATA	AVENGER SERIES	SEW-150
Dwg:	DS-A02-019	Rev: 2	Date: 01/16

MOTOR SPECIFICATIONS

Motor Design	NEMA design B, squirrel cage induction
Motor Type	Enclosed submersible
Insulation Class	Class E
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.3
Voltage Tolerance	± 10% from nominal



MOTOR DATA, 60Hz

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
SEW-150	1	1.5	115	17.6	88.0	H	0.95	0.69	2/3450
	1	1.5	208	9.7	48.5	J	0.93	0.69	2/3450
	3	1.5	230	5.5	27.5	J	0.93	0.75	2/3450
	3	1.5	460	2.8	14.0	J	0.91	0.75	2/3450
	3	1.5	575	2.5	12.5	K	0.90	0.75	2/3450

MATERIALS OF CONSTRUCTION

Upper Motor Lid	Cast Iron ASTM A48 Class 30
Motor Housing	AISI 304 Stainless Steel
Oil Chamber	Cast Iron ASTM A48 Class 30
Volute	Cast Iron ASTM A48 Class 30
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	AISI 410 Stainless Steel
Upper Bearing	Single row Sealed
Lower Bearing(s)	Single row Sealed
Upper Shaft Seal	Carbon/Ceramic
Lower Shaft Seal	SiC/SiC
Impeller	Cast Iron ASTM A48 Class 30

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	55lbs (25kg)
Pump weight three phase	55lbs (25kg)
Maximum submergence	33 feet (10m)
Discharge size, standard	2" NPT female vertical
Maximum temp. of pumped fluid	104°F (40°C)

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
SEW-150	1Ø-115V	SJTOW 12/3	33feet (10m)	NBR
	1Ø-230V	SJTOW 14/3	33feet (10m)	NBR
	3Ø-230V	STOW 16/4	33feet (10m)	NBR
	3Ø-460V	STOW 16/4	33feet (10m)	NBR
	3Ø-575V	STOW 16/4	33feet (10m)	NBR

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.


Specifications subject to change without notice



Horsepower: 1.5 HP

Hertz: 60 Hz

EFF (%) BHP





SPECIFICATIONS

AVENGER SERIES

SEW-150

STANCOR



Dwg:

DS-A02-022

Rev: 1

Date: 05/15

SEW-150



TYPE	DISCHARGE	A	A1	A2	D	D1	D2	H	H1	H2	H3
SEW-150	2" NPT female	10.67	3.66	5.31	7.32	3.46	3.86	19.92	14.80	5.94	5.63

Specifications subject to change without notice

Stancor, Inc. 515 Fan Hill Road, Monroe, CT 06468

Tel: 203-268-7513

Fax : 203-268-7958

www.stancorpumps.com