



Hale Trailer Brake & Wheel

SERIAL: **MA0303**



SL-520 Quote

The SL-520 SwapLoader hoist (50,000 lb. Dump / Lift Capacity)

- Optimum body lengths 19' - 22'
- Potential Body Lengths 19' to 24'
- Cab to trunion (CT) requirement is 176" to 190" with 190" being the optimum CT.
- Clear frame requirement is 245".

The SL-520 is shipped with the following items as standard equipment:

Dual 7" DA lift cylinders, sliding jib with 4.5" DA cylinder, slide through body locks, 30 gallon reservoir tank, hydraulic two (2) section manual valve, in-cab manual control levers and 96" cables. Order pump as separate line item from hoist. Hoist is shipped less PTO (customer to furnish PTO) and the hoist is painted a black primer, finish paint recommended.

ITEM NO.	DESCRIPTION
HOIST	
44H23	SL-520 (adjustable jib 53 7/8" to 61 3/4") 50,000 # Dump / Lift Capacity Hoist
HOIST ACCESSORIES (<i>mounts permanently to chassis and/or hoist</i>)	
22p45	RH Rotation Direct Mount Pump-SL-520 / 518 / 650
led-lb	LED Rear Light Bar
12h63	Fenders - Polypropylene (double radius/tandem axle - set) w/brackets, fits 20", 22" tires. Color: Blk
52H11	Rear Bumper (Fits all models)
90H47	Air Shift Control w/2-section valve - fits SL-520/518/650

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice