



Hale Trailer Brake & Wheel

SERIAL: **CB1558**



SL-240 Quote

The SL-240 SwapLoader hoist (24,000 lb. Dump / Lift Capacity)

Optimum body lengths 14' - 16'

Potential Body Lengths 14' to 18'

Cab to axle (CA) requirement is 130" to 144" with 144" being the optimum CA. Cab to trunion (CT) requirement is 120" to 132" with 132" being the optimum CT.

Clear frame requirement is 184".

The SL-240 is shipped with the following items as standard equipment:

Dual 6" DA lift cylinders, sliding jib with 3.5" DA cylinder, slide through body locks, 25 gallon reservoir tank, hydraulic two (2) section manual valve, in-cab manual control levers and 84" cables. Order pump as separate line item from hoist. Hoist is shipped less PTO (customer to furnish PTO) and the hoist is painted a black primer, finish paint recommended.

ITEM NO.	DESCRIPTION
HOIST	
52H58	SL-240 (Adjustable 53 7/8" to 61 3/4" jib) 24,000 # Dump / Lift Capacity Hoist
HOIST ACCESSORIES (mounts permanently to chassis and/or hoist)	
11H66	Fenders - Polypropylene (full radius/single axle - set) with brackets fits 20", 22" tires. Color: Black
led-lb	LED Rear Light Bar
52H11	Rear Bumper (Fits all models)
20p43	RH Rotation Pump-SL-220 / 222 / 240 / 2418
ehv-240	Electric Over Hydraulic Control Valve 2-section - SL-240

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.