



Hale Trailer Brake & Wheel

SERIAL: **AB0140**



SL-75 Quote

The SL-75-PWR SwapLoader hoist (7,500 lb. Dump / Lift Capacity)

- Optimum body lengths 10' - 12'
- Potential Body Lengths 9' to 13'
- Cab to axle (CA) requirement is 84" to 96" with 96" being the optimum CA.
- Clear frame requirement is 126".

The SL-75 - PWR is shipped with the following items as standard equipment:

Single 4" DA lift cylinder, dual sliding jib, slide through body lock & shelf ASSY, SwapLoader Power Pack Hydraulic System, No pump or PTO required. Requires single auxiliary battery. Hoist is painted a black primer, finish paint recommended.

ITEM NO.	DESCRIPTION
	HOIST
SL-75-PWR	SL-75 (fixed 35 5/8" jib) 7,500 # Dump / Lift Capacity Hoist -Self Contained Power Unit
	HOIST ACCESSORIES (mounts permanently to chassis and/or hoist)
FEN-195	Fenders - Polypropylene (full radius/single axle - set) with brackets fits 19 1/2" tires. Color: Black
LED-LB	LED Rear Light Bar

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.