



Hale Trailer Brake & Wheel

SERIAL: VK0177



SL-160 Quote

The SL-160 SwapLoader hoist (16,000 lb. Dump / Lift Capacity)

- Optimum body lengths 12' - 14'
- Potential Body Lengths 10' to 15'
- Cab to axle (CA) requirement is 102" to 120" with 120" being the optimum CA.
- Clear frame requirement is 152".

The SL-160 is shipped with the following items as standard equipment:

Dual 5" DA lift cylinders, sliding jib with 3" DA cylinder, slide through body locks, 15 gallon reservoir tank, hydraulic two (2) section manual valve, in-cab manual control levers and 84" cables. Order pump as separate line item from hoist. Hoist is shipped less PTO (customer to furnish PTO) and the hoist is painted a black primer, finish paint recommended.

ITEM NO.	DESCRIPTION	HOIST
13H69	SL-160 (adjustable 35 5/8" jib to 53 7/8" jib) 16,000 # Dump / Lift Capacity	Hoist
	HOIST ACCESSORIES (mounts permanently to chassis and/or hoist)	
11H66	Fenders - Polypropylene (full radius/single axle - set) with brackets fits 20", 22" tires. Color: Black	
52H11	Rear Bumper (Fits all models)	
EHV-160	Electric Over Hydraulic Control Valve 2-section - SL-160	

****Rotation Pump & Rear LED Light Bar Are Included!****

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.