



Hale Trailer Brake & Wheel

SERIAL: **VJ0275**



SL-214 Quote

The SL-214 SwapLoader hoist (20,000 lb. Dump / Lift Capacity)

- Optimum body lengths 14' - 16'
- Potential Body Lengths 14' to 18'
- Cab to axle (CA) requirement is 120" to 138" with 138" being the optimum CA.
- Clear frame requirement is 172".

The SL-214 is shipped with the following items as standard equipment:

Dual 5.50" DA lift cylinders, sliding jib with 3" DA cylinder, slide through body locks, 15 gallon reservoir tank, hydraulic two (2) section manual valve, in-cab manual control levers and 84" cables. Order pump as separate line item from hoist. Hoist is shipped less PTO (customer to furnish PTO) and the hoist is painted a black primer, finish paint recommended.

ITEM NO.	DESCRIPTION
	HOIST
13h60	SL-214 (Adjustable 35 5/8" to 53 7/8" jib)20,000 # Dump / Lift Capacity Hoist
	HOIST ACCESSORIES (mounts permanently to chassis and/or hoist)
11h66	Fenders - Polypropylene (full radius/single axle - set) with brackets fits 20", 22" tires.
led-lb	LED Rear Light Bar
52h11	Rear Bumper (Fits all models)
20p98	RH Rotation Pump-SL-160 / 212 / 214
ehv-214	Electric Over Hydraulic Control Valve 2-section - SL-214

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.