



Hale Trailer Brake & Wheel

SERIAL:



SL-212 Quote

The SL-212 SwapLoader hoist (20,000 lb. Dump / Lift Capacity)

- Optimum body lengths 12' - 14'
- Potential Body Lengths 12' to 16'
- Cab to axle (CA) requirement is 108" to 120" with 120" being the optimum CA.
- Clear frame requirement is 156".

The SL-212 is shipped with the following items as standard equipment:

Dual 5.50" DA lift cylinders, sliding jib with 3" DA cylinder, slide through body locks, 15 gallon reservoir tank, hydraulic two (2) section manual valve, in-cab manual control levers and 84" cables. Order pump as separate line item from hoist. Hoist is shipped less PTO (customer to furnish PTO) and the hoist is painted a black primer, finish paint recommended.

| ITEM NO. | DESCRIPTION |
|----------|---|
| | HOIST |
| 13H02 | SL-212 (Adjustable 35 5/8" to 53 7/8" jib) 20,000 # Dump / Lift Capacity Hoist |
| | HOIST ACCESSORIES (mounts permanently to chassis and/or hoist) |
| 11H66 | Fenders - Polypropylene (full radius/single axle - set) with brackets fits 20", 22" tires. Color: Black |
| 52H11 | Rear Bumper (Fits all models) |
| LED-LB | LED Rear Light Bar |
| EHV-212 | Electric Over Hydraulic Control Valve 2-section - SL-212 |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.