



## Hale Trailer Brake & Wheel

SERIAL: VK0321



### SL-160 Quote

The SL-160 SwapLoader hoist (16,000 lb. Dump / Lift Capacity)

- Optimum body lengths 12' - 14'
- Potential Body Lengths 10' to 15'
- Cab to axle (CA) requirement is 102" to 120" with 120" being the optimum CA.
- Clear frame requirement is 152".



The SL-160 is shipped with the following items as standard equipment:

Black powder coat finish, Dual 5" DA lift cylinders, sliding jib with 3" DA cylinder, slide through body locks, and 15 gallon reservoir tank. Order pump and PTO as separate line items from hoist which are NOT included.

ITEM NO.	DESCRIPTION
	<b>HOIST</b>
13H69	SL-160 (adjustable 355/8" jib to 53 7/8" jib) 16000 # Dump / Lift Capacity Hoist
	<b>HOIST ACCESSORIES (mounts permanently to chassis and/or hoist)</b>
FEN-195	Fenders - Polypropylene (full radius/single axle - set) with brkts fits 19 1/2" tires. Color: Black
EHV-160	Electric Over Hydraulic Control Valve 2-section - SL-160
53H20	LED Tail Light Package, Stainless Steel



### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.