

Part Number	Description	Length		Ribs	Load Capacity		Min./Max Center Distance w/43mm (1.9 in) Endcap	
		(mm)	(in)		(kg)	(lbs)	(mm)	(in)
70494901	Black 75 2EPJ404	404	15.9	2	1 to 200	1 to 440	131.3 - 137.4	5.17 - 5.41
70495001	Black 75 3EPJ404			3	201 to 300	441 to 661		
70495101	Black 75 4EPJ404			4	301 to 400	662 to 882		
70477501	Black 75 2EPJ435	435	17.1	2	1 to 200	1 to 440	144.1 - 150.6	5.67 - 5.93
70483601	Black 75 3EPJ435			3	201 to 300	441 to 661		
70483701	Black 75 4EPJ435			4	301 to 400	662 to 882		
70486201	Black 75 2EPJ442	442	17.4	2	1 to 200	1 to 440	152.1 - 158.7	5.99 - 6.25
70477901	Black 75 3EPJ442			3	201 to 300	441 to 661		
70486301	Black 75 4EPJ442			4	301 to 400	662 to 882		
70486701	Black 75 2EPJ486	486	19.1	2	1 to 200	1 to 440	172.5 - 179.8	6.79 - 7.08
70486801	Black 75 3EPJ486			3	201 to 300	441 to 661		
70486901	Black 75 4EPJ486			4	301 to 400	662 to 882		
70479001	Black 75 2EPJ536	536	21.1	2	1 to 200	1 to 440	198.2 - 206.4	7.80 - 8.12
70488701	Black 75 3EPJ536			3	201 to 300	441 to 661		
70488801	Black 75 4EPJ536			4	301 to 400	662 to 882		
70479201	Black 75 2EPJ636	636	25.0	2	1 to 200	1 to 440	249.9 - 262.8	9.84 - 10.35
70489101	Black 75 3EPJ636			3	201 to 300	441 to 661		
70489201	Black 75 4EPJ636			4	301 to 400	662 to 882		
70479301	Black 75 2EPJ746	746	29.4	2	1 to 200	1 to 440	304.1 - 315.4	11.97-12.42
70489301	Black 75 3EPJ746			3	201 to 300	441 to 661		
70489401	Black 75 4EPJ746			4	301 to 400	662 to 882		

Product availability is subject to change at any time

2mm, 3/32", 3mm, 1/8" Round Cross Sections

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in)		Minimum Pulley Ø (in)		Working Load @ Percent Tension								Weight	
						4% (N)		6% (N)		8% (N)		10% (N)		lbs/ft	kg/m
Material and Color						(lbs)	(N)	(lbs)	(N)	(lbs)	(N)	(lbs)	(N)		
Eagle Blue 80 EC	4928000		2	0.55	14	0.1	0.7	0.2	1	0.3	1.4	0.4	1.7	0.002	0.004
Eagle Clear 80 EC	4927000		2	0.55	14	0.1	0.7	0.2	1	0.3	1.4	0.4	1.7	0.002	0.004
Eagle Opaque 80	L040P802M		2	0.55	14	0.2	0.9	0.4	1.6	0.5	2.2	0.6	2.7	0.003	0.004
Eagle Orange 85	L040G852M		2	0.63	16	0.2	0.9	0.3	1.3	0.4	1.8	0.5	2.2	0.003	0.004
Eagle Clear 85	L04C852M		2	0.63	16	0.2	0.9	0.3	1.3	0.4	1.8	0.5	2.2	0.003	0.004
Eagle Green 89	4905402		2	0.71	18	0.3	1.4	0.5	2.4	0.7	3.2	0.9	4	0.003	0.004
Eagle Green 89 Textured	4905302		2	0.71	18	0.2	1	0.4	1.7	0.5	2.3	0.7	2.9	0.003	0.004
Eagle Red 90	4940017		2	0.79	20	1.1	4.7	1.5	6.8	1.9	8.5	2.2	10	0.003	0.004
Eagle Orange 85	1032003	3/32		0.75	19	0.3	1.2	0.4	1.9	0.6	2.5	0.7	3.1	0.004	0.005
Eagle Clear 85	4908003	3/32		0.75	19	0.3	1.2	0.4	1.9	0.6	2.5	0.7	3.1	0.004	0.005
Eagle Clear 95	4907003	3/32		0.94	24	0.5	2.3	0.8	3.4	1	4.3	1.2	5.1	0.004	0.005
Eagle Orange 85	1032004	1/8		1	25	0.5	2.2	0.7	3.3	1	4.4	1.2	5.5	0.006	0.01
Eagle Clear 85	4908006	1/8		1	25	0.5	2.2	0.7	3.3	1	4.4	1.2	5.5	0.006	0.01
Eagle Clear 95	4907006	1/8		1.25	32	0.9	4	1.3	6	1.7	7.7	2.1	9.1	0.007	0.01
Eagle Blue 80 EC	4928001		3	0.83	21	0.4	1.7	0.6	2.5	0.8	3.5	1	4.3	0.005	0.008
Eagle Clear 80 EC	4927001		3	0.83	21	0.4	1.7	0.6	2.5	0.8	3.5	1	4.3	0.005	0.008
Eagle Opaque 80	L040P803M		3	0.83	21	0.5	2.1	0.8	3.5	1.1	4.9	1.4	6.2	0.006	0.009
Eagle Orange 85	L040G853M		3	0.94	24	0.4	1.9	0.7	3	0.9	4	1.1	4.9	0.006	0.009
Eagle Clear 85	L04C853M		3	0.94	24	0.4	1.9	0.7	3	0.9	4	1.1	4.9	0.006	0.009
Eagle Blue 85	L04BL853M		3	0.94	24	0.4	1.9	0.7	3	0.9	4	1.1	4.9	0.006	0.009
Eagle Green 89	L04G893MS		3	1.06	27	0.7	3.2	1.2	5.2	1.6	7.2	2	9	0.006	0.009
Eagle Green 89 Textured	4905303		3	1.06	27	0.5	2.3	0.9	3.8	1.2	5.2	1.5	6.5	0.006	0.009
Eagle Red 90	4940020		3	1.18	30	2.4	10.5	3.4	15.1	4.3	19	5	22.2	0.006	0.009
Eagle White 40D	L04BY403M		3	1.42	36	1.9	8.3	2.9	12.8	3.8	16.8	4.5	20.2	0.006	0.008

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)
Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Conveying - Eagle Polyurethane

4mm, 5mm, 3/16" Round Cross Sections

Round Belting



Round

NON-REINFORCED	Part Number*	Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	Working Load @ Percent Tension										Weight	
Material and Color				4% (lbs) (N)	6% (lbs) (N)	8% (lbs) (N)	10% (lbs) (N)	lbs/ft	kg/m						
Eagle Blue 80 EC	4928002	4	1.1 28	0.6 2.8	0.9 4.2	1.3 5.6	1.5 6.7	0.009	0.014						
Eagle Clear 80 EC	4927002	4	1.1 28	0.6 2.8	0.9 4.2	1.3 5.6	1.5 6.7	0.009	0.014						
Eagle Opaque 80	L040P804	4	1.1 28	0.8 3.7	1.4 6.2	2 8.7	2.5 11	0.01	0.015						
Eagle Orange 85	L040G854	4	1.26 32	0.8 3.4	1.2 5.3	1.6 7	1.9 8.6	0.01	0.015						
Eagle Clear 85	L04C854	4	1.26 32	0.8 3.4	1.2 5.3	1.6 7	1.9 8.6	0.01	0.015						
Eagle Red 85	L04R8504	4	1.26 32	0.8 3.4	1.2 5.3	1.6 7	2 8.7	0.01	0.015						
Eagle Blue 85	L04BL854	4	1.26 32	0.8 3.4	1.2 5.3	1.6 7	2 8.7	0.01	0.015						
Eagle Green 89	4905404	4	1.42 36	1.3 5.7	2.1 9.3	2.9 12.8	3.6 16	0.01	0.015						
Eagle Green 89 Textured	4905304	4	1.42 36	0.9 4.1	1.5 6.8	2.1 9.3	2.6 11.6	0.01	0.015						
Eagle Red 90	4940021	4	1.57 40	4.2 18.6	6 26.8	7.6 33.8	8.9 39.5	0.01	0.015						
Eagle White 40D	L04BY404	4	1.89 48	3.3 14.8	5.1 22.8	6.7 29.8	8.1 36	0.01	0.015						
Eagle Blue 80 MD	4941100	3/16	1.31 33	0.8 3.5	1.2 5.4	1.6 7	1.9 8.6	0.013	0.02						
Eagle Orange 85	1032006	3/16	1.5 38	1.1 4.9	1.7 7.5	2.2 10	2.8 12.3	0.014	0.021						
Eagle Clear 85	4908009	3/16	1.5 38	1.1 4.9	1.7 7.5	2.2 10	2.8 12.3	0.014	0.021						
Eagle Red 90	4940022	3/16	1.88 48	6 26.5	8.6 38.2	10.8 48.1	12.6 56.2	0.014	0.022						
Eagle Clear 95	4907009	3/16	1.88 48	2 9.1	3 13.5	3.9 17.3	4.6 20.6	0.015	0.022						
Eagle Clear 85 QC	4934009	.188 × .080†	1.5 38	0.5 2	0.7 3.1	0.9 4.2	1.2 5.2	0.012	0.018						
Eagle Yellow 85 QC	4934021	.188 × .080†	1.5 38	0.5 2	0.7 3.1	0.9 4.2	1.2 5.2	0.012	0.018						
Eagle Blue 80 EC	4928003	5	1.38 35	0.9 4.2	1.4 6.3	1.9 8.4	2.4 10.6	0.015	0.022						
Eagle Clear 80 EC	4927003	5	1.38 35	0.9 4.2	1.4 6.3	1.9 8.4	2.4 10.6	0.015	0.022						
Eagle Opaque 80	L040P805M	5	1.38 35	1.3 5.7	2.2 9.7	3.1 13.6	3.9 17.2	0.016	0.024						
Eagle Orange 85	4940100	5	1.57 40	1.2 5.4	1.9 8.3	2.5 11	3.1 13.6	0.016	0.024						
Eagle Clear 85	L04C855M	5	1.57 40	1.2 5.3	1.9 8.2	2.5 11	3 13.5	0.016	0.024						
Eagle Red 85	L04R855	5	1.57 40	1.2 5.3	1.9 8.2	2.5 11	3 13.5	0.016	0.024						
Eagle Blue 85	L04BL855M	5	1.57 40	1.2 5.3	1.9 8.2	2.5 11	3 13.5	0.016	0.024						
Eagle Green 89	4905405	5	1.77 45	2 8.9	3.3 14.6	4.5 20.1	5.6 25.1	0.016	0.023						
Eagle Green 89 Textured	4905305	5	1.77 45	1.5 6.5	2.4 10.6	3.3 14.6	4.1 18.2	0.016	0.023						
Eagle Red 90	L04R9005M	5	1.97 50	6 26.5	8.6 38.2	10.8 48.1	12.6 56.2	0.014	0.022						
Eagle Beige 95	L04BE955M	5	1.97 50	5.3 23.6	7.5 33.4	9.4 41.8	11 48.8	0.016	0.024						
Eagle White 40D	L04BY405M	5	2.36 60	5.2 23.1	8 35.5	10.5 46.6	12.6 56.2	0.015	0.023						
Eagle Blue 80 EC QC	4928020	5 × 2†	1.38 35	0.4 1.8	0.6 2.8	0.8 3.7	1 4.6	0.012	0.018						
Eagle Clear 85 QC	L04QC855M	5 × 2†	1.57 40	0.5 2.3	0.8 3.5	1.1 4.7	1.3 5.8	0.013	0.02						
Eagle Red 85 QC	L04QR855M	5 × 2†	1.57 40	0.5 2.3	0.8 3.5	1.1 4.7	1.3 5.8	0.013	0.02						
Eagle Blue 85 QC	L04QB855M	5 × 2†	1.38 35	0.5 2.3	0.8 3.5	1.1 4.7	1.3 5.8	0.013	0.02						
QC Connectors	4935009	25/pack													
REINFORCED	Part Number*	Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	Working Load @ Percent Tension								Weight			
Material and Color				1% (lbs) (N)	2% (lbs) (N)	3% (lbs) (N)	4% (lbs) (N)	lbs/ft	kg/m						
Eagle Hyfen 85	5218009	3/16	2.06 52	2.8 12.5	6.8 30.2	11.2 49.8	15.5 68.9	0.014	0.021						
Eagle Green 89	L04G895MRS	5	1.97 50	1.7 7.4	5 22.2	10.2 45.4	15.7 70.1	0.016	0.023						
Eagle Green 89 Textured	4940056	5	1.97 50	2.3 10.2	6.9 30.5	14 62.5	21.7 96.3	0.016	0.023						

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

6mm, 1/4" Round Cross Sections

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 4% (N)	(lbs) 6% (N)	(lbs) 8% (N)	(lbs) 10% (N)	lbs/ft	kg/m				
Eagle Blue 80 EC	4928004	6	1.65	42	1.3	5.9	2.1	9.1	2.8	12.3	3.4	15.2	0.021	0.032	
Eagle Clear 80 EC	4927004	6	1.65	42	1.3	5.9	2.1	9.1	2.8	12.3	3.4	15.2	0.021	0.032	
Eagle Opaque 80	L040P806M	6	1.65	42	1.9	8.2	3.2	14	4.4	19.6	5.6	24.7	0.023	0.034	
Eagle Orange 85	L040G856M	6	1.89	48	1.7	7.7	2.7	11.8	3.5	15.8	4.4	19.4	0.023	0.034	
Eagle Clear 85	L04C856M	6	1.89	48	1.7	7.7	2.7	11.8	3.5	15.8	4.4	19.4	0.023	0.034	
Eagle Blue 85	L04BL856M	6	1.89	48	1.7	7.7	2.7	11.9	3.6	15.8	4.4	19.5	0.023	0.034	
Eagle Green 89	4905406	6	2.13	54	2.9	12.8	4.7	21	6.5	28.9	8.1	36.1	0.023	0.034	
Eagle Green 89 Textured	4905306	6	2.13	54	2.1	9.3	3.4	15.3	4.7	21	5.9	26.2	0.023	0.034	
Eagle White 40D	L04BY406M	6	2.83	72	7.5	33.3	11.5	51.2	15.1	67.1	18.2	80.9	0.022	0.033	
Eagle Blue 80 EC QC	4928021	6 × 2.5†	1.65	42	0.6	2.5	0.9	3.9	1.2	5.3	1.5	6.6	0.018	0.026	
Eagle Clear 85 QC	L04QC856M	6 × 2.5†	1.89	48	0.7	3.2	1.1	5	1.5	6.7	1.9	8.3	0.019	0.028	
Eagle Red 85 QC	L04QR856M	6 × 2.5†	1.89	48	0.7	3.2	1.1	5	1.5	6.7	1.9	8.3	0.019	0.028	
Eagle Blue 85 QC	L04QB856M	6 × 2.5†	1.89	48	0.7	3.2	1.1	5	1.5	6.7	1.9	8.3	0.019	0.028	
Eagle Blue 80 MD	4941101	1/4	6.3	1.75	44	1.3	6	2.1	9.2	2.8	12.3	3.4	15.3	0.024	0.035
Eagle Opaque 80	4940003	1/4	6.3	1.75	44	2.1	9.2	3.5	15.7	4.9	22	6.2	27.7	0.026	0.039
Eagle Orange 85	1032008	1/4	6.3	2	51	1.9	8.6	3	13.3	4	17.7	4.9	21.9	0.026	0.038
Eagle Clear 85	4908012	1/4	6.3	2	51	1.9	8.6	3	13.3	4	17.7	4.9	21.9	0.026	0.038
Eagle Red 90	4940023	1/4	6.3	2.5	64	10.6	47.2	15.3	67.9	19.2	85.5	22.5	100	0.026	0.038
Eagle Clear 95	4907012	1/4	6.3	2.5	64	3.6	16.1	5.4	24	6.9	30.8	8.2	36.6	0.026	0.039
Eagle Clear 85 QC	4934012	.250 × .098†	2	51	0.8	3.7	1.3	5.7	1.7	7.7	2.1	9.5	0.022	0.032	
Eagle Yellow 85 QC	4934022	.250 × .098†	2	51	0.8	3.7	1.3	5.7	1.7	7.7	2.1	9.5	0.022	0.032	
Eagle Blue 80 EC	4928005	1/4	6.3	1.74	44	1.5	6.6	2.3	10.2	3.1	13.7	3.8	17	0.023	0.035
Eagle Blue 85	L04BL856.3	1/4	6.3	2	51	1.9	8.6	3	13.3	4	17.7	4.9	21.8	0.025	0.037
QC Connectors	L04CON6S	25/pack													
REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 1% (N)	(lbs) 2% (N)	(lbs) 3% (N)	(lbs) 4% (N)	lbs/ft	kg/m				
Eagle Orange 85	L040G856MR	6	2.36	60	0.7	3.2	2.5	11	4.8	21.5	6.9	30.8	0.023	0.034	
Eagle Green 89	L04G896MSR	6	2.36	60	2.4	10.6	7.2	32	14.7	65.5	22.7	100.9	0.023	0.034	
Eagle Green 89 Textured	4940057	6	2.36	60	3.3	14.6	9.9	43.9	20.2	90	31.2	138.8	0.023	0.034	
Eagle Orange 85	4940058	1/4	6.3	2.5	64	0.8	3.6	2.8	12.3	5.4	24.1	7.8	34.6	0.026	0.038
Eagle Hyfen 85	5218012	1/4	6.3	2.75	70	3.7	16.5	12.4	55.2	20	89	27.8	123.7	0.026	0.038

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Conveying - Eagle Polyurethane

7mm, 8mm, 5/16" Round Cross Sections



Round

Round Belting

NON-REINFORCED		Part Number*	Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	Working Load @ Percent Tension								Weight	
Material and Color					4% (lbs) (N)		6% (lbs) (N)		8% (lbs) (N)		10% (lbs) (N)		lbs/ft	kg/m
Eagle Orange 85	L040G857M		7	2.2 56	2.4 10.5	3.6 16.2	4.8 21.6	6 26.6	0.031	0.046				
Eagle Clear 85	L04C857M		7	2.2 56	2.4 10.5	3.6 16.2	4.8 21.6	6 26.6	0.031	0.046				
Eagle Green 89	4999637		7	2.48 63	3.9 17.4	6.4 28.6	8.8 39.3	11 49.1	0.031	0.046				
Eagle Green 89 Textured	4905307		7	2.48 63	2.9 12.7	4.7 20.9	6.4 28.7	8.1 35.8	0.031	0.046				
Eagle Red 90	L04R907		7	2.76 70	12.9 57.4	18.6 82.7	23.4 104.1	27.4 121.8	0.031	0.047				
Eagle Blue 80 MD	4941102	5/16		2.19 56	2.1 9.4	3.3 14.5	4.3 19.3	5.5 24.3	0.037	0.055				
Eagle Orange 85	1032010	5/16		2.5 64	3 13.5	4.7 20.8	6.2 27.7	7.7 34.1	0.04	0.059				
Eagle Clear 85	4908015	5/16		2.5 64	3 13.5	4.7 20.8	6.2 27.7	7.7 34.1	0.04	0.059				
Eagle Clear 95	4907015	5/16		3.13 79	5.7 25.2	8.4 37.4	10.8 48.1	12.9 57.2	0.041	0.061				
Eagle Clear 85 QC	4934015	.313 × .126†		2.5 64	1.3 5.7	2 8.9	2.7 11.9	3.3 14.7	0.034	0.05				
Eagle Yellow 85 QC	4934023	.313 × .126†		2.5 64	1.3 5.7	2 8.9	2.7 11.9	3.3 14.7	0.034	0.05				
Eagle Blue 80 EC	4928006		8	2.2 56	2.4 10.5	3.6 16.2	4.8 21.5	6.1 26.9	0.038	0.056				
Eagle Clear 80 EC	4927006		8	2.2 56	2.4 10.5	3.6 16.2	4.8 21.5	6.1 26.9	0.038	0.056				
Eagle Opaque 80	L040P808M		8	2.2 56	3.3 14.7	5.6 25	7.8 34.9	9.9 43.9	0.041	0.061				
Eagle Orange 85	L040G858M		8	2.52 64	3.1 13.7	4.7 21.1	6.3 28.1	7.8 34.7	0.041	0.06				
Eagle Clear 85	L04C858		8	2.52 64	3.1 13.7	4.7 21.1	6.3 28.1	7.8 34.7	0.041	0.06				
Eagle Blue 85	L04BL858M		8	2.52 64	3.1 13.7	4.7 21.1	6.3 28.1	7.8 34.7	0.041	0.06				
Eagle Green 89	L04G898MS		8	2.83 72	5.1 22.8	8.4 37.4	11.5 51.3	14.4 64.1	0.04	0.06				
Eagle Green 89 Textured	4905308		8	2.83 72	3.7 16.6	6.1 27.2	8.4 37.3	10.5 46.7	0.04	0.06				
Eagle Red 90	4940024		8	3.15 80	16.8 74.9	24.3 107.9	30.5 135.8	35.7 158.9	0.041	0.061				
Eagle Beige 95	L04BE958		8	3.15 80	13.6 60.5	19.3 85.7	24.1 107	28.1 125.1	0.042	0.062				
Eagle White 40D	L04BY408M		8	3.78 96	13.3 59.2	20.5 91	26.8 119.3	32.3 143.8	0.04	0.059				
Eagle Blue 80 EC QC	4928022	8 × 3.2‡		2.2 56	1 4.6	1.6 7.1	2.2 9.6	2.7 11.9	0.032	0.047				
Eagle Clear 85 QC	L04QC858M	8 × 3.2‡		2.52 64	1.3 5.8	2 9	2.7 12.1	3.4 14.9	0.034	0.051				
Eagle Red 85 QC	L04QR858M	8 × 3.2‡		2.52 64	1.3 5.8	2 9	2.7 12.1	3.4 14.9	0.034	0.051				
Eagle Blue 85 QC	L04QB858M	8 × 3.2‡		2.52 64	1.3 5.7	2 8.9	2.7 11.9	3.3 14.6	0.034	0.051				
QC Connectors	L04CON8S	25/pack												
REINFORCED		Part Number*	Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	Working Load @ Percent Tension								Weight	
Material and Color					1% (lbs) (N)		2% (lbs) (N)		3% (lbs) (N)		4% (lbs) (N)		lbs/ft	kg/m
Eagle Green 89	L04G897MRS		7	2.76 70	3.3 14.5	9.8 43.5	20.1 89.2	30.9 137.6	0.031	0.046				
Eagle Green 89 Textured	4940050		7	2.76 70	4.5 19.9	13.5 59.9	27.6 122.7	42.5 189.2	0.031	0.046				
Eagle Orange 85	4940059	5/16		3.13 79	1.3 5.6	4.3 19.3	8.5 37.6	12.1 54	0.04	0.059				
Eagle Hyfen 85	5218015	5/16		3.44 87	3.7 16.5	12.4 55.2	20 89	27.8 123.7	0.04	0.059				
Eagle Orange 85	L040G858R		8	3.15 80	1.3 5.7	4.4 19.6	8.6 38.2	12.3 54.8	0.041	0.06				
Eagle Green 89	L04G898MRS		8	3.15 80	4.3 18.9	12.8 56.8	26.2 116.4	40.4 179.5	0.04	0.06				
Eagle Green 89 Textured	4940051		8	3.15 80	5.8 26	17.6 78.2	36 160.1	55.5 246.8	0.04	0.06				
Eagle Beige 95	L04BE958R		8	3.78 96	3.8 16.9	7 31.1	10.4 46.3	13.6 60.5	0.042	0.062				

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

9mm, 9.5mm, 3/8" Round Cross Sections

Round Belting



NON-REINFORCED		Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color	Part Number*					4% (lbs) (N)	6% (lbs) (N)	8% (lbs) (N)	10% (lbs) (N)	12% (lbs) (N)	14% (lbs) (N)	16% (lbs) (N)	18% (lbs) (N)	lbs/ft	kg/m
Eagle Green 89 Textured	L04G899		9	3.19	81	4.7	21	7.7	34.4	10.6	47.2	13.3	59	0.051	0.076
Eagle Blue 80 MD	4941103	3/8	9.5	2.63	67	3	13.5	4.7	20.9	6.3	27.9	7.8	34.8	0.054	0.08
Eagle Opaque 80	4940005	3/8	9.5	2.63	67	4.7	20.8	8	35.4	11.1	49.4	14	62.3	0.058	0.087
Eagle Orange 85	1032012	3/8	9.5	3	76	4.4	19.4	6.7	29.9	9	39.9	11.1	49.2	0.057	0.086
Eagle Orange 89 SureConnect	4934145	3/8	9.5	3	76	4.4	19.4	6.7	29.9	9	39.9	11.1	49.2	0.057	0.086
Eagle Clear 85	4908018	3/8	9.5	3	76	4.4	19.4	6.7	29.9	9	39.9	11.1	49.2	0.057	0.086
Eagle Red 90	4940025	3/8	9.5	3.75	95	23.9	106.1	34.4	152.9	43.3	192.4	50.6	225.1	0.058	0.086
Eagle Clear 95	4907018	3/8	9.5	3.75	95	8.2	36.3	12.1	53.9	15.6	69.3	18.5	82.4	0.059	0.088
Eagle Clear 85 QC	4934018	.375 × .152†		3	76	1.8	8.2	2.9	12.7	3.8	17.1	4.7	21	0.048	0.071
Eagle Yellow 85 QC	4934025	.375 × .152†		3	76	1.8	8.2	2.9	12.7	3.8	17.1	4.7	21	0.048	0.071
Eagle Blue 80 EC	4928007	3/8	9.5	2.62	67	3.4	15	5.2	23.2	7	31	8.7	38.7	0.053	0.079
Eagle Blue 85	L04BL859.5M	3/8	9.5	3	76	4.4	19.4	6.7	29.9	9	39.9	11.1	49.2	0.057	0.085
Eagle Green 89	L04G899.5MS	3/8	9.5	3.39	86	7.2	32.1	11.8	52.7	16.3	72.4	20.3	90.4	0.057	0.084
Eagle Blue 80 EC QC	4928023		9.5 × 3.8†	2.64	67	1.5	6.4	2.3	10.1	3	13.5	3.8	16.8	0.045	0.067
QC Connectors	L04CON10S	20/pack													
SureConnect Connectors	4935031	5/pack													
REINFORCED		Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color	Part Number*					1% (lbs) (N)	2% (lbs) (N)	3% (lbs) (N)	4% (lbs) (N)	5% (lbs) (N)	6% (lbs) (N)	7% (lbs) (N)	8% (lbs) (N)	lbs/ft	kg/m
Eagle Orange 85	4940060	3/8	9.5	3.75	95	1.8	8	6.2	27.8	12.2	54.2	17.5	77.8	0.057	0.086
Eagle Hyfen 85	5218018	3/8	9.5	4.13	105	7.3	32.5	26.2	116.5	43.5	193.5	57.4	255.3	0.057	0.086

Can Cable

REINFORCED		Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color	Part Number‡					1% (lbs) (N)	2% (lbs) (N)	3% (lbs) (N)	4% (lbs) (N)	5% (lbs) (N)	6% (lbs) (N)	7% (lbs) (N)	8% (lbs) (N)	lbs/ft	kg/m
Blue 55D Can Cable	4816019	3/8	9.5	12	305	18.1	80.4	42.9	190.6	79.4	353.1	118.4	526.5	0.057	0.086
Natural 55D Can Cable	4816018	3/8	9.5	12	305	18.1	80.4	42.9	190.6	79.4	353.1	118.4	526.5	0.057	0.086
Natural 63D Can Cable	4899006	3/8	9.5	12	305	18.1	80.4	42.9	190.6	79.4	353.1	118.4	526.5	0.058	0.087
Red 50D LCF Can Cable	4816020	3/8	9.5	10	254	23.8	105.9	57.8	257.2	104.3	463.8	152.3	677.2	0.058	0.087
Green 63D Can Cable	4817018	3/8	9.5	12	305	18.1	80.4	42.9	190.6	79.4	353.1	118.4	526.5	0.058	0.087
Blue 55D Aramid Can Cable	4899012	3/8	9.5	12	305	41.7	185.5	149.1	663.2	281.1	1250.4	—	—	0.057	0.086

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Conveying - Eagle Polyurethane

10mm, 12mm, 12.7mm, 1/2" Round Cross Sections

Round Belting



Round

NON-REINFORCED					Working Load @ Percent Tension								Weight		
Material and Color	Part Number*				Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	4% (N) (lbs)		6% (N) (lbs)		8% (N) (lbs)		10% (N) (lbs)		lbs/ft
Eagle Blue 80 EC	4928008	10	2.76	70	3.7	16.4	5.8	25.6	7.7	34.1	9.6	42.6	0.059	0.088	
Eagle Clear 80 EC	4927008	10	2.76	70	3.7	16.4	5.8	25.6	7.7	34.1	9.6	42.6	0.059	0.088	
Eagle Opaque 80	L040P8010M	10	2.76	70	5.1	22.9	8.8	39	12.2	54.5	15.4	68.6	0.064	0.096	
Eagle Orange 85	L040G8510M	10	3.15	80	4.8	21.4	7.4	33	9.9	44	12.2	54.2	0.063	0.094	
Eagle Clear 85	L04C8510M	10	3.15	80	4.8	21.4	7.4	33	9.9	44	12.2	54.2	0.063	0.094	
Eagle Blue 85	L04BL8510M	10	3.15	80	4.8	21.4	7.4	33	9.9	44	12.2	54.2	0.063	0.094	
Eagle Green 89	L04G8910MS	10	3.54	90	8	35.4	13.1	58.2	18	79.9	22.4	99.8	0.063	0.093	
Eagle Green 89 Textured	4905310	10	3.54	90	5.8	25.8	9.5	42.3	13.1	58.1	16.3	72.5	0.063	0.093	
Eagle Green 89 T SureConnect	4934141	10	3.54	90	5.8	25.8	9.5	42.3	13.1	58.1	16.3	72.5	0.063	0.093	
Eagle Red 90	L04R9010M	10	3.94	100	26.3	116.9	37.9	168.4	47.6	211.9	55.7	248	0.064	0.095	
Eagle Beige 95	L04BE9510M	10	3.94	100	21.2	94.5	30.1	133.8	37.6	167.2	43.9	195.5	0.065	0.097	
Eagle White 40D	L04BY4010M	10	4.72	120	20.8	92.5	32	142.2	41.9	186.5	50.5	224.6	0.062	0.092	
Eagle Blue 55D	L04BY5510M	10	5.12	130	39.3	174.6	60.4	268.7	78.5	349.2	93	413.8	0.063	0.094	
Eagle Red 85 QC	L04QR8510M	10 × 3.8 [†]	3.15	80	2.1	9.3	3.2	14.4	4.3	19.3	5.3	23.8	0.054	0.081	
Eagle Blue 85 QC	L04QB8510M	10 × 3.8 [†]	3.15	80	2.1	9.3	3.2	14.4	4.3	19.3	5.3	23.8	0.054	0.081	
Eagle Orange 85	L040G8512M	12	3.78	96	6.9	30.8	10.7	47.5	14.2	63.3	17.5	78	0.091	0.136	
Eagle Clear 85	L04C8512M	12	3.78	96	6.9	30.8	10.7	47.5	14.2	63.3	17.5	78	0.091	0.136	
Eagle Green 89	L04G8912MS	12	4.25	108	11.5	51.2	18.9	84.1	26	115.5	32.4	144.3	0.09	0.135	
Eagle Green 89 Textured	4905312	12	4.25	108	8.4	37.3	13.8	61.2	18.9	84.1	23.6	105.1	0.091	0.135	
Eagle Green 89 T SureConnect	4934142	12	4.25	108	8.4	37.3	13.8	61.2	18.9	84.1	23.6	105.1	0.091	0.135	
Eagle Red 90	L04R9012M	12	4.72	120	37.8	168.4	54.5	242.5	68.6	305.2	80.3	357.2	0.092	0.137	
Eagle Red 85 QC	L04QR8512M	12 × 5.2 [†]	3.78	96	2.8	12.6	4.4	19.7	5.9	26.3	7.3	32.5	0.074	0.11	
Eagle Blue 85 QC	L04QB8512	12 × 5.2 [†]	3.78	96	2.8	12.6	4.4	19.7	5.9	26.3	7.3	32.5	0.074	0.11	
Eagle Blue 80 MD	4941105	1/2	12.7	3.5	89	5.4	23.9	8.4	37.3	11.2	49.7	13.8	61.6	0.095	0.142
Eagle Orange 85	1032016	1/2	12.7	4	102	7.8	34.5	12	53.2	16	71	19.6	87.4	0.102	0.152
Eagle Orange 89 SureConnect	4934146	1/2	12.7	4	102	7.8	34.5	12	53.2	16	71	19.6	87.4	0.102	0.152
Eagle Clear 85	4908024	1/2	12.7	4	102	7.8	34.5	12	53.2	16	71	19.6	87.4	0.102	0.152
Eagle Red 90	4940026	1/2	12.7	5	127	42.4	188.6	61.1	271.7	76.9	342	90	400.2	0.103	0.153
Eagle Clear 95	4907024	1/2	12.7	5	127	14.5	64.6	21.6	95.9	27.7	123.1	32.9	146.4	0.105	0.156
Eagle Clear 85 QC	4934024	.500 × .205 [†]	4	102	3.3	14.5	5.1	22.5	6.8	30.2	8.4	37.2	0.085	0.126	
Eagle Yellow 85 QC	4934026	.500 × .205 [†]	4	102	3.3	14.5	5.1	22.5	6.8	30.2	8.4	37.2	0.085	0.126	
Eagle Red 85	L04R8512.7	1/2	12.7	4	102	7.8	34.5	12	53.2	16	71	19.6	87.4	0.102	0.152
Eagle Blue 85	L04BL8512.7	1/2	12.7	4	102	7.8	34.5	12	53.2	15.9	70.9	19.6	87.4	0.102	0.152
QC Connectors	L04CON10S	20/pack (Use for 3/8" and 10mm)													
QC Connectors	L04CON13S	20/pack (Use for 1/2" and 12-13mm)													
SureConnect Connectors	4935031	5/pack (Use for 10mm)													
SureConnect Connectors	4935032	5/pack (Use for 1/2" and 12mm)													
REINFORCED					Working Load @ Percent Tension								Weight		
Material and Color	Part Number*				Dimensions Ø (in) (mm)	Minimum Pulley Ø (in) (mm)	1% (N) (lbs)		2% (N) (lbs)		3% (N) (lbs)		4% (N) (lbs)		lbs/ft
Eagle Orange 85	L040G8510MR	10	3.94	100	2	8.8	6.9	30.6	13.4	59.7	19.3	85.7	0.063	0.094	
Eagle Green 89	L04G8910MRS	10	3.94	100	6.6	29.5	20	88.8	40.9	181.9	63.1	280.5	0.063	0.093	
Eagle Green 89 Textured	4940052	10	3.94	100	9.1	40.6	27.5	122.1	56.2	250.1	86.7	385.6	0.063	0.093	
Eagle Beige 95	L04BE9510R	10	4.72	120	6	26.7	11	48.9	16.2	72.1	21.2	94.3	0.065	0.097	
Eagle Orange 85	L040G8512R	12	4.72	120	2.9	12.7	9.9	44.1	19.3	85.9	27.7	123.4	0.091	0.136	
Eagle Green 89	L04G8912MRS	12	4.72	120	9.6	42.6	28.8	127.9	58.9	262	90.8	404	0.09	0.135	
Eagle Green 89 Textured	4940053	12	4.72	120	13.2	58.5	39.5	175.9	81	360.2	124.9	555.4	0.09	0.135	
Eagle Orange 85	4940061	1/2	12.7	5	127	3.2	14.2	11.1	49.4	21.6	96.3	31.1	138.3	0.102	0.152
Eagle Hyfen 85	5218024	1/2	12.7	5.5	140	7.3	32.5	26.2	116.5	43.5	193.5	57.4	255.3	0.102	0.152

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Belt has a .156" radius guide.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

13mm, 9/16" Round Cross Sections

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 4% (N)	(lbs) 6% (N)	(lbs) 8% (N)	(lbs) 10% (N)	lbs/ft	kg/m				
Eagle Clear 85 QC	L04QC8513	13 x 5.2†		4.09	104	3.5	15.3	5.4	23.8	7.2	31.9	8.9	39.4	0.09	0.134
Eagle Red 85 QC	L04QR8513M	13 x 5.2†		4.09	104	3.5	15.3	5.4	23.8	7.2	31.9	8.9	39.4	0.09	0.134
Eagle Blue 80 MD	4941106	9/16		3.94	100	6.9	30.6	10.6	47.1	14.2	63	17.6	78.2	0.121	0.18
Eagle Orange 85	1032018	9/16		4.5	114	9.8	43.7	15.1	67.3	20.2	89.8	24.9	110.6	0.129	0.192
Eagle Orange 89 SureConnect	4934147	9/16		4.5	114	9.8	43.7	15.1	67.3	20.2	89.8	24.9	110.6	0.129	0.192
Eagle Clear 85	4908027	9/16		4.5	114	9.8	43.7	15.1	67.3	20.2	89.8	24.9	110.6	0.129	0.192
Eagle Red 90	4940036	9/16		5.63	143	53.7	238.6	77.3	343.8	97.3	432.7	113.8	506.3	0.13	0.194
Eagle Clear 95	4907027	9/16		5.63	143	18.4	81.7	27.3	121.3	35	155.8	41.7	185.3	0.133	0.197
QC Connectors	L04CON13S	20/pack													
SureConnect Connectors	4935033	5/pack													
REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 1% (N)	(lbs) 2% (N)	(lbs) 3% (N)	(lbs) 4% (N)	lbs/ft	kg/m				
Eagle Orange 85	4940062	9/16		5.63	143	4.1	18	14	62.5	27.4	121.8	39.3	174.9	0.129	0.192
Eagle Hyfen 85	5218027	9/16		6.19	157	16.7	74.3	36.6	162.8	58	258	75.8	337.2	0.129	0.192

15mm, 16mm, 5/8" Round Cross Sections

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 4%	(N) 4%	(lbs) 6%	(N) 6%	(lbs) 8%	(N) 8%	(lbs) 10%	(N) 10%	lbs/ft	kg/m
Eagle Opaque 80	L040P8015M		15	4.13	105	11.6	51.6	19.7	87.7	27.6	122.6	34.7	154.4	0.145	0.216
Eagle Blue 85	L04BL8515		15	4.72	120	10.8	48.1	16.7	74.2	22.2	99	27.4	121.9	0.142	0.212
Eagle Green 89	L04G8915MS		15	5.31	135	18	80	29.5	131.4	40.6	180.5	50.7	225.5	0.141	0.21
Eagle Green 89 Textured	4905315		15	5.31	135	13.1	58.1	21.5	95.4	29.5	131.1	36.8	163.8	0.141	0.21
Eagle Green 89 T SureConnect	4934143		15	5.31	135	13.1	58.1	21.5	95.4	29.5	131.1	36.8	163.8	0.141	0.21
Eagle Red 90	4999315		15	5.91	150	59.1	262.9	85.2	378.8	107.2	476.8	125.4	557.9	0.144	0.214
Eagle Beige 95	L04BE9515M		15	5.91	150	47.8	212.5	67.7	301.2	84.6	376.2	98.9	440	0.146	0.217
Eagle White 40D	L04BY4015		15	7.09	180	46.8	208.1	71.9	319.9	94.3	419.6	113.6	505.4	0.139	0.207
Eagle Blue 55D	L04BY5515		15	7.68	195	88.3	392.9	135.9	604.6	176.7	785.8	209.3	931	0.142	0.212
Eagle Blue 80 MD	4941107	5/8		4.38	111	8.4	37.5	13.1	58.2	17.4	77.6	21.7	96.4	0.149	0.222
Eagle Orange 85	1032020	5/8		5	127	12.1	53.9	18.7	83.1	24.9	110.8	30.7	136.5	0.16	0.238
Eagle Clear 85	4908030	5/8		5	127	12.1	53.9	18.7	83.1	24.9	110.8	30.7	136.5	0.16	0.238
Eagle Clear 95	4907030	5/8		6.25	159	22.7	100.9	33.7	149.8	43.2	192.3	51.4	228.7	0.164	0.243
Eagle Clear 85 QC	4934030	.625 x .273†		5	127	5	22.1	7.7	34.2	10.3	45.9	12.7	56.6	0.129	0.192
Eagle Yellow 85 QC	4934020	.625 x .273†		5	127	5	22.1	7.7	34.2	10.3	45.9	12.7	56.6	0.129	0.192
Eagle Clear 85 QC	L04QC8516M		16 x 6.8†	5.04	128	5.1	22.7	7.9	35.2	10.6	47.2	13.1	58.2	0.133	0.198
Eagle Red 85 QC	L04QR8516M		16 x 6.8†	5.04	128	5.1	22.7	7.9	35.2	10.6	47.2	13.1	58.2	0.133	0.198
QC Connectors	4935030	15/pack													
SureConnect Connectors	4935033	5/pack													
REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 1%	(N) 1%	(lbs) 2%	(N) 2%	(lbs) 3%	(N) 3%	(lbs) 4%	(N) 4%	lbs/ft	kg/m
Eagle Orange 85	L04OG8515MR		15	5.91	150	4.5	19.9	15.5	68.9	30.2	134.3	43.3	192.8	0.142	0.212
Eagle Green 89	L04G8915MRS		15	5.91	150	15	66.5	44.9	199.9	92	409.3	141.9	631.2	0.141	0.21
Eagle Green 89 Textured	4940054		15	5.91	150	20.6	91.5	61.8	274.8	126.5	562.8	195.1	867.9	0.141	0.21
Eagle Beige 95	L04BE9515R		15	7.09	180	13.5	60.1	24.7	109.9	36.5	162.4	47.8	212.6	0.146	0.217
Eagle Hyfen 85	5218030	5/8		6.88	175	16.7	74.3	36.6	162.8	58	258	75.8	337.2	0.16	0.238

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Belt has a .156" radius guide.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

18mm, 3/4" Round Cross Sections

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 4% (N)	(lbs) 6% (N)	(lbs) 8% (N)	(lbs) 10% (N)	lbs/ft	kg/m				
Eagle Green 89	L04G8918MS	18	6.38	162	25.9	115.2	42.5	189.2	58.4	259.9	73	324.6	0.203	0.303	
Eagle Green 89 Textured	4940091	18	6.38	162	18.8	83.7	30.9	137.5	42.4	188.8	53	235.9	0.203	0.303	
Eagle White 40D	L04BY4018	18	8.5	216	67.4	299.7	103.6	460.7	135.8	604.2	163.6	727.8	0.2	0.298	
Eagle Blue 55D	L04BY5518	18	9.21	234	127.2	565.8	195.7	870.6	254.4	1131.6	301.4	1340.7	0.205	0.305	
Eagle Orange 85	1032024	3/4	6	152	17.5	77.7	26.9	119.6	35.9	159.6	44.2	196.6	0.23	0.342	
Eagle Clear 85	4908033	3/4	6	152	17.5	77.7	26.9	119.6	35.9	159.6	44.2	196.6	0.23	0.342	
Eagle Clear 95	4907033	3/4	7.5	191	32.7	145.3	48.5	215.7	62.3	277	74	329.4	0.236	0.351	
SureConnect Connectors	4935034	5/pack (Use for 18mm and 3/4")													
REINFORCED	Part Number*	Dimensions Ø (in) (mm)		Minimum Pulley Ø (in) (mm)		Working Load @ Percent Tension								Weight	
Material and Color						(lbs) 1% (N)	(lbs) 2% (N)	(lbs) 3% (N)	(lbs) 4% (N)	lbs/ft	kg/m				
Eagle Green 89 Textured	4940055	18	7.09	180	29.6	131.7	89	395.7	182.2	810.5	280.9	1249.7	0.203	0.303	
Eagle Orange 85	4940064	3/4	7.5	191	7.2	32.1	25	111.1	48.7	216.6	69.9	311	0.23	0.342	
Eagle Hyfen 85	5218033	3/4	8.25	210	16.7	74.3	36.6	162.8	58	258	75.8	337.2	0.23	0.342	

20mm Round Cross Section

Round Belting



NON-REINFORCED	Part Number*	Dimensions Ø (in)	(mm)	Minimum Pulley Ø (in)	(mm)	Working Load @ Percent Tension								Weight	
Material and Color						(lbs)	4% (N)	(lbs)	6% (N)	(lbs)	8% (N)	(lbs)	10% (N)	(lbs)	12% (N)
Eagle Green 89	L04G8920MS		20	7.09	180	32	142.3	52.5	233.5	72.1	320.8	90.1	400.8	0.251	0.374
Eagle Green 89 Textured	4940092		20	7.09	180	23.2	103.4	38.1	169.7	52.4	233.1	65.5	291.2	0.251	0.374
Eagle White 40D	L04BY4020		20	9.45	240	83.2	370	127.9	568.7	167.7	745.9	202	898.6	0.247	0.368



* Standard package length 100' / 30.5m
† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)
‡ Standard Can Cable package length 500' reel
Dimensions are for reference only.
All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.