

Medium LED Flash Signal Light

XPE



Colors Red, Amber, Green, Blue

Globe Polycarbonate resin with superb shock resistance and heat resistance

The XPE Series features a 162mm diameter, a triple-flash rate pattern, and multiple voltage options.

- Triple-flash pattern with 110 flash rate per minute
- Durable structure with stainless steel bolts
- Built-in dimmer function
- Available colors: Red, Amber, Green, Blue

Specifications

Model	Rated Voltage	Power Consumption	Flashing Rate	Mass
XPE-12	12V DC	5.0W	110±10 /minute (Triple flash)	1.2kg
XPE-24	24V DC	4.5W		
XPE-M2	100/200/230V AC	5.7W		

Model Code

XPE-12-R

Model

Rated Voltage

Colors


12	12V DC	R	Red
24	24V DC	Y	Amber
M2	100/200/230V AC	G	Green
		B	Blue

Optional Parts


For details, see pages 182 to 187.

Optional Parts	Model
Wallmount Bracket	SZ-023
Wallmount Bracket	SZ-008

Dimensions (mm)



Wiring Diagram



Large LED Flash Signal Light

XME



Colors Red, Amber, Blue

Globe Polycarbonate resin with superb shock resistance and heat resistance

The XME Series features a 182mm diameter, a triple-flash rate pattern, and multiple voltage options.

- Triple-flash pattern with 110 flash rate per minute
- Durable structure with stainless steel lens mounts and bolts
- Built-in dimmer function
- Available colors: Red, Amber, Blue

Specifications

Model	Rated Voltage	Power Consumption	Flashing Rate	Mass
XME-12	12V DC	5.0W	110±10 /minute (Triple flash)	1.8kg
XME-24	24V DC	4.5W		
XME-M2	100/200/230V AC	5.7W		

Model Code

XME-12-R

Model

Rated Voltage

Colors


12	12V DC	R	Red
24	24V DC	Y	Amber
M2	100/200/230V AC	B	Blue

Optional Parts

For details, see pages 182 to 187.

Optional Parts	Model
Wallmount Bracket	SZ-008

Dimensions (mm)



Wiring Diagram

