



GRIPPER SEAT COVER INSTALLATION INTSTRUCTIONS



PREPARE THE FOLLOWING TOOLS FOR THE INSTALLATION PROCESS:

- Screwdriver: Flat blade
- Small needle nose pliers
- Staple Gun: Pneumatic or electric for best results
- Staples: 3/8" (9.5mm) length or shorter
- Damp rag
- X-Acto knife or razor blade
- Heat Gun / Hair dryer (optional)

INSTALLATION NOTE: You can lightly warm up the gripper seat cover with a heat gun or hair dryer to relax and expand the materials for installation. However, be careful not to overheat the materials.

- 1) Remove the seat from the bike or sled and clean the underside with a damp rag.
- 2) Remove the staples from the existing seat cover with the screwdriver and needle nose pliers.
- 3) Place the Stompgrip gripper seat cover on the seat and visualize the line-up.
- 4) Rotate the front seam over the nose of the seat so it is hidden underneath. This will also reduce direct stress to the seam.
- 5) Center the gripper seat cover left to right, lightly pull back and tighten, but do not over-stretch the gripper seat cover front to rear. Center the gripper seat cover left to right at the tail, turn the seat over, and tack the first staple.
- 6) Check that the gripper seat cover is centered in the front of the seat, lightly pull back and tighten, but do not over-stretch the gripper seat cover rear to front. Turn the seat over and tack the second staple.
- 7) Pull down on the material at the center of the seat making sure it is centered and stretch material eliminating any wrinkles on the top of the seat. Hold the material down and turn the seat over and place a staple in the middle edge on both sides.



- 8) Turn the seat back over and pull at the front of the gripper seat cover making sure it is centered and stretch the material down so that there are no wrinkles on the top. Turn the seat over and staple both sides of the seat.
- 9) Turn the seat back over and pull the rear of the gripper seat cover down making sure it is centered and stretch the material down so that there are no wrinkles on the top. Turn the seat over and staple both sides of the seat.
- 10) Staple along the edges of the seat tacking a staple approximately one-half inch from each other. Be sure to pull down on the material as you are stapling the material down and check to avoid wrinkles on the top.
- 11) Once the gripper seat cover is stapled to the seat trim the excess material underneath the seat especially where it may have line-up or wear points that coincide with the bike or sled frame.
- 12) Clean the seat and gripper seat cover with a damp rag and/or mild cleaner like Windex.
- 13) Install the seat on your bike or sled.
- 14) Go ride!

If you have any questions check out our installation videos:
<https://stompgrip.com/media/installation> or you can contact us.

STOMPGRIP, Inc.
888-612-5240 • 714-894-9388 • Fax 714-894-4648
customerservice@stompgrip.com
WWW.STOMPGRIP.COM