



TURN TO YOKOHAMA, AND TURN ON TECHNOLOGY.

World-class technology and worldwide availability make Yokohama Off-the-Road tires a leader you can count on. From underground mining to some of the largest earth moving trucks in the field, Yokohama has more than 40 different designs. And when special applications require customization, no one matches Yokohama's service to its customers. Yokohama's staff of Sales, Sales Engineers and Customer Service Professionals will partner with you to design tires that are needed for your unique applications.

So turn to Yokohama for all your tire applications, and turn on world-class technology.



Y524Z

- For use on loaders and dozers
- Specially designed half slick asymmetric tread pattern
- Superior tread and sidewall cut resistance

Y523

- For use on dump trucks
- Engineered for use under highly abrasive conditions
- Better tread cut and impact resistance at tread crown area
- High tensile steel breaker available

RT31+

- 26.5R25
- Designed for use on articulated dump trucks and wheel loaders
- Non-directional tread pattern provides better traction, less vibration
- New compound provides outstanding wear and cut resistance

Y69U

- Designed for rough, underground, low profile mine vehicle applications
- Unique Wavy Side Profile adds armor-like protection to protect sidewalls
- Specially formulated tread compounds resist chipping and cutting

For product information inside the U.S., contact:

Gary Nash
gary.nash@yokohamatire.com

For product information outside of the U.S., contact:

Henry Sakurabayashi
Henry.Sakura@mta.yrc.co.jp

www.yokohamatire.com

 **YOKOHAMA**
TECHNOLOGY THAT DELIVERS™

Tire Size	Part Number	Compound	Groove Depth	Ply Rating and Type	Weight	Rim Size	Inflated Dimensions				Static Radius		Static Width	
							Overall Diameter		Overall Width		(mm)	(Inch)	(mm)	(Inch)
							(mm)	(Inch)	(mm)	(Inch)				

Y524Z L-5

35/65-33	52428	CPC	121	24	T/L	2672	25.00 x 33	2075	81.7	899	35.4	953	37.5	932	36.7
35/65-33	52432	CPC	121	30	T/L	2719	28.00 x 33	2065	81.3	907	35.7	955	37.6	935	36.8
40/65-39	52437	CPC	133	36	T/L	3819	32.00 x 39	2400	94.5	1026	40.4	1107	43.6	1062	41.8
45/64-45	52430	CPC	145	38	T/L	5192	36.00 x 45	2741	107.9	1181	46.5	1260	49.6	1229	48.4
45/65-45	52439	CPC	145	46	T/L	5675	36.00 x 45	2741	107.9	1181	46.5	1260	49.6	1229	48.4
45/65-45	52438	CPC	145	50	T/L	5851	36.00 x 45	2741	107.9	1181	46.5	1260	49.6	1229	48.4
45/65-45	52440	CPC	145	58	T/L	6012	36.00 x 45	2741	107.9	1181	46.5	1260	49.6	1229	48.4

Y523 E-4

1600-25	02326	CPC	75	28	T/L	556	11.25 x 25	1539	60.6	442	17.4	724	28.5	467	18.4
1800-25	52303	CPC	77	28	T/L	789	13.00 x 25	1651	65.0	518	20.4	772	30.4	541	21.3
1800-25	52304	CPC	77	32	T/L	818	13.00 x 25	1539	60.6	442	17.4	772	30.4	541	21.3
1800-33	52315	CPC	71	32	T/L	976	13.00 x 33	1849	72.8	518	20.4	869	34.2	541	21.3
1800-33	52318	RER	71	32	T/L	997	13.00 x 33	1849	72.8	518	20.4	869	34.2	541	21.3
1800-33	02333	CPC/STL	71	36	T/L	1017	13.00 x 33	1850	72.8	518	20.4	869	34.0	542	21.0
1800-33	02335	CPC/STL	71	40	T/L	1124	13.00 x 33	1850	72.8	518	20.4	869	34.0	542	21.0
2100-35	02302	CPC	80	36	T/L	1314	15.00 x 35	2045	80.5	589	23.2	945	37.2	622	24.5
2100-35	52319	RER	80	36	T/L	1314	15.00 x 35	2045	80.5	589	23.2	945	37.2	622	24.5
2400-35	52321	RER	81	36	T/L	1624	17.00 x 35	2146	84.5	665	26.2	991	39.0	711	28.0
2400-35	02303	CPC	81	36	T/L	1612	17.00 x 35	2146	84.5	665	26.2	991	39.0	711	28.0
2100-35	02336	CPC/STL	80	36	T/L	1323	15.00 x 35	2045	80.5	590	23.2	951	37.0	623	25.0
2400-35	52328	CPC/STL	81	36	T/L	1659	17.00 x 35	2147	84.5	666	26.4	999	39.0	710	28.0
2400-35	02334	CPC/STL	81	36	T/L	1592	17.00 x 45	2146	84.5	665	26.2	991	39.0	711	28.0
2400-35	52330	CPC/STL	81	42	T/L	1648	17.00 x 35	2147	84.5	666	26.4	999	39.0	710	28.0
2700-49	02327	CPC/STL	90	42	T/L	2461	19.50 x 49	2679	105.5	748	29.4	1245	49.0	791	31.0
2700-49	02328	CPC/STL	90	48	T/L	2549	19.50 x 49	2679	105.5	748	29.4	1245	49.0	791	31.0
3000-51	52390	RET	90	46	T/L	3579	22.00 x 51	2875	113.2	848	33.4	1339	52.7	897	35.3
3300-51	52329	CPC/STL	104	50	T/L	4780	24.00 x 51	3039	119.6	927	36.5	1404	55.0	985	39.0
2400-35	02320	CPC	81	42	T/L	1569	17.00 x 35	2146	84.5	665	26.2	991	39.0	711	28.0
2400-35	52322	RER	81	42	T/L	1700	17.00 x 35	2146	84.5	665	26.2	991	39.0	711	28.0
2400-49	52339	CPC	81	42	T/L	2277	17.00 x 49	2530	99.6	655	25.8	1184	46.6	696	27.4
2400-49	52371	RER	81	42	T/L	2163	17.00 x 49	2530	99.6	655	25.8	1184	46.6	696	27.4
2700-49	52388	RET	90	42	T/L	2677	19.50 x 49	2680	105.5	747	29.4	1245	49.0	790	31.1
2700-49	52372	RER	90	42	T/L	2655	19.50 x 49	2680	105.5	747	29.4	1245	49.0	790	31.1
2700-49	52340	CPC	90	42	T/L	2655	19.50 x 49	2680	105.5	747	29.4	1245	49.0	790	31.1
2700-49	52341	CPC	90	48	T/L	2711	19.50 x 49	2680	105.5	747	29.4	1245	49.0	790	31.1
2700-49	52373	RER	90	48	T/L	2711	19.50 x 49	2680	105.5	747	29.4	1245	49.0	790	31.1
3000-51	52342	CPC	106	46	T/L	3579	22.00 x 51	2875	113.2	848	33.4	1339	52.7	897	35.3
3300-51	52376	RER	104	50	T/L	4681	24.00 x 51	3038	119.6	927	36.5	1405	55.3	986	38.8
3600-51	52345	CPC	116	50	T/L	5639	26.00 x 51	3198	125.9	1039	40.9	1476	58.1	1090	42.9
4000-57	02307	RET	122	68	T/L	7791	29.00 x 57	3551	139.8	1128	44.4	1623	63.9	1199	47.2
4000-57	02308	RET	122	76	T/L	7979	29.00 x 57	3551	139.8	1128	44.4	1623	63.9	1199	47.2

RT31 + E-3+

26.5R25	03173	CPC	57	**	T/L	832	22.00 x 25	1730	68.1	671	26.4	777	30.6	747	29.4
---------	-------	-----	----	----	-----	-----	------------	------	------	-----	------	-----	------	-----	------

RT31 + L-3+

26.5R25	03174	CPC	58	**	T/L	1017	22.00 x 25	1730	68.1	671	26.4	765	30.1	759	29.9
---------	-------	-----	----	----	-----	------	------------	------	------	-----	------	-----	------	-----	------

Y69U L-4S

1200-24	06907	CPSC	69	16	T/T	311	8.5V x 24	1255	49.4	328	12.9	589	23.2	348	13.7
---------	-------	------	----	----	-----	-----	-----------	------	------	-----	------	-----	------	-----	------

Y69U L-5S

1800-25	06939	CPSC	106	40	T/L	1235	13.00 x 25	1669	65.7	536	21.1	780	30.7	572	22.5
1800-25	06908	CPSC	106	24	T/L	1151	13.00 x 25	1669	65.7	536	21.1	780	30.7	572	22.5
1800-25	06937	CPSC	106	28	T/L	1151	13.00 x 25	1669	65.7	536	21.1	780	30.7	572	22.5
1800-25	06938	CPSC	106	32	T/L	1182	13.00 x 25	1669	65.7	536	21.1	780	30.7	572	22.5
26.5-25	06918	CPSC	114	32	T/L	1726	22.00 x 25	1796	70.7	711	28.0	838	33.0	739	29.1

YOKOHAMA TIRE CORPORATION

Corporate Headquarters
P.O. Box 4550
Fullerton, CA 92834-4550
800.423.4544
714.870.3800

DTR CUSTOMER SERVICE

For Dealer Orders Call: 714.870.3888
Dealer Fax Orders: 714.870.3950

CONSUMER AFFAIRS

800.722.9888

M-393-0904

 **YOKOHAMA**
TECHNOLOGY THAT DELIVERS™