

## Supermarket Two Glass Doors Upright Display Fridge - 1000 Litre

Convenience businesses, pubs, local marts, supermarkets, and even takeout establishments throughout Australia are going to find our supermarket standup display refrigerator with two glass doors ideal. There are five movable shelves and 1000 litres of storage space in our refrigerator. This item features caster wheels.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a 24-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



### Appearance

- Two glass doors
- CAREL iJF LED controller and display
- Internal LED lighting

### Construction

- Powder Coated Body
- 1000L capacity
- 5 adjustable wire shelves per door
- Pre-installed castor wheels
- 35°C/70% humidity ambient temperature
- DONPER, KK480CU1 compressor

### Operation

- The temperature set range is between +2°C and +5°C
- Top and bottom heating stripe
- Electronic temperature control
- Fan-forced ventilated cooling

### Installation and Maintenance

- This unit MUST not be exposed to direct or indirect sunlight or near any heat-radiated appliances.
- This unit MUST be placed leaving a minimal clearance of 20cm from the wall to the back of the unit for ventilation. Please refer to the user manual for details.
- This unit MUST be placed on a levelled surface.
- High-humidity locations will require additional drainage.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

**NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.**

**Errors and omissions excepted (E&OE)**

## SPECIFICATION

AMBIENT TEMPERATURE	35°C / 70% Humidity
CAPACITY	1000 Litres
CURRENT	2.8 Amps
ENERGY CONSUMPTION	7 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	612W
INTERNAL DIMENSION MM	1140(w) x 530(d) x 1555(h)
PACKAGE DIMENSION MM	1310(w) x 780(d) x 2160(h)
PRODUCT DIMENSION MM	1260(w) x 730(d) x 2010(h)
PRODUCT WEIGHT	240 Kg
REFRIGERANT	R290/150g
SHIPPING WEIGHT	260 Kg