

Supermarket Three Doors Upright Display Freezer - 1539L

Attention all store owners and food enthusiasts! Introducing our Supermarket Three Glass Doors Upright Dual Compressors Display Freezer - the ultimate solution for your refrigeration needs. With a whopping 1539 litres of storage space and five movable shelves, this freezer is a game-changer for convenience stores, bars, local marts, supermarkets, and takeaways across Australia. Plus, with the included caster wheels, you can easily move and position this freezer wherever you need it. Keep your products fresh and easily accessible with this top-of-the-line display freezer. Get yours today and watch your business soar to new heights!

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a 24-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Appearance

- Three glass doors
- CAREL iJF LED controller and display
- Internal LED lighting

Construction

- Powder Coated Body
- 1539L capacity
- 5 adjustable wire shelves per door
- Pre-installed castor wheels
- 32°C/70% humidity ambient temperature
- EMBARCO, NEX2180UB x 2 compressor

Operation

- The temperature set range is between -18°C and -22°C
- Top and bottom heating stripe
- Electronic temperature control
- Fan-forced ventilated cooling

Installation and Maintenance

- Installed with a 10 Amp Plug
- This unit MUST be placed on a levelled surface.
- This unit MUST not be exposed to direct or indirect sunlight or near any heat-radiated appliances.
- This unit MUST be placed 20cm clearance from the wall
- For optimal performance and longevity, the condenser on this unit must be cleaned monthly.

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	32°C / 70% Humidity
CAPACITY	1539 Litres
CURRENT	8 Amps
ENERGY CONSUMPTION	32 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	1600W
INTERNAL DIMENSION MM	1770(w) x 530(d) x 1555(h)
PACKAGE DIMENSION MM	1940(w) x 780(d) x 2160(h)
PRODUCT DIMENSION MM	1890(w) x 730(d) x 2010(h)
PRODUCT WEIGHT	380 Kg
REFRIGERANT	R290/150g x2
SHIPPING WEIGHT	400 Kg