

## Supermarket Single Glass Door Upright Display Freezer - 450 Litre

Upgrade your store with the ultimate solution for displaying and preserving your frozen goods - the Supermarket Single Glass Door Upright Display Freezer. Designed specifically for convenience stores, bars, local marts, supermarkets, and takeaways across Australia, this freezer combines functionality with style.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a 24-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



### Appearance

- Single glass doors
- CAREL iJF LED controller and display
- Internal LED lighting

### Construction

- Powder Coated Body
- Double-glazed glass doors
- 450L capacity
- 5 adjustable wire shelves per door
- Pre-installed castor wheels
- 32°C/70% humidity ambient temperature
- EMBARCO, NEU217BU compressor

### Operation

- The temperature set range is between -18°C and -22°C
- Top and bottom heating stripe
- Electronic temperature control
- Fan-forced ventilated cooling

### Installation and Maintenance

- This unit MUST be placed on a levelled surface.
- This unit MUST not be exposed to direct or indirect sunlight or near any heat-radiated appliances.
- This unit MUST be placed leaving a minimal clearance of 20cm from the wall to the back of the unit for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser on this unit must be cleaned monthly.

**NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.**

**Errors and omissions excepted (E&OE)**

## SPECIFICATION

AMBIENT TEMPERATURE	32°C / 70% Humidity
CAPACITY	450 Litres
CURRENT	3 Amps
ENERGY CONSUMPTION	12 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	700W
INTERNAL DIMENSION MM	510(w) x 530(d) x 1555(h)
PACKAGE DIMENSION MM	680(w) x 780(d) x 2160(h)
PRODUCT DIMENSION MM	630(w) x 730(d) x 2010(h)
PRODUCT WEIGHT	200 Kg
REFRIGERANT	R290/150g
SHIPPING WEIGHT	215 Kg