

1000 Litre Upright Double Stainless Steel Door Freezer

Enhance your kitchen with this freezer's sturdy stainless steel construction, self-closing doors, and practical castor wheels, making it ideal for busy kitchens. With five adjustable shelves per door, you can properly organise your frozen goods while also maximising storage space. Lockable doors also safeguard the safety of your contents, giving you peace of mind after hours. Improve your kitchen operations with this large, secure, and user-friendly freezer today!

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month part and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL, which has more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Stainless steel
- Two doors
- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity

Construction

- Stainless steel body and doors
- 1065L capacity
- 5 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- Cubigel compressor

Operation

- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between -16°C and -22°C
- Fan-forced ventilated cooling
- Lockable doors

Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

NOTE: Product images are for illustration purposes only; actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	1065 Litres
CURRENT	4.8 Amp
ENERGY CONSUMPTION	10.5 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	735W
INTERNAL DIMENSION MM	1220(w) x 582(d) x 1390(h)
PACKAGE DIMENSION MM	1370(w) x 790(d) x 2060(h)
PRODUCT DIMENSION MM	1340(w) x 750(d) x 2010(h)
PRODUCT WEIGHT	135 kg
REFRIGERANT	R290/140g
SHIPPING HEIGHT	155 K-