

1300 Litre Upright Double Stainless Steel Door Fridge

The X-series GNX1400TN double-door fridge comes with many well-appointed features, such as high-grade stainless-steel construction, self-closing doors, and fan-forced cooling. It offers a generous 1300L storage capacity with fully adjustable shelves (five per door, fitting 2xGN1/1 trays, or pans per shelf) and uniquely designed centre shelf connectors to fully utilise the storage space in this heavy-duty commercial fridge. High-quality components and electronics are installed to maintain optimal temperature control. Castor wheels come as standard to assist in the manoeuvrability and positioning of the fridge at your premises. This commercial fridge also comes with lockable doors to ensure your contents remain secure during unsupervised hours.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL, with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Stainless steel
- Two doors
- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity

Construction

- Stainless steel body and doors
- 1300L capacity
- 5 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% Humidity ambient temperature
- Cubigel compressor

Operation

- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling
- Lockable doors

Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- The condenser and filter on this unit must be cleaned monthly.
Click [here](#) to watch the installation video
Click [here](#) to watch the maintenance video

NOTE: Product images are for illustration purposes only; actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	1300 Litres
CURRENT	3.5 Amp
ENERGY CONSUMPTION	7 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	500W
INTERNAL DIMENSION MM	1360(w) x 700(d) x 1400(h)
PACKAGE DIMENSION MM	1505(w) x 855(d) x 2070(h)
PRODUCT DIMENSION MM	1480(w) x 830(d) x 2010(h)
PRODUCT WEIGHT	174 Kg
REFRIGERANT	R290/130g
SHIPPING WEIGHT	220 Kg