

## Commercial Two Door Worktop / Under Bench Freezer 700mm Depth

Upgrade your kitchen game with the finest two-door commercial worktop freezer! Crafted from quality stainless steel, this powerhouse can withstand temperatures up to 43°C. Say hello to steady cooling with its self-closing doors, Carel iJF controls, and fan-forced vented cooling system. With room for up to four Gastronome 1/1 trays in each of its two doors, this freezer is essential for restaurants, cafes, and pubs looking to increase efficiency while lowering operating costs. Get yours today and watch as your kitchen operations reach new heights of productivity!

The new X-series has been redesigned with dual fans located at the front and side of the unit. This new design frees the rear ventilation space, allowing you to position these models flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL, which has more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

### Appearance

- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Stainless steel
- Two stainless steel doors

### Construction

- Stainless steel body and self-closing doors
- 282L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C (65% humidity) ambient temperature
- CUBIGEL compressor

### Operation

- The temperature set range is between -16°C and -22°C
- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- Fan-forced ventilated cooling

### Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation and maintenance video.

**NOTE: Product images are for illustration purposes only; actual products may differ in appearance. Errors and omissions excepted (E&OE)**

## SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	282 Litres
CURRENT	4 Amp
ENERGY CONSUMPTION	6.6 kWh / 24hr
FREQUENCY	50Hz
INPUT POWER	600W
INTERNAL DIMENSION MM	795(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1405(w) x 750(d) x 910(h)
PRODUCT DIMENSION MM	1360(w) x 700(d) x 850(h)
PRODUCT WEIGHT	99 Kg
REFRIGERANT	R290/115g
SHIPPING WEIGHT	120 Kg