

Commercial Two Glass Door Worktop / Under Bench Display Fridge 700mm Depth

This fridge is made of sturdy stainless steel and can manage ambient temperatures of up to 43°C. Ideal for restaurants, cafes, and bars, the self-closing glass doors and modern Carel iJF electronic controls enable accurate temperature regulation even in high-pressure conditions. This unit, with fan-forced ventilated cooling and double-glazed glass doors with GN1/1-sized shelves, can hold up to four complete Gastronomie 1/1 trays or pans. Improve your kitchen's efficiency instantly!

The X-series are designed with dual fans located at the front and side of the unit. This frees the rear ventilation space, allowing you to position these models flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front must be clear from obstructions.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL, which has more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Stainless steel
- Two double-glazed glass doors
- Carel iJF LED controller and display

Construction

- Stainless steel body and glass doors
- 282L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- CUBIGEL compressor

Operation

- The temperature set range is between +2°C and +8°C
- Electronic temperature control
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- The condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation and maintenance video

NOTE: Product images are for illustration purposes only: actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	282 Litres
CURRENT	2.8 Amp
ENERGY CONSUMPTION	5 kWh / 24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	800(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1410(w) x 750(d) x 880(h)
PRODUCT DIMENSION MM	1360(w) x 700(d) x 850(h)
PRODUCT WEIGHT	99 Kg
REFRIGERANT	R290/85g
SHIPPING WEIGHT	120 Kg