

Two Door Commercial Worktop / Under Bench Fridge 700mm Depth

Built with high-quality stainless steel, and insulated construction to withstand ambient temperatures of up to 43°C, this fridge is a compact and practical addition to kitchens in restaurants, cafes, and pubs. The self-closing solid stainless-steel doors, Carel iJF electronic controls and fan-forced ventilated cooling help to maintain consistent temperatures efficiently and reliably in high-pressure environments. Each of the two doors has two GN1/1-sized shelves per door to accommodate up to four full Gastronorm 1/1 trays or pans.

The X-series has been designed with dual fans, located at the front and side of the unit. This design frees the rear ventilation space allowing you to position these models to flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Stainless steel
- Two stainless steel doors

Construction

- Stainless steel body and self-closing doors
- 282L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C / 65% humidity ambient temperature
- CUBIGEL compressor

Operation

- The temperature set range is between +2°C and +8°C
- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation and maintenance video

NOTE:- Product images are for illustration purposes only. actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	282 Litres
CURRENT	2.8 Amp
ENERGY CONSUMPTION	4.8 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	800(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1405(w) x 750(d) x 910(h)
PRODUCT DIMENSION MM	1360(w) x 700(d) x 850(h)
PRODUCT WEIGHT	99 Kg
REFRIGERANT	R290/85g
SHIPPING WEIGHT	120 Kg