

Three Door Commercial Worktop / Under Bench Fridge 700mm Depth

The heavy-duty stainless-steel worktop fridge conserves both bench space and energy and can be used as an under bench or worktop. Fitted with heavy-duty doors, a Carel iJf digital temperature controller and a CUBIGEL compressor, this commercial unit is designed to function in environments of up to 43°C. Designed for restaurants, bars, clubs and other hospitality venues, the adjustable shelving is 1/1GN compatible and features a unique centre-shelf connector so loose items do not fall through.

The X-series are designed with dual fans, located at the front and side of the unit. This design frees the rear ventilation space allowing you to position these models to flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Stainless steel worktop
- Three doors
- Recessed Handles
- Carel iJf Digital Controller with NFC and Bluetooth connectivity

Construction

- Stainless steel body and self-closing doors
- 417L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% Humidity ambient temperature
- CUBIGEL compressor

Operation

- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation and maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance. Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	417 Litres
CURRENT	2.8 Amp
ENERGY CONSUMPTION	5.1 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	1235(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1840(w) x 750(d) x 880(h)
PRODUCT DIMENSION MM	1795(w) x 700(d) x 850(h)
PRODUCT WEIGHT	113 Kg
REFRIGERANT	R290/85g
SHIPPING WEIGHT	140 Kg