

## 429 Litre Upright Single Stainless Steel Door Freezer

Offering 429L of storage capacity, this single-door upright freezer has adjustable wire shelves and comes equipped with castor wheels, so it can be easily moved into place. It's designed for busy commercial kitchens in pubs, bars, and restaurants and features self-closing doors, interior LEDs, a digital temperature controller, and an automated defrosting system. Made from high-quality stainless steel, the smart exterior is matched by trusted parts such as the Cubigel compressor and Carel electronics.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL, with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

### Appearance

- Upright
- Single door
- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Internal LED lighting

### Construction

- Stainless steel body and doors
- 429L capacity
- 5 adjustable wire shelves
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- Cubigel compressor

### Operation

- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between -16°C and -22°C
- Fan-forced ventilated cooling
- Automated defrosting system
- Lockable door

### Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video  
Click [here](#) to watch the maintenance video

NOTE: Product images are for illustration purposes only; actual products may differ in appearance.

Errors and omissions excepted (E&OE)

## SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	429 Litres
CURRENT	4 Amp
ENERGY CONSUMPTION	6.5 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	500w
INTERNAL DIMENSION MM	564(w) x 582(d) x 1414(h)
PACKAGE DIMENSION MM	710(w) x 790(d) x 2060(h)
PRODUCT DIMENSION MM	680(w) x 750(d) x 2010(h)
PRODUCT WEIGHT	98 KG
REFRIGERANT	R290 / 115g
SHIPPING WEIGHT	108 KG