

429 Litre Upright Single Door Stainless Steel Door Fridge

Featuring castor wheels for easy manoeuvrability and a self-closing door so you can let it just swing shut, this upright fridge is designed intelligently for busy kitchens in pubs, restaurants and bars. Single door with a compact depth, the adjustable wire shelving allows the total 429L capacity to be utilised while internal LED lighting provides easy visibility. With a robust stainless-steel body, this fridge is designed to withstand high ambient temperatures and is fitted with fan-forced ventilated cooling and electronic temperature controls.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Upright
- Single door
- Internal LED light

Construction

- Stainless steel body and doors
- 429L capacity
- 5 adjustable wire shelves
- Pre-installed castor wheels
- 43°C and 65% humidity ambient temperature
- Cubigel compressor

Operation

- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling
- Lockable door

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- A minimum of 50cm of ventilation must be provided at the top of the refrigeration unit.
- The condenser and filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance. Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	429 Litres
CURRENT	2.8 Amps
ENERGY CONSUMPTION	4.8 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	564(w) x 582(d) x 1414(h)
PACKAGE DIMENSION MM	710(w) x 790(d) x 2060(h)
PRODUCT DIMENSION MM	680(w) x 750(d) x 2010(h)
PRODUCT WEIGHT	98 KG
REFRIGERANT	R290 / 100g
SHIPPING WEIGHT	108 KG