

600 Litre Upright Stainless Steel Door Fridge

Made from high-quality stainless steel with a self-closing door and fan-forced ventilated cooling, this unit is designed to maintain efficient temperature control. The castor wheels ensure easy manoeuvrability, and the lockable door helps contents remain secure during closing hours. Offering 600L of storage, each of the five adjustable shelves has room for 2x GN1/1 trays or pans.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Stainless steel
- Two doors
- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity

Construction

- Stainless steel body and doors
- 600L capacity
- 5 adjustable wire shelves per door
- Pre-installed castor wheels
- 43°C / 65% humidity ambient temperature
- Cubigel compressor

Operation

- The temperature set range is between +2°C and +8°C
- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- Fan-forced ventilated cooling
- Lockable door

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- The condenser and filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	600 Litres
CURRENT	2.8 Amps
ENERGY CONSUMPTION	5.5 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	564(w) x 682(d) x 1414(h)
PACKAGE DIMENSION MM	710(w) x 890(d) x 2060(h)
PRODUCT DIMENSION MM	680(w) x 850(d) x 2010(h)
PRODUCT WEIGHT	125 KG
REFRIGERANT	R290/100g
SHIPPING WEIGHT	135 KG