

## 650 Litre Upright Stainless Steel Door Freezer

This single-door freezer is a high-quality addition to commercial kitchens, featuring adjustable shelves and internal LED light. Designed for businesses like cafes, restaurants, bars, and pubs.

With 5 shelves, each capable of holding 2x 1/1GN trays/pans. The heavy-duty door is self-closing to aid efficiency and help the unit withstand up to 43°C ambient temperatures while keeping contents fresh. Made from stainless steel, this commercial freezer features fan-forced ventilated cooling and an automated defrosting system that keeps it frost-free.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL, with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Click [here](#) to watch Carel App installation and temperature function video

### Appearance

- 650L single-door upright
- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- LED internal light

### Construction

- Stainless steel body and door
- 650L capacity
- 5 adjustable wire shelves per door
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- CUBIGEL compressor

### Operation

- The temperature set range is between -16°C and -22°C
- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- Lockable door
- Fan-forced ventilated cooling
- Automated defrosting system

### Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

**NOTE:- Product images are for illustration purposes only, actual products may differ in appearance. Errors and omissions excepted (E&OE)**

## SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	650 Litres
CURRENT	4.2Amp
ENERGY CONSUMPTION	8.2 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	680W
INTERNAL DIMENSION MM	620(w) x 700(d) x 1400(h)
PACKAGE DIMENSION MM	765(w) x 855(d) x 2070(h)
PRODUCT DIMENSION MM	740(w) x 830(d) x 2010(h)
PRODUCT WEIGHT	112 KG
REFRIGERANT	R290/120g
SHIPPING WEIGHT	140 KG
TEMPERATURE RANGE	Sets between -16°C and -22°C