

## 400L Upright Single Door Ventilated Light-Duty Fridge

The upright fridge is specifically engineered for light-duty storage-centric solutions at bustling cafés, kiosks, food vans, and sandwich bars. Featuring a single door and a space-efficient design, it provides a storage capacity of 293 litres. Its durable construction ensures reliability and space-saving size. The fridge is equipped with fan-forced ventilated cooling and electronic temperature controls, ensuring optimal performance and consistent refrigeration.

R600a Refrigerant is non-toxic, natural and free of ozone-depleting properties. R600a is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

### Appearance

- Upright
- Single door
- White interior and exterior
- Carel Digital Controller

### Construction

- 40mm insulation
- 4 adjustable wire shelves, 80mm depth, 30 Kg capacity per shelf
- Self-Closing Door
- 2x Rear Wheels
- 38°C / 60% Humidity ambient temperature
- Wanbao compressor

### Operation

- Electronic temperature control
- The temperature set range is between +2°C and +8°C
- Light Duty for storage purposes ONLY
- Fan-forced ventilated cooling
- 42dB Noise Level
- Lockable door

### Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- A minimum of 20cm of ventilation must be provided from the back of the fridge to the wall.
- The condenser and compressor grills at the back of the unit must be cleaned and maintained with a soft brush and blower monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

**NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.**

**Errors and omissions excepted (E&OE)**

## SPECIFICATION

|                       |                           |
|-----------------------|---------------------------|
| AMBIENT TEMPERATURE   | 38°C / 60% Humidity       |
| CAPACITY              | 293 Litres                |
| CURRENT               | 1 Amps                    |
| ENERGY CONSUMPTION    | 1.42 kWh/24hr             |
| FREQUENCY             | 50Hz                      |
| INPUT POWER           | 66W                       |
| INTERNAL DIMENSION MM | 445(w) x 440(d) x 1673(h) |
| PACKAGE DIMENSION MM  | 660(w) x 665(d) x 1905(h) |
| PRODUCT DIMENSION MM  | 595(w) x 662(d) x 1882(h) |
| PRODUCT WEIGHT        | 62 Kg                     |
| REFRIGERANT           | R600a / 45g               |
| SHIPPING WEIGHT       | 77 kg                     |
| TEMPERATURE RANGE     | Sets between +2°C to +8°C |
| VOLTAGE               | 220V - 240V               |
| WARRANTY              | 2 Years Parts & Labour    |