

600L Upright Single Door Ventilated Light-Duty Fridge

The upright fridge is specifically engineered for light-duty storage-centric solutions at bustling cafés, kiosks, food vans, and sandwich bars. It has a single door and a space-efficient design, and it has a storage capacity of 510 litres. Its durable construction ensures reliability and space-saving size. The fridge has fan-forced ventilated cooling and electronic temperature controls, ensuring optimal performance and consistent refrigeration.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Appearance

- Upright
- Single door
- White interior and exterior
- Carel Digital Controller

Construction

- 40mm insulation
- 4 adjustable wire shelves, 80mm depth, 30 Kg capacity per shelf
- Self-Closing Door
- 2x Rear Wheels
- 38°C / 60% Humidity ambient temperature
- Huayi compressor

Operation

- Electronic temperature control
- The temperature set range is between +2°C and +8°C
- Light Duty for storage purposes ONLY
- Fan-forced ventilated cooling
- 45dB Noise Level
- Lockable door

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- A minimum of 20cm of ventilation must be provided from the back of the fridge to the wall.
- The condenser and compressor grills at the back of the unit must be cleaned and maintained with a soft brush and blower monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	38°C / 60% Humidity
CAPACITY	510 Litres
CURRENT	1 Amps
ENERGY CONSUMPTION	1.88 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	133W
INTERNAL DIMENSION MM	625(w) x 540(d) x 1673(h)
PACKAGE DIMENSION MM	840(w) x 765(d) x 1905(h)
PRODUCT DIMENSION MM	775(w) x 762(d) x 1882(h)
PRODUCT WEIGHT	88 Kg
REFRIGERANT	R290 / 60g
SHIPPING WEIGHT	106.82 kg
TEMPERATURE RANGE	Sets between +2°C to +8°C
VOLTAGE	220V - 240V
WARRANTY	2 Years Parts & Labour