

## 2 Door Saladette Fridge – Fits 7 x 1/3 GN Trays

This stainless-steel saladette fridge and worktop are designed for cafes, sandwich shops and other commercial kitchens where easy access to various prep items is important. The trays above the bench space accommodate seven 1/3 GN trays and feature a full-length closable lid. Along with a 30cm deep preparation bench and castor wheels for easy manoeuvrability.

Inside, the adjustable two-wire shelves for each door are complemented by unique centre-shelf connectors and have room for four 1/1GN trays or pans. Equipped with a CUBIGEL compressor and an automated defrosting system, the unit is complemented by a Carel digital controller with an LED temperature display.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

The X-series are designed with dual fans, located at the front and side of the unit. This frees the rear ventilation space allowing you to position these models to flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

### Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Click [here](#) to watch Carel App installation and temperature function video

### Appearance

- Stainless steel body, worktop and doors
- Two doors
- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity

### Construction

- Stainless steel body and doors
- 282L capacity
- 2 adjustable wire shelves per door
- Benchtop suitable for seven 1/3 GN trays
- Shelving suitable for 1/1 GN trays
- Removable PVC cutting board
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- CUBIGEL compressor

### Operation

- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling

### Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

**NOTE:- Product images are for illustration purposes only, actual products may differ in appearance. Errors and omissions excepted (E&OE)**

## SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	282 Litres
CURRENT	2.6 Amp
ENERGY CONSUMPTION	5 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	380W
INTERNAL DIMENSION MM	795(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1390(w) x 730(d) x 1125(h)
PRODUCT DIMENSION MM	1360(w) x 700(d) x 1085(h)
PRODUCT WEIGHT	120 Kg
REFRIGERANT	R290/85g
SHIPPING WEIGHT	140 Kg