

3 Door Saladette Fridge - Fits 8 x 1/3 GN Trays

Equipped with castor wheels for easy manoeuvrability and constructed from heavy-duty stainless steel, the saladette worktop fridge is designed for busy commercial environments such as cafes, restaurants, pubs, and sandwich shops. With a 30cm deep preparation bench, self-closing doors on the fridge storage space and shelving rails suitable for 1/1 GN and 1/3 GN trays, this unit is designed to keep food products fresh and accessible during the meal-time rush. This unit is built with a Cubigel compressor and an automated defrosting system, complemented by Carel iJF digital controller with LED temperature displays.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

The X-series are designed with dual fans, located at the front and side of the unit. This frees up the rear ventilation space, allowing you to position these models flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

When you buy from AG Equipment, you know you are getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL, with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through Bluetooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Stainless steel body, worktop and doors
- Three doors
- Removable PVC cutting board

Construction

- Stainless steel body and doors
- Benchtop suitable for 8 x 1/3 GN trays
- Shelving suitable for 6 x 1/1 GN trays
- 417L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- CUBIGEL compressor

Operation

- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation video

Click [here](#) to watch the maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance.

Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	417 Litres
CURRENT	2.8 Amp
ENERGY CONSUMPTION	5.5 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	1230(w) x 580(d) x 560(h)
PACKAGE DIMENSION MM	1825(w) x 730(d) x 1125(h)
PRODUCT DIMENSION MM	1795(w) x 700(d) x 1085(h)
PRODUCT WEIGHT	140 Kg