

3 Door Saladette Fridge - 10 x 1/3 GN Trays

AG Equipment's latest Saladette refrigerator is just what you need for your cafe, sandwich shop, restaurant, or commercial kitchen. Made from stainless steel, it has three self-closing doors to keep your produce fresh, ten 1/3 GN trays and an extra wide 40cm stainless steel preparation bench area. The unit also includes two closable lids to improve efficiency when you are not serving. The Saladette fridge comes complete with castor wheels for easy manoeuvrability.

R290 Refrigerant is non-toxic, natural, and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

The X-series are designed with dual fans, located at the front and side of the unit. This frees the rear ventilation space allowing you to position these models to flush against the back wall. All you are required for ventilation is to provide 150mm at the side and the front clear from obstructions.

When you buy from AG Equipment, you know you are getting a twenty-four-month part and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL with more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Recessed Handle
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Stainless steel body
- Three Stainless Steel doors
- 10 x 1/3 GN Trays with lids included.
- 40cm deep stainless steel workbench
- Removable PVC cutting board

Construction

- 580L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- CUBIGEL compressor

Operation

- CONTROLLA mobile app available on Android and Apple App Stores
- Electronic and Remote temperature control
- The temperature set range is between +2°C and +8°C
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed leaving clearance for ventilation. Please refer to the user manual for details
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly

Click [here](#) to watch the installation video
Click [here](#) to watch the maintenance video

NOTE:- Product images are for illustration purposes only, actual products may differ in appearance. Errors and omissions excepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	580 Litres
CURRENT	2.8 Amp
ENERGY CONSUMPTION	5.8 kWh/24hr
EFFICIENCY	5.0Hz
INPUT POWER	400W
INTERNAL DIMENSION MM	1455(w) x 680(d) x 560(h)
PACKAGE DIMENSION MM	2050(w) x 830(d) x 1125(h)
PRODUCT DIMENSION MM	2020(w) x 800(d) x 1085(h)
PRODUCT WEIGHT	180 Kg
REFRIGERANT	R290/85g