

Commercial Two Door Worktop / Under Bench Fridge 600mm Depth

Built from high-quality stainless steel with insulated construction to withstand ambient temperatures of up to 43°C, this fridge unit is a compact and practical addition to kitchens in restaurants, cafes, and pubs. The self-closing solid stainless steel doors, Carel iJF electronic controls, and fan-forced ventilated cooling help to maintain consistent temperatures efficiently and reliably in high-pressure environments.

R290 Refrigerant is non-toxic, natural and free of ozone-depleting properties. R290 is one of the most climate-friendly and cost-effective refrigerants available. Fridges and Freezers using this refrigerant are more efficient and can reduce your overall energy costs by up to 28%.

When you buy from AG Equipment, you know you're getting a twenty-four-month parts and labour warranty from a trusted Australian supplier.

Carel iJF Controller

The new iJF controller is by CAREL, which has more than thirty years of experience in the refrigeration controller market. Customisation options, aesthetics and functionalities have been considered when commissioning the controller. Its frameless flat design and distinctive appearance blend perfectly into any fridge or freezer appliance.

- Provides Logs
- Fault alarm warnings
- Mobile connectivity with Controlla Application through BlueTooth



Click [here](#) to watch Carel App installation and temperature function video

Appearance

- Recessed Handles
- Carel iJF Digital Controller with NFC and Bluetooth connectivity
- Stainless steel
- Two stainless steel doors

Construction

- Stainless steel body and self-closing doors
- 228L capacity
- 2 adjustable wire shelves per door
- Centre shelf connectors
- Pre-installed castor wheels
- 43°C/65% humidity ambient temperature
- Cubigel compressor

Operation

- The temperature set range is +2°C and +8°C
- CONTROLLA mobile app is available on Android and Apple App Stores
- Electronic and Remote temperature control
- Fan-forced ventilated cooling

Installation and Maintenance

- This unit must be placed, leaving clearance for ventilation. Please refer to the user manual for details.
- For optimal performance and longevity, the condenser filter on this unit must be cleaned monthly.

Click [here](#) to watch the installation and maintenance video.

NOTE: Product images are for illustration purposes only; actual products may differ in appearance.

Errors and omissions accepted (E&OE)

SPECIFICATION

AMBIENT TEMPERATURE	43°C / 65% Humidity
CAPACITY	228 Litres
CURRENT	2.6 Amp
ENERGY CONSUMPTION	4.8 kWh/24hr
FREQUENCY	50Hz
INPUT POWER	380W
INTERNAL DIMENSION MM	795(w) x 480(d) x 560(h)
PACKAGE DIMENSION MM	1410(w) x 650(d) x 880(h)
PRODUCT DIMENSION MM	1360(w) x 600(d) x 850(h)
PRODUCT WEIGHT	81 Kg
REFRIGERANT	R290/65g
SHIPPING WEIGHT	102 Kg
TEMPERATURE RANGE	2°C to 8 °C