



## PRODUCT ADVANTAGES

- **XL wash chamber:** the large hood and chamber provide best wash results, e.g. for
  - up to 24 plates/rack
  - up to 8 sheets 600 x 400 mm
  - up to 8 trays 660 x 500 mm
  - up to 2 1/1 GN-boxes
- **VISIOTRONIC control:** single button control with remaining time indicator together with text and graphic display
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **Exhaust energy storage:** the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 3 kW, less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **GENIUS-X<sup>2</sup> fine filter system:** advanced filter system with pre-wash function reduces detergent consumption up to 35%
- **ROTOR-X wash system:** separate rotating upper & lower 4-spoke wash arms deliver dynamic wash power
- **VAPOSTOP (optional):** prevents vapour escaping from the machine when the hood is opened
- **Certified to remove the need for an exhaust canopy**
- **Intelligent energy management:** the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- **Interlocked strainer:** prevents operation without tank strainer
- **EASY-CLEAN concept:** blue markings in the machine help the operator to identify the components which require cleaning

## TECHNICAL DATA

|                      |  |
|----------------------|--|
| Cycle times*         | 1. 52sec<br>2. 75sec<br>3. 180sec<br>4. Continuous (20min) |
| Water consumption    | 2 l/rack   |
| Tank capacity        | 40 litres  |
| Tank heating         | 2.5 kW   |
| Power supply         | 415 / 50 / 3N  |
| Booster loading      |  |
| Standard             | 12.4 kW  |
| Alternative          | 6.2 kW   |
| Total loading        |  |
| Standard             | 16.3   3 x 32 A  |
| Alternative          | 10.1   3 x 25 A  |
| Wash pump            | 1.1 kW   |
| Rack size            | 500 x 500  <br>600 x 500 mm                                |
| Loading height       | 540 mm   |
| Noise level          | 67 dB (A)  |
| Weight (gross / net) | 155 / 135 kg   |

# INDUSTRY KITCHENS

[www.industrykitchens.com.au](http://www.industrykitchens.com.au) 1800 611 058

\* Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly.

For corner operation we recommend to make the right side of the machine accessible for service.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

## CONNECTIONS

|                               |                             |
|-------------------------------|-----------------------------|
| ① Drain hose                  | 2,000 mm  <br>ID 20 / OD 25 |
| ② Supply hose                 | 2,000 mm   R 3/4"           |
| Required flow rate            | 5 l/min                     |
| Flow pressure                 | 0.5 bar - 6 bar             |
| Max. supply water temperature | 60 °C                       |
| ③ Power cord                  | 2,500 mm                    |
| Supply hose for               |                             |
| ④ Detergent                   | 2,000 mm                    |
| ⑤ Rinse aid                   | 2,000 mm                    |

## DIMENSIONAL DRAWING

