


**PRODUCT ADVANTAGES**

- **PERMANENT-CLEAN automatic soil removal:** innovative filter system eliminates manual pre-cleaning. Soil is immediately removed into an external strainer, which saves operating costs and protects the machine
- **Double capacity:** the double wide wash chamber can cover 2 racks or bigger containers
- **VISIOTRONIC control:** single button control with remaining time indicator together with text and graphic display
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **Eco programme:** switchable steam rinse cycle reduces fresh-water consumption to 1.4 l/cycle. Saving of up to 44 % water and chemicals
- **VAPO-ACTIVE steam washing:** significantly less manual pre-cleaning and second runs by intensive wash cycles with steam
- **POWER-PLUS wash programme:** selectable high-pressure programme to wash heavily soiled wash items
- **Exhaust energy storage:** the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 6 kW; less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **ROTOR-X wash system:** separate rotating upper & lower 4-spoke wash arms deliver dynamic wash power
- **VAPOSTOP (optional):** prevents vapour escaping from the machine when the hood is opened
- **Certified to remove the need for an exhaust canopy**
- **Intelligent energy management:** the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- **Interlocked strainer:** prevents operation without tank strainer
- **EASY-CLEAN concept:** blue markings in the machine help the operator to identify the components which require cleaning

**TECHNICAL DATA**

Cycle times*	1. 52sec 2. 70sec 3. 170sec 4. 180sec.
Water consumption	1.4 l/rack
Tank capacity	80 l
Tank heating	6 kW
Power supply	415 / 50 / 3N
Booster loading	
Standard	12.4 kW
Alternative	6.2 kW
Total loading	
Standard	23.5   3 x 40 A
Alternative	18.7   3 x 32 A
Wash pump	4 x 1.1 kW
Rack size	500 x 500 mm
Loading height	440 mm
Noise level	71 dB (A)
Weight (gross / net)	241 / 209 kg

# INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058

**CONNECTIONS**

① Drain hose	2,000 mm   ID 20 / OD 25
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 bar - 6 bar
Max. supply water temperature	60 °C
③ Power cord	2,500 mm
Supply hose for	
④ Detergent	2,000 mm
⑤ Rinse aid	2,000 mm
⑥ Drain hose PERMANENT-CLEAN	2,000 mm   ID 20 / OD 25

\* Thermostop guarantees required temperatures with cold water connection, the actual cycle times extend accordingly.

**DIMENSIONAL DRAWING**
