

## Hood Type Dishwasher with ESD

## AH800EES

### Product Information:

- High performance hood-type dishwasher with pre-fitted, easy to install energy savings device (ESD)
- **E-Management:** intuitive and advanced electronic interface
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- **ES System:** energy savings device (ESD)
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Stainless steel wash and rinse arms
- Robust upper tank scrap filters in stainless steel
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Vertical self-draining wash pump
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **18-months parts and labour warranty**

### Included Accessories:

- 1 x flat cup basket 500x500mm
- 2 x peg plate basket 500x500mm
- 1 x cutlery insert
- 1 x water inlet hose, length 1.5m
- 1 x drain hose, length 2.0m
- Fitted with 150mm adjustable legs

### Optional Accessories:

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets



### Specifications:

**Model** AH800EES  
**W x D x H (mm)** 657 x 793 x 2294

Note: Dimensions do not include handle

**Weight** 163kg  
**Packed Dimensions (mm)** 770 x 930 x 1870  
**Packed Weight** 182kg

**Total Connected Load** 9.55kW  
**- Convertible to:** 6.75kW (low power option)

Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.

**Electrical Connection** 3Ø+N+E 415VAC / 50Hz  
 (Lead fitted, onsite connection)

**Water Quantity Per Cycle** 2.5 Litres  
**Water Connection** 1.5m Hose / 3/4" BSP  
**Water Inlet Pressure** 100 - 500KPA  
**Cold water supply** 10°C - 25°C  
**Waste Connection** 2m Hose / ø20.5mm

### Legend:

- A Electrical Connection
- B Water Connection
- C Drain Connection
- D Detergent Connection
- E Rinse-Aid Connection

