


30 TRAY / 4.8 M² TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



199 Hour
Timer



Ambient - 90°C
Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

30CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	3 kW (1 kW x 3 Zones)	Number of Racks	3
Avg Power Usage	1.5 kW (500 W x 3 Zones)	Number of Hooks	90
Voltage / Frequency	220-240V/50-60HZ	Total Tray Area	4.8 m ²
Max Amperage	12A	Total Trays	30
Safety Breaker Required	Single Phase/15A	Tray Dimensions	40 x 40 cm
Temperature Range	15°C - 90°C (1°C Increments), plus Ambient Air Mode	Space Between Trays	35 mm
Timer	0 - 199hr	Tray Mesh Spacing	14 x 14 mm
Independent Zones	3	Product Dimensions (W x H x D)	470 x 1370 x 580 mm
Average Noise Level	45 dB	Chamber Dimensions (W x H x D)	415 x 380 x 400 mm / Zone
Machine Weight	52.5kg	Chamber Volume	63L / Zone (189L) 0.063 m ³ / Zone
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		
Certifications	ANSI/NSF4, UL/cUL, RCM, AS/NZS 4417, CE, UKCA		