


32 TRAY HORIZONTAL / 5.12 M² TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



199 Hour
Timer



Ambient - 90°C
Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

32HCUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	3.75 kW (1.875 kW x 2 Zones)	Number of Racks	4
Avg Power Usage	1.875 kW (937.5 W x 2 Zones)	Number of Hooks	120
Voltage / Frequency	220-240V/50-60HZ	Total Tray Area	5.12 m ²
Max Amperage	15A	Total Trays	32
Safety Breaker Required	Single Phase/20A	Tray Dimensions	40 x 40 cm
Temperature Range	15°C - 90°C (1°C Increments), plus Ambient Air Mode	Space Between Trays	35 mm
Timer	0 - 199hr	Tray Mesh Spacing	14 x 14 mm
Independent Zones	2	Product Dimensions (W x H x D)	930 x 790 x 550 mm
Average Noise Level	45 dB	Chamber Dimensions (W x H x D)	415 x 580 x 400 mm / Zone
Machine Weight	59kg	Chamber Volume	96L / Zone (192L) 0.096 m ³ / Zone
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		
Certifications	ANSI/NSF4, UL/cUL, RCM, AS/NZS 4417, CE, UKCA		