


60 TRAY / 9.6 M² TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



199 Hour
Timer



Ambient - 90°C
Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

60CUDG SPECIFICATIONS

Max Power Usage	5.75 kW (1.9 kW x 3 Zones)	Total Tray Area	9.6 m ²
Avg Power Usage	2.875 kW (958.3 W x 3 Zones)	Total Trays	60
Voltage / Frequency	220-240V/50-60HZ	Tray Dimensions	40 x 40 cm
Max Amperage	23A	Space Between Trays	35 mm
Safety Breaker Required	Single Phase/25A	Tray Mesh Spacing	14 x 14 mm
Temperature Range	15°C - 90°C (1°C Increments), plus Ambient Air Mode	Chamber Volume	121L / Zone (363L) 0.121 m ³ / Zone
Timer	0 - 199hr	Chamber Dimensions (W x H x D)	415 x 730 x 400 mm / Zone
Independent Zones	3	Product Dimensions (W x H x D)	1410 x 930 x 555 mm
Average Noise Levels	55 dB	Machine Weight	88 kg
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		
Certifications	ANSI/NSF4, UL/cUL, RCM, AS/NZS 4417, CE, UKCA		