

# DOUBLE TROLLEY HIGH-CAPACITY INDUSTRIAL DEHYDRATOR

INDUSTRIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL




Save Set Recipes



CSV Data Export



Completion Cooling Cycle



Uniform Drying Without Rotation



Programmable Staged Drying



DrySync™ Technology



Remote Operational Control



Food-Grade 304 Stainless Steel

## MODEL IU02 SPECIFICATIONS

Max Power Rating	16.15 kW	Internal Airflow	6800 m <sup>3</sup> /hr
Avg. Power Rating	6-7 kW	Number of Exhaust Fans	1
Voltage / Frequency	3-Phase / 50-60Hz - 400V, Custom	Total Trolleys	2 Trolley
Product Dimension (W x H x D)	2200 x 2000 x 1200 mm	Trolley Dimensions	920 x 1450 x 695 mm
Loading Footprint Required	2200 x 2000 x 2600 mm	Space Between Trays	40 - 80 mm
Machine Weight	750 kg	Total Trays	60 - 120 trays
Temperature Range	Ambient - 120°C	Tray Dimensions	460 x 640 mm
Exhaust Air Volume	850 m <sup>3</sup> /hr (per Exhaust Fan)	Total Tray Area	17.7 - 35.3 m <sup>2</sup>
Static Pressure Rating	1020 pa (per Exhaust Fan)	Timer	0 - 5000 hours
Product Material	Double walled industrial-grade 304 stainless steel. Insulated with high density aluminium silicate cotton.		