

10 TROLLEY HIGH-CAPACITY INDUSTRIAL DEHYDRATOR


INDUSTRIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



- 

Save Set Recipes
- 

CSV Data Export
- 

Completion Cooling Cycle
- 

Uniform Drying Without Rotation
- 

Programmable Staged Drying
- 

DrySync™ Technology
- 

Remote Operational Control
- 

Food-Grade 304 Stainless Steel

MODEL IU10 SPECIFICATIONS			
Max Power Rating	71.8 kW	Internal Airflow	27200 m³/hr
Avg. Power Rating	28-30 kW	Number of Exhaust Fans	5
Voltage / Frequency	3-Phase / 50-60Hz - 400V, Custom	Total Trolleys	10 Trolley
Product Dimension (W x H x D)	2500 x 2200 x 5200 mm	Trolley Dimensions	920 x 1450 x 695 mm
Loading Footprint Required	2500 x 2200 x 6600 mm	Space Between Trays	40 - 80 mm
Machine Weight	3100 kg	Total Trays	300 - 600 trays
Temperature Range	Ambient - 120°C	Tray Dimensions	460 x 640 mm
Exhaust Air Volume	850 m³/hr (per Exhaust Fan)	Total Tray Area	88.3 - 176.6 m²
Static Pressure Rating	1020 pa (per Exhaust Fan)	Timer	0 - 5000 hours
Product Material	Double walled industrial-grade 304 stainless steel. Insulated with high density aluminium silicate cotton.		