



Bezzera 3 Group Moda DE PID Espresso Machine - BZMODAPID3B

Quick Overview

- Combining the practicality of a compact machine with the production capacity of a 2-group espresso coffee machine, it comes standard with 2 manual steam outputs.
- The thermal stability and productivity are guaranteed by a heating system that keeps a
- constant coffee temperature in case of maximum use. Special grids placed under the groups allow the use of cups of height up to 13cm, as well as the traditional espresso cups.
- Independent brewing unit temperature control via PID thermostat
- Brewing timer for precise extraction
- Auto On/Off system for energy efficiency
- Programmable pre-infusion for enhanced flavour extraction
- Coffee counter to track usage
- Automatic group washing program for easy maintenance
- Copper-insulated boiler for reduced power consumption and increased productivity
- Safety system featuring a boiler high-temperature cutoff thermostat and hydraulic overpressure
- Premium build with stainless steel AISI 304 (14301) body and copper hydraulic system

Description

Bezzera 3 Group Moda DE PID Espresso Machine - BZMODAPID3B

Key Features

- Combining the practicality of a compact machine with the production capacity of a 2-group espresso coffee machine, it comes standard with 2 manual steam outputs.
- The thermal stability and productivity are guaranteed by a heating system that keeps a
- constant coffee temperature in case of maximum use. Special grids placed under the groups allow the use of cups of height up to 13cm, as well as the traditional espresso cups.
- Independent brewing unit temperature control via PID thermostat
- Brewing timer for precise extraction
- Auto On/Off system for energy efficiency
- Programmable pre-infusion for enhanced flavour extraction
- Coffee counter to track usage
- Automatic group washing program for easy maintenance
- Copper-insulated boiler for reduced power consumption and increased productivity
- Safety system featuring a boiler high-temperature cutoff thermostat and hydraulic overpressure
- Premium build with stainless steel AISI 304 (14301) body and copper hydraulic system

1-year parts only

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	87
Width (mm)	877
Depth (mm)	550
Height (mm)	520
Packing Width (mm)	887
Packing Depth (mm)	505
Packing Height (mm)	535
Power	240V, 5500W/25A
Warranty	1 year parts only