



Bonvue Dual-Access Refrigerated Deli, Meat and Seafood Display Case - AMS-21DD

Quick Overview

- Gross Volume: 1443L
- Max Ambient Temperature: 30°C, 55%RH
- Temperature Range: -1 to +5 ° C
- Efficient Freshness: Double gravity coil for even cooling, perfect for deli, meat and seafood products
- Durable Slanted Front Glass: Double-layer tempered for clear, safe display
- Adjustable Shelves: Easily modify for different heights
- LED Lighting: Showcases items with individually wired shelf lights
- Insulated Sliding Rear Doors: Easy staff access while retaining cold air
- Extra Refrigerated Storage: Spacious rear area for stock
- Optimised Cooling: Over-sized components and slow fans maintain freshness
- Auto Defrost: Timer system prevents ice build-up
- No Plumbing Needed: Self-contained for hassle-free installation
- Stainless Steel Interior: Floor and grille designed for durability and airflow

Description

Bonvue Dual-Access Refrigerated Deli, Meat and Seafood Display Case - AMS-21DD

The dual-access design allows staff to restock from the rear without interrupting customers at the front, making it ideal for high-traffic retail settings like butcher shops, seafood counters, and deli displays. It streamlines service flow and keeps the presentation neat and professional throughout busy trading hours.

Key Features

- Gross Volume: 1443L
- Max Ambient Temperature: 30 °C, 55%RH
- Temperature Range: -1 to +5 °C
- Efficient Freshness: Double gravity coil for even cooling, perfect for deli, meat and seafood products
- Durable Slanted Front Glass: Double-layer tempered for clear, safe display
- Adjustable Shelves: Easily modify for different heights
- LED Lighting: Showcases items with individually wired shelf lights
- Insulated Sliding Rear Doors: Easy staff access while retaining cold air
- Extra Refrigerated Storage: Spacious rear area for stock
- Optimised Cooling: Over-sized components and slow fans maintain freshness
- Auto Defrost: Timer system prevents ice build-up
- No Plumbing Needed: Self-contained for hassle-free installation
- Stainless Steel Interior: Floor and grille designed for durability and airflow

1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice.

Your Shipping Specifications

| | |
|-------------------------|---|
| Product Condition | New |
| Doors | 2 |
| Door Type | Sliding Doors |
| Body | Stainless Steel |
| Gross Volume | 1443L |
| Max Ambient Temperature | 30 , 55%RH |
| Temperature Range | -1 to +5 ° C |
| Form Factor | Display |
| Net Weight (Kg) | 230 |
| Width (mm) | 2123 |
| Depth (mm) | 855 |
| Height (mm) | 1406 |
| Packing Width (mm) | 2185 |
| Packing Depth (mm) | 915 |
| Packing Height (mm) | 1560 |
| Power | 240V, 950W/10A |
| Warranty | 1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice. |