



Bonvue Backfill Heated Display Cabinet HWB2-138

Quick Overview

- Dual-Tier Shelves: Organizes and displays products effectively
- Stainless Steel Food Slide Guide: Regulates the descent of food from the back
- Stainless Steel Accents: Offers a sleek and clean appearance
- Glass Visibility: Full transparency for viewing from any angle
- Mechanical Temperature Control: For hands-on, reliable adjustments
- Visible Temperature Display: Allows for easy monitoring of heat levels
- Contemporary Black Design: Fits seamlessly into modern settings
- Robust Leg Supports: Provides stability and proper elevation
- Temperature range(°C) 30-90
- General Rayed Input Power(W) 1880
- Rated Current(A) 8.2
- Rated Voltage(V) 220-240~
- Rated Frequency(Hz) 50
- Display Area(m²) 1.38
- Net Weight(kg) 63.5
- Grade of Waterproof IPX4

Description

Bonvue Backfill Heated Display Cabinet HWB2-138

This unit is crafted for commercial environments, enabling effortless control with a mechanical controller and clear temperature display. The specialized stainless steel guide is designed to ensure a smooth transition of food from the back to the front for service

Key Features

- Dual-Tier Shelves: Organizes and displays products effectively
- Stainless Steel Food Slide Guide: Regulates the descent of food from the back
- Stainless Steel Accents: Offers a sleek and clean appearance
- Glass Visibility: Full transparency for viewing from any angle
- Mechanical Temperature Control: For hands-on, reliable adjustments
- Visible Temperature Display: Allows for easy monitoring of heat levels
- Contemporary Black Design: Fits seamlessly into modern settings
- Robust Leg Supports: Provides stability and proper elevation
- Temperature range() 30-90
- General Rated Input Power(W) 1880
- Rated Current(A) 8.2
- Rated Voltage(V) 220-240~
- Rated Frequency(Hz) 50
- Display Area(m²) 1.38
- Net Weight(kg) 63.5
- Grade of Waterproof IPX4

One Year Parts and Labour Warranty

Your Shipping Specifications

Net Weight (Kg)	63.5
Width (mm)	1259
Depth (mm)	703
Height (mm)	704
Packing Width (mm)	767
Packing Depth (mm)	1325
Packing Height (mm)	736
Power	240V, 1880/8.2A
Warranty	One Year Parts and Labour Warranty