

Camshelving Premium Vented Starter Kit - 4 Tier

Stationary commercial shelving | Configurable product family



CORE SPECIFICATIONS	
SERIES	Camshelving Premium
CONFIGURATION	Stationary starter unit
SHELVING	4 removable vented shelves
CONSTRUCTION	Steel-core posts and traverses with smooth polypropylene exterior
SHELF PLATES	Reinforced polypropylene with moulded-in Camguard antimicrobial
UNIT CAPACITY	Up to 910 kg, evenly distributed; configuration dependent
TEMPERATURE	-38 C to 88 C series operating range
SHELF ADJUSTMENT	Approximately 100 mm increments
COLOUR	Speckled Grey (480)

4 VENTED SHELVES	910 kg MAX. UNIT LOAD	-38 to 88 C TEMPERATURE	CAMGUARD ANTIMICROBIAL
---------------------	--------------------------	----------------------------	---------------------------

PRODUCT OVERVIEW

The CAMBRO Camshelving Premium Vented Starter Kit is a modular four-tier storage system for high-volume foodservice environments. Its steel-core structure is encapsulated in smooth polypropylene for strength, cleanability and resistance to rust and corrosion. Removable vented shelf plates promote air circulation and can be washed in a commercial dishwasher.

KEY BENEFITS

- Suitable for walk-in coolers, freezers, dry stores and wet storage areas.
- Weldless design helps prevent liquids and dirt entering inaccessible crevices.
- Removable shelf plates and traverses support thorough routine cleaning.
- Shared-post and optional corner-connector design supports efficient storage layouts.

Configuration and technical details

Select the final model code according to the required depth, length and height.

AVAILABLE NOMINAL SIZES

DEPTH	LENGTH	HEIGHT
460 mm 535 mm 610 mm	610 / 760 / 910 / 1070 mm 1220 / 1380 / 1530 / 1830 mm	1630 mm 1830 mm 2140 mm

MODEL-CODE GUIDE

Example: CPU244872V4480 = Premium starter, 610 D x 1220 L x 1830 H mm, 4 vented shelves, Speckled Grey.

CPU	24	48	72	V4	480
SERIES	DEPTH	LENGTH	HEIGHT	SHELVES	COLOUR

COMMON AUSTRALIAN CONFIGURATIONS

MODEL	DIMENSIONS (D x L x H)	SHELVES	COLOUR
CPU183672V4480	460 x 910 x 1830 mm	4 vented	Speckled Grey
CPU184272V4480	460 x 1070 x 1830 mm	4 vented	Speckled Grey
CPU244872V4480	610 x 1220 x 1830 mm	4 vented	Speckled Grey

INCLUDED COMPONENTS

- Two post kits with adjustable feet and post connectors.
- Eight traverses and removable vented plates for four shelf levels.
- Matching dovetails and assembly components.

CLEANING AND INSTALLATION

- Remove shelf plates for washing in a commercial dishwasher.
- Wipe or steam-clean posts and traverses as required.
- Freestanding weldless assembly; use a rubber mallet for setup and adjustment.

IMPORTANT SELECTION NOTE

This is a product-family specification sheet. Exact dimensions, packed weight and load distribution vary by model. Confirm the complete CPU model code before ordering or publishing model-specific data. Accessories such as corner connectors, wall fasteners, identification tags and dunnage stands are optional unless stated in the quotation.

SOURCES

Cambro Premium stationary vented starter-unit page and Camshelving Specification Guide (2025); Comcater listings.
cambro.com comcater.com.au