

Convotherm mini pro easyTouch Combi Steamer

CMINIPRO6.10 ELECTRIC DIRECT STEAM 6 X 1/1 GN

- Direct steam system
- Cooking methods: Steam, Combi-steam, Convection
- Extra functions:
 - Crisp&Tasty - 5 moisture removal settings
 - HumidifyPro - 5 humidity settings
 - BakePro - 5 levels of traditional baking
 - Controllable fan - 5 speed settings
 - AirFry mode
- easyTouch 7" TFT HiRes glass touch display (capacitive)
- ConvoClean S2L integrated cleaning system
- HygieniCare
- EasyStack - seamless stacking of two appliances
- MaxiCavity - best ratio for cooking chamber volume to appliance size
- Ethernet interface (LAN) and WiFi module (accessory)
- Multipoint core temperature probe
- LED lighting in oven cavity
- Triple glass appliance door and safety catch
- Integrated recoil hand shower
- Right-hinged appliance door



CMINIPRO6.10



CMINIPRO6.10-B

Standard Features

- Cooking methods:
 - Steam (30-130°C) with guaranteed steam saturation
 - Combi-steam (30-250 °C) with automatic moisture control
 - Convection (30-250 °C) with optimised heat transfer
 - Regenerating function
- Operation of easyTouch user interface:
 - 7" TFT HiRes glass touch display (capacitive)
 - Intuitive, image-based user guidance
 - TriColor indicator ring - indicates the current operating status
 - Smooth-action, quick reacting scrolling function
- Climate Management
 - Intelligent Steam Management, HumidityPro, Crisp&Tasty, AirFlowPro
- Quality Management
 - BakePro, AirFry Mode
 - Preheat and cool down function
- Production Management
 - Automatic cooking with Press&Go with up to 399 cooking profiles
 - Integrated cookbook with 7 different categories
 - TrayTimer – load management for different products at the same time
 - TrayView – load management for automatic cooking of different products using Press&Go
 - Favourites management
 - HACCP data storage
 - ecoCooking – energy-save function
 - LT cooking (low temperature cooking) / Delta-T cooking
 - Cook&Hold – cook and hold in one process
 - Autostart – start time preselection
 - Add steam
 - Regenerate - flexible multi-mode rethermalisation function with preselect
 - Manager and crew mode with password protection
 - Energy and water consumption display

- Cleaning Management:
 - ConvoClean S2L unique integrated space saving Solid2Liquid cleaning system with cleaning cartridges - contactless, compact, biodegradable, space saving
 - 3 intensity levels - express, QuickRinse, DryingStep, CareStep & Eco cleaning
 - Safe Cool Down function before cleaning (when door is closed)
 - Cleaning profiles can be set individually as favourites
 - Cleaning scheduler
- HygieniCare:
 - Hygienic handles (door and hand-shower handles)
 - Hygienic Steam function
- Appliance rests flush on the installation surface for improved hygiene
- Side panels and rear panel completely removable for easy service access
- EasyRack - rack for loading US and GN baking trays
- IPX5 rated

Options

- Left-hinged appliance door
- ConvoSense - AI optical food recognition
- Available in various voltages
- SmartDoor with AutoLock, AutoVent, AutoOpen


Accessories

- Stands in various sizes and designs
- KitchenConnect
- EasyStack stacking kit
- Stands in various sizes and designs
- Wall mounting brackets
- mini pro condensation hood with grease filter and front extraction
- WiFi module
- RO Systems available if water quality is outside of specification


Convotharm mini pro easyTouch Combi Steamer

CMINIPRO6.10 ELECTRIC DIRECT STEAM 6 X 1/1 GN


Front view




Side view




View from above with wall clearances



Rear view



Connection points



- A** Water connection, G 3/4"
- C** Drain connection, DN 40 (Ø40 mm)
- D** Electrical connection
- E** Protective equipotential bonding
- F1** Shelf for rinse aid cartridge
- G1** Shelf for cleaning agent cartridge
- H** Air vent connection Ø48mm
- I** Ventilation port Ø48mm

- M** Safety overflow 60mmx20mm
- N** RJ45 Ethernet port
- P** Electrical connection for hood
- R** Control cable connection for hood
- S** USB C port / USB A port
- T** WiFi module - accessory
- U** Mounting point accessories (STK/hood)

DIMENSIONS

Width	498 mm
Depth	793 mm
Height	694 mm
Weight	73 kg

PACKED DIMENSIONS

Width	580 mm
Depth	910 mm
Height	890 mm
Weight	87 kg

Safety clearances*

Right	50 mm
Left	50 mm

Top (for ventilation)** 500 mm

*Heat sources must lie at a minimum distance of 500mm from the appliance.

**Depends on type of air ventilation system and nature of ceiling.

INSTALLATION REQUIREMENTS

For precise installation instructions please refer to the units installation manual

LOADING CAPACITY

Shelf distance	67mm
GN 1/1 flat	6
GN 1/1 (40-65mm deep) 5	
Plates max. Ø26cm	10

Max. loading weight

Per combi steamer	20 kg
Per shelf	5 kg

ELECTRICAL SUPPLY

3N~400-415V~50/60Hz (3P+N+E)

Connected load	7.6kW
	7.7kW

Rated current 10.5A

Fuse 16A

RCD (GFCI), frequency converter Type A

Special voltage options available on request. Connection to an energy optimisation system as standard

WATER CONNECTION

Water supply

G 3/4" permanent connection.

Flow pressure 150 - 600 kPa (1.5 - 6 bar)

Appliance drain

Drain version Permanent connection

(recommended) or funnel waste trap

Type DN40 (Ø40mm)

Slope for waste-water pipe min. 5% (3°)

Water consumption

Ø Consumption for cooking 0-20l/h

Max. water flow rate 10 l/min

WATER QUALITY

Drinking water

(install water treatment system if necessary). Treated tap water for water injection. Untreated tap water for cleaning, recoil hand shower.

Overall hardness 4-20°dh / 70-360ppm

/ 7-35 °TH / 5-25 °e

Properties

pH	6.5 - 8.5
Cl ⁻ (chloride)	max. 60 mg/l
Cl ₂ (free chlorine)	max. 0.2 mg/l
SO ₄ ²⁻ (sulphate)	max. 150 mg/l
Fe (iron)	max. 0.1 mg/l
Electrical conductivity	min 20 µS/cm
SiO ₂ (silicate)	max. 13 mg/l
NH ₂ Cl (monochloramine)	max. 0.2 mg/l
Temperature	max. 40°C

EMISSIONS

Heat output

Latent heat 1400 KJ/h

Sensible heat 1700 KJ/h

Noise during operation max. 70 dBA

MOFFAT®

Australia

moffat.com.au

New Zealand

moffat.co.nz

Australia

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road

Mulgrave, Victoria 3170

Ph 03-9518 3888

Fax 03-9518 3833

vsales@moffat.com.au

www.moffat.com.au

New South Wales

Ph 02-8833 4111

nswsales@moffat.com.au

South Australia

Ph 03-9518 3888

vsales@moffat.com.au

Queensland

Ph 07-3630 8600

qldsales@moffat.com.au

Western Australia

Ph 08-9413 2400

wasaes@moffat.com.au

New Zealand

Moffat Limited

Christchurch

45 Illinois Drive

Izone Business Hub

Rolleston 7675

New Zealand

Telephone +64 3-983 6600

Facsimile +64 3-983 6660

sales@moffat.co.nz

Auckland

Ph +64 9-574 3150

sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd

AN.CON.S.01.25

